



FluxPanel LED

2x4, 4300 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse

2x4, 4300 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse - 107 lm/W

Philips Day-Brite/Philips CFI FluxPanel LED recessed is a highly versatile luminaire designed to provide smooth lighting gradient on the lens surface and ease of installation. Available for use in recessed, suspended,;and surface mount orientation, FluxPanel is ideal for general lighting applications such as open office, schools, healthcare, and retail.

Product data

General Information	
Lamp Source Code	LED
Color Temperature	4000K
CRI	80
Mounting	Recessed Surface Suspended
Operating and Electrical	
Luminaire Input Watts	39
Voltages	120/277/347/UNIV V
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular
Snape	Rectangular

Initial Performance (IEC Compliant)	
Luminaire Lumens	4300
Efficacy	107 lm/W
Product Data	
Order product name	2x4, 4300 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse
Commercial Code	2FXP43L840-4-DS-UNV-DIM
Order code	2FXP43L840-4-DS-UNV-DIM
Catalog Number Description	2x4, 4300 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse
Material Nr. (12NC)	CFI70000752

Datasheet, 2018, April 10 data subject to change