



## FluxPanel LED

## 2x4, 4800 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse

2x4, 4800 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse - 104 lm/W

Philips Day-Brite/Philips CFI FluxPanel LED recessed is a highly versatile luminaire designed to provide smooth lighting gradient on the lens surface and ease of installation. Available for use in recessed, suspended,;and surface mount orientation, FluxPanel is ideal for general lighting applications such as open office, schools, healthcare, and retail.

## Product data

General Information	
General Information	
Lamp Source Code	LED
Color Temperature	3500K
CRI	80
Mounting	Recessed Surface Suspended
Operating and Electrical	
Luminaire Input Watts	47
Voltages	120/277/347/UNIV V
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular

Initial Performance (IEC Compliant)	
Luminaire Lumens	4800
Efficacy	104 lm/W
Product Data	
Order product name	2x4, 4800 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse
Commercial Code	2FXP48L835-4-DS-UNV-DIM
Order code	2FXP48L835-4-DS-UNV-DIM
Catalog Number Description	2x4, 4800 Nominal Delivered Lumens, 80 CRI, 3500K, Diffuse
Material Nr. (12NC)	CFI70000753

Datasheet, 2018, May 15 data subject to change