



# LED Bollard II BCP150/151 – reliable landscape lighting for harmonious city living

## LED Bollard II

People want to create a pleasant atmosphere around their property – something that will catch visitors' attention, make them feel good and want to come back again. They would like to be able to create an appealing ambience with optimized-quality lighting at minimum cost. Combining reliable low-power LEDs and an integrated driver, the robustly designed LED Bollard II delivers an affordable LED lighting solution to meet your landscaping needs.

### Benefits

- Reliable, robust design
- Easy to install and maintenance-free
- Environmentally friendly: no hazardous substances (no mercury, no lead) or UV

### Features

- Low-power white-light LED light source, available in a choice of warm white (3000 K) or neutral white (4000 K)
- Integrated baseplate and driver for easy installation
- Choice of colors for housing (dark grey RAL7043, light grey RAL9006)
- Height 0.5 m or 0.8 m
- Long lifetime of 25,000 hours (70% lumen maintenance @ T<sub>c</sub> = 25°C)
- IP65 protection and IK10 impact resistance

# LED Bollard II

## Application

- Parks and gardens
- Squares, plazas
- Residential areas

## Versions



LED module 15,000 lm



LED module 15,000 lm

Approval and Application	
Mech. impact protection code	IK10
Controls and Dimming	
Dimmable	No
General Information	
CE mark	CE mark
Light source colour	830 warm white
Optical cover/lens type	PC-UV
Driver included	Yes
Flammability mark	F
Lamp family code	LED-LP
Light source replaceable	No
Number of gear units	1 unit
Number of light sources	1
Initial Performance (IEC Compliant)	
Init. Corr. Colour Temperature	3000 K
Init. Colour Rendering Index	>80
Initial luminous flux	150 lm

## Mechanical and Housing

Order Code	Full Product Name	Colour
910403307702	BCP150 LED150/WW PSU 220-240V 7043	Dark Grey
910403308302	BCP151 LED150/WW PSU 220-240V 9006	Aluminium and White

## LED Bollard II

