



Celino – light beam

Celino LED BPS680 C

Celino is a complete luminaire range that reflects the market trend towards miniaturization and architectural integration, while delivering a significant advance in optical performance. Celino features Philips' aluminum micro optic with 3D lamellae, which ensures optimum visual comfort and efficiency in compliance with the latest office-lighting norm (EN 12464-1). Made of natural anodized aluminum, the housing of Celino is a mere 71 mm wide and has die-cast-aluminum end caps. The design allows multiple luminaires to be connected in a line arrangement. Celino is available as a full range – suspended, surface-mounted, free-standing, recessed and wall-mounted, with a choice of TL5, TL5 Eco or LED light sources – for maximum freedom in application.

Benefits

- Complete luminaire range that reflects the trend to miniaturization and architectural integration
- Excellent optical performance using optical covers for optimum visual comfort and efficiency

Features

- Inspiring: aesthetical and novel design with visually better ceiling integration
- Comfort: spacious and pleasant environment with comfortable lighting appearance
- Efficient: high efficacy achieved with optics innovation

Application

- Open plan office
- Meeting room
- Reception area
- Cell office
- Lounge

Specifications

Type	BPS680	Power	30 W (for LED24)
Light source	Non-replaceable LED module		52 W (for LED48)

Celino LED BPS680 C

Luminous flux	1800-4200 lm (dependant on configuration)
Correlated Color	4000 K
Temperature	
Color Rendering Index	80
Maintenance of lumen output - L90	25,000 hours at 25°C
Maintenance of lumen output - L70	50,000 hours at 25°C
Operating temperature range	25°C
Driver	
	Built-in
	PSU: fixed output driver, PSD: dimmable driver
Mains voltage	220-240 V / 50-60 Hz
Dimming	DALI

Material	
	Housing: natural anodized aluminum
	End caps: die-cast aluminum
Color	
	Aluminum (ALU)
Optical cover	
	OLC micro-lens optic in polycarbonate cover (MLO-PC)
	Opal optic in polycarbonate cover (O-PC)
	Linear lens array optic in polycarbonate cover (LIN-PC)
Installation	
	Individual, suspended mounting with a set of two single steel-wire suspensions, with metal-like power cord, and ceiling caps
	Fast fine adjustment with clutch device
	Installation without removing light source and optical cover
Remarks	
	W7L120: indicating same size as Celino conventional TL5 1-lamp version
	W17L120: indicating same size as Celino conventional TL5 2-lamps version

Versions



BPS680 C LED24

Product details



Celino LED BPS680 C

Product details



Application Conditions

Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

Approval and Application

Mech. impact protection code	IK03
Ingress protection code	IP20

Operating and Electrical

Input Voltage	220-240 V
---------------	-----------

General Information

Beam angle of light source	120 °
CE mark	-
Protection class IEC	Safety class I (I)
Optical cover/lens type	O-PC
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Glow-wire test	650/30
Lamp family code	LED24
Light source replaceable	No
Number of gear units	1 unit
Optic type	WB

Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM <4
Init. Corr. Colour Temperature	4000 K
Init. Colour Rendering Index	>80
Initial LED luminaire efficacy	71.000 lm/W
Initial luminous flux	2100 lm
Luminous flux tolerance	+/-7.5%

Mechanical and Housing

Colour	Silver
Geometry	W7L120

Application Conditions

Order Code	Full Product Name	Maximum dim level
911401540101	BPS680 C LED24/840 PSD W7L120 O-PC	10%
911401540501	BPS680 C LED24/840 PSU W7L120 O-PC	-

Controls and Dimming

Celino LED BPS680 C

Order Code	Full Product Name	Dimmable
911401540101	BPS680 C LED24/840 PSD W7L120 O-PC	Yes

Order Code	Full Product Name	Dimmable
911401540501	BPS680 C LED24/840 PSU W7L120 O-PC	No

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial input power
911401540101	BPS680 C LED24/840 PSD W7L120 O-PC	30 W

Order Code	Full Product Name	Initial input power
911401540501	BPS680 C LED24/840 PSU W7L120 O-PC	32 W

