



# Product Description

## MASTER PL-C 2 Pin

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

### Benefits

- Optimal light performance for short or long operation per switch-on
- Optimal light performance for short or long operation per switch on
- Multiple light color choice
- Long life and sustainable light output
- Good color rendering (CRI  $\geq$  80)

### Features

- 2-pin base with a housing incorporating the special instant starter
- 2-pin base with a housing incorporating the special instant starter and capacitor
- Fluorescent tri-phosphor technology
- Lamp characteristics are influenced by operating conditions and control gear used
- Low light depreciation over lamp life
- Dimming is not possible

### Application

- Designed for general or supplementary lighting in professional or home environments
- Designed for general or supplementary lighting in professional or home environments
- Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps
- Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps

# MASTER PL-C 2 Pin

## Warnings and Safety

- Use only with electromagnetic control gear
- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

## Versions



LPPR PLC2P 13W




LPPR PLC2P 18W



LPPR PLC2P 26W

## Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
MASTER PL-C 18W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
MASTER PL-C 26W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm

MASTER PL-C 2 Pin

Light Technical	
Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Controls and Dimming	
Dimmable	No
Approval and Application	
Mercury (Hg) Content (Max)	1.4 mg
Mercury (Hg) Content (Nom)	1.4 mg

General Information

Order Code	Full Product Name	Cap-Base
927904884040	MASTER PL-C 13W/840/2P 1CT/5X10BOX	G24D-1
927905784040	MASTER PL-C 18W/840/2P 1CT/5X10BOX	G24D-2

Order Code	Full Product Name	Cap-Base
927906184040	MASTER PL-C 26W/840/2P 1CT/5X10BOX	G24D-3

Light Technical

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)
927904884040	MASTER PL-C 13W/840/2P 1CT/5X10BOX	69 lm/W
927905784040	MASTER PL-C 18W/840/2P 1CT/5X10BOX	67 lm/W

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)
927906184040	MASTER PL-C 26W/840/2P 1CT/ 5X10BOX	68 lm/W

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)
927904884040	MASTER PL-C 13W/840/2P 1CT/5X10BOX	0.170 A
927905784040	MASTER PL-C 18W/840/2P 1CT/5X10BOX	0.230 A

Order Code	Full Product Name	Lamp Current (Nom)
927906184040	MASTER PL-C 26W/840/2P 1CT/5X10BOX	0.335 A

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/ 1000 h
927904884040	MASTER PL-C 13W/840/2P 1CT/ 5X10BOX	14 kWh
927905784040	MASTER PL-C 18W/840/2P 1CT/ 5X10BOX	19 kWh

Order Code	Full Product Name	Energy Consumption kWh/ 1000 h
927906184040	MASTER PL-C 26W/840/2P 1CT/ 5X10BOX	27 kWh

## MASTER PL-C 2 Pin

