# 產品說明

## MASTER PL-C 4 Pin

省電型精巧螢光燈管。精巧型長電弧低壓水銀放電燈管。套管內含 4 個平行細長螢光燈管

### 优点

- 每次開燈，無論時間長短，都能展現最佳的照明狀態
- 使用壽命長，光量輸出不衰減

### 特点

- 4 接腳基座，無點燈器和電容
- 燈管特性取決於操作條件與採用何種控制裝置
- 可調光

### 应用

- 適用於專業或居家環境的一般或輔助照明
- 嵌入式或吸頂式崁燈、壁燈、桌燈和吊燈

### 安全提示

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

# MASTER PL-C 4 Pin

## Versions

LPPR PLC4P 13W

## 二维绘图




| Product | D (max) | D1 (max) | A (max) | B (max) | C (max) |
|---|---|---|---|---|---|
| MASTER PL-C 13W/827/4P 1CT/5X10BOX | 27.1 mm | 27.1 mm | 97.5 mm | 117.0 mm | 131.9 mm |
| MASTER PL-C 13W/840/4P 1CT/5X10BOX | 27.1 mm | 27.1 mm | 97.5 mm | 117.0 mm | 131.9 mm |
| MASTER PL-C 26W/830/4P 1CT/5X10BOX | 27.1 mm | 27.1 mm | 130.5 mm | 149.0 mm | 163.9 mm |
| MASTER PL-C 26W/840/4P 1CT/5X10BOX | 27.1 mm | 27.1 mm | 130.5 mm | 149.0 mm | 163.9 mm |

| | |
|---|---|
| **照明技術** | |
| 演色性指數 (CRI) | 82 |
| **控制與調光** | |
| 可調光 | 是 |
| **認證與應用** | |
| 汞 (Hg) 含量 (標稱) | 1.4 mg |

## 一般資訊

| Order Code | Full Product Name | 燈座基底 | 標稱使用壽命 |
|---|---|---|---|
| 927907182701 | MASTER PL-C 13W/827/4P 1CT/5X10BOX | G24q-1 | - |
| 927907184002 | MASTER PL-C 13W/840/4P 1CT/5X10BOX | G24q-1 | - |

| Order Code | Full Product Name | 燈座基底 | 標稱使用壽命 |
|---|---|---|---|
| 927907383001 | MASTER PL-C 26W/830/4P 1CT/5X10BOX | G24q-3 | 10,000 h |
| 927907384002 | MASTER PL-C 26W/840/4P 1CT/5X10BOX | G24q-3 | 10,000 h |

## 照明技術

| Order Code | Full Product Name | 色彩名稱 | 相關色彩溫度 (規範) | 光效 (額定) (標準) | 光通量 |
|---|---|---|---|---|---|
| 927907182701 | MASTER PL-C 13W/827/4P 1CT/5X10BOX | 白熾白色 | 2700 K | 69 lm/W | 925 lm |
| 927907184002 | MASTER PL-C 13W/840/4P 1CT/5X10BOX | 冷白光 (CW) | 4000 K | 69 lm/W | 925 lm |

| Order Code | Full Product Name | 色彩名稱 | 相關色彩溫度 (規範) | 光效 (額定) (標準) | 光通量 |
|---|---|---|---|---|---|
| 927907383001 | MASTER PL-C 26W/830/4P 1CT/5X10BOX | 暖白光 (WW) | 3000 K | 67 lm/W | 1,800 lm |

# MASTER PL-C 4 Pin

| Order Code | Full Product Name | 色彩名稱 | 相關色彩溫度 (規範) | 光效 (額定) (標準) | 光通量 |
|---|---|---|---|---|---|
| 927907384002 | MASTER PL-C 26W/840/4P 1CT/5X10BOX | 冷白光 (CW) | 4000 K | 67 lm/W | 1,800 lm |

## 運轉與電力

| Order Code | Full Product Name | 燈具電流 (標稱) | 耗電量 |
|---|---|---|---|
| 927907182701 | MASTER PL-C 13W/827/4P 1CT/5X10BOX | 0.170 A | 13.0 W |
| 927907184002 | MASTER PL-C 13W/840/4P 1CT/5X10BOX | 0.170 A | 13.0 W |

| Order Code | Full Product Name | 燈具電流 (標稱) | 耗電量 |
|---|---|---|---|
| 927907383001 | MASTER PL-C 26W/830/4P 1CT/5X10BOX | 0.335 A | 26.0 W |
| 927907384002 | MASTER PL-C 26W/840/4P 1CT/5X10BOX | 0.335 A | 26.0 W |

## 認證與應用

| Order Code | Full Product Name | 能源消耗 kWh/1000 h |
|---|---|---|
| 927907182701 | MASTER PL-C 13W/827/4P 1CT/5X10BOX | 15 kWh |
| 927907184002 | MASTER PL-C 13W/840/4P 1CT/5X10BOX | 15 kWh |

| Order Code | Full Product Name | 能源消耗 kWh/1000 h |
|---|---|---|
| 927907383001 | MASTER PL-C 26W/830/4P 1CT/5X10BOX | 29 kWh |
| 927907384002 | MASTER PL-C 26W/840/4P 1CT/5X10BOX | 29 kWh |

© 2023 Signify Holding 保留一切權利。 Signify 不對本協議所含括資訊之準確性及完整性提供任何聲明或保證，對以此訊息為依據採取的任何行動亦概不負責。 除非 Signify 同意，本文件提及之資訊並非任何商業合約，亦不構成任何報價或合約任一部分。 其他所有商標均為 Signify Holding 或個別擁有人所有財產。