



The alternative!

PL-Q 4 Pin

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 4-pin version is designed for operation on electronic gear.

Benefits

- Low built-in height
- Multiple light color choice
- Good color rendering (CRI >80)
- Dimming possible down to 10%

Features

- 4-pin base
- Fluorescent tri-phosphor technology

Application

- Ideal for applications such as corridors, toilets, stairwells and reception areas


PL-Q 4 Pin

Versions



GR10q, 4P

Dimensional drawing



Product	U (max)	D (max)	D1 (max)	C (max)	C1 (max)	F (max)	E (max)
PL-Q 21W/ 830/4P 1CT/10 BOX	40 mm	15 mm	27.5 mm	141 mm	49 mm	41 mm	138 mm
PL-Q 28W/ 835/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 16W/ 830/4P 1CT/ 10BOX	40 mm	13.7 mm	27.5 mm	138 mm	49 mm	40.5 mm	135 mm
PL-Q 38W/ 840/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 28W/ 827/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 28W/ 840/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 28W/ 830/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 38W/ 835/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 16W/ 827/4P 1CT/ 10BOX	40 mm	13.7 mm	27.5 mm	138 mm	49 mm	40.5 mm	135 mm
PL-Q 38W/ 830/4P 1CT/ 10BOX	46.5 mm	18.9 mm	33 mm	203 mm	76 mm	41 mm	200 mm
PL-Q 16W/ 835/4P 1CT/ 10BOX	40 mm	13.7 mm	27.5 mm	138 mm	49 mm	40.5 mm	135 mm

PL-Q 4 Pin

Controls and Dimming

Dimmable	Yes
----------	-----

General Information

Cap-Base	GR10Q
LSF Preheat 16000 h Rated	22 %
LSF Preheat 20000 h Rated	4 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	95 %
LSF Preheat 8000 h Rated	89 %

Light Technical

Color Rendering Index (Nom)	82
LLMF 2000 h Rated	90 %
LLMF 8000 h Rated	80 %

Temperature

Design Temperature (Nom)	25 °C
--------------------------	-------

Approval and Application

Order Code	Full Product Name	Energy	Energy	Mercury	Mercury (Hg) Content (Nom)
		Consumption kWh/ 1000 h	Efficiency Label (EEL)	Content (Max)	
927938383040	PL-Q 21W/830/4P 1CT/10 BOX	23 kWh	-	3.0 mg	-
927939182740	PL-Q 16W/827/4P 1CT/ 10BOX	18 kWh	A	-	4 mg
927939183040	PL-Q 16W/830/4P 1CT/ 10BOX	18 kWh	A	-	4 mg
927939183540	PL-Q 16W/835/4P 1CT/ 10BOX	18 kWh	A	-	4 mg
927939382740	PL-Q 28W/827/4P 1CT/ 10BOX	31 kWh	A	-	4 mg
927939383040	PL-Q 28W/830/4P 1CT/ 10BOX	31 kWh	A	-	4 mg
927939383540	PL-Q 28W/835/4P 1CT/ 10BOX	31 kWh	A	-	4 mg
927939384040	PL-Q 28W/840/4P 1CT/ 10BOX	31 kWh	A	-	4 mg
927939483040	PL-Q 38W/830/4P 1CT/ 10BOX	42 kWh	A	-	4 mg
927939483540	PL-Q 38W/835/4P 1CT/ 10BOX	42 kWh	A	-	4 mg
927939484040	PL-Q 38W/840/4P 1CT/ 10BOX	42 kWh	A	-	4 mg

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927938383040	PL-Q 21W/830/4P 1CT/10 BOX	0.260 A	21.0 W
927939182740	PL-Q 16W/827/4P 1CT/10BOX	0.195 A	16.0 W
927939183040	PL-Q 16W/830/4P 1CT/10BOX	0.195 A	16.0 W
927939183540	PL-Q 16W/835/4P 1CT/10BOX	0.195 A	16.0 W
927939382740	PL-Q 28W/827/4P 1CT/10BOX	0.320 A	24.8 W
927939383040	PL-Q 28W/830/4P 1CT/10BOX	0.320 A	24.8 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927939383540	PL-Q 28W/835/4P 1CT/10BOX	0.320 A	24.8 W
927939384040	PL-Q 28W/840/4P 1CT/10BOX	0.320 A	24.8 W
927939483040	PL-Q 38W/830/4P 1CT/10BOX	0.430 A	35.5 W
927939483540	PL-Q 38W/835/4P 1CT/10BOX	0.430 A	35.5 W
927939484040	PL-Q 38W/840/4P 1CT/10BOX	0.430 A	35.5 W

General Information

Order Code	Full Product Name	Life To 50% Failures Preheat (Nom)
927938383040	PL-Q 21W/830/4P 1CT/10 BOX	13000 h
927939182740	PL-Q 16W/827/4P 1CT/10BOX	13000 h
927939183040	PL-Q 16W/830/4P 1CT/10BOX	13000 h
927939183540	PL-Q 16W/835/4P 1CT/10BOX	13000 h
927939382740	PL-Q 28W/827/4P 1CT/10BOX	13000 h
927939383040	PL-Q 28W/830/4P 1CT/10BOX	13000 h

Order Code	Full Product Name	Life To 50% Failures Preheat (Nom)
927939383540	PL-Q 28W/835/4P 1CT/10BOX	13000 h
927939384040	PL-Q 28W/840/4P 1CT/10BOX	13000 h
927939483040	PL-Q 38W/830/4P 1CT/10BOX	12000 h
927939483540	PL-Q 38W/835/4P 1CT/10BOX	13000 h
927939484040	PL-Q 38W/840/4P 1CT/10BOX	13000 h

Light Technical (1/2)

PL-Q 4 Pin

Order Code	Full Product Name	Color Code	Color Designation	Correlated	LLMF
				Color Temperature (Nom)	12000 h Rated
927938383040	PL-Q 21W/830/4P 1CT/10 BOX	830	Warm White (WW)	3000 K	69 %
927939182740	PL-Q 16W/827/4P 1CT/10BOX	827	Incandescent White	2700 K	79 %
927939183040	PL-Q 16W/830/4P 1CT/10BOX	830	Warm White (WW)	3000 K	69 %
927939183540	PL-Q 16W/835/4P 1CT/10BOX	835	White (WH)	3500 K	79 %
927939382740	PL-Q 28W/827/4P 1CT/10BOX	827	Incandescent White	2700 K	79 %
927939383040	PL-Q 28W/830/4P 1CT/10BOX	830	Warm White (WW)	3000 K	79 %

Order Code	Full Product Name	Color Code	Color Designation	Correlated	LLMF
				Color Temperature (Nom)	12000 h Rated
927939383540	PL-Q 28W/835/4P 1CT/10BOX	835	White (WH)	3500 K	79 %
927939384040	PL-Q 28W/840/4P 1CT/10BOX	840	Cool White (CW)	4000 K	79 %
927939483040	PL-Q 38W/830/4P 1CT/10BOX	830	Warm White (WW)	3000 K	79 %
927939483540	PL-Q 38W/835/4P 1CT/10BOX	835	White (WH)	3500 K	79 %
927939484040	PL-Q 38W/840/4P 1CT/10BOX	840	Cool White (CW)	4000 K	79 %

Light Technical (2/2)

Order Code	Full Product Name	LLMF 16000 h	LLMF 20000 h	LLMF 4000 h	LLMF 6000 h	Luminous Efficacy	Luminous Flux	Luminous Flux
		Rated	Rated	Rated	Rated	(rated) (Nom)	(Nom)	(Rated) (Nom)
927938383040	PL-Q 21W/830/4P 1CT/10 BOX	-	-	83 %	78 %	66.6 lm/W	1400 lm	1400 lm
927939182740	PL-Q 16W/827/4P 1CT/10BOX	78 %	78 %	86 %	83 %	66.6 lm/W	1050 lm	1050 lm
927939183040	PL-Q 16W/830/4P 1CT/10BOX	-	-	83 %	78 %	66.6 lm/W	1050 lm	1050 lm
927939183540	PL-Q 16W/835/4P 1CT/10BOX	78 %	78 %	86 %	83 %	66.6 lm/W	1050 lm	1050 lm
927939382740	PL-Q 28W/827/4P 1CT/10BOX	78 %	78 %	86 %	83 %	73.2 lm/W	2050 lm	2050 lm
927939383040	PL-Q 28W/830/4P 1CT/10BOX	78 %	78 %	86 %	83 %	73.2 lm/W	2050 lm	2050 lm
927939383540	PL-Q 28W/835/4P 1CT/10BOX	78 %	78 %	86 %	83 %	73.2 lm/W	2050 lm	2050 lm
927939384040	PL-Q 28W/840/4P 1CT/10BOX	78 %	78 %	86 %	83 %	73.2 lm/W	2050 lm	2050 lm
927939483040	PL-Q 38W/830/4P 1CT/10BOX	78 %	78 %	86 %	83 %	75 lm/W	2850 lm	2850 lm
927939483540	PL-Q 38W/835/4P 1CT/10BOX	78 %	78 %	86 %	83 %	75 lm/W	2850 lm	2850 lm
927939484040	PL-Q 38W/840/4P 1CT/10BOX	78 %	78 %	86 %	83 %	75 lm/W	2850 lm	2850 lm

