



Widest product range in the world!

MASTER PL-T 4 Pin

MASTER PL-T is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Benefits

- Optimal light performance for short or long operation per switch-on
- Substantially more light (about 15% more) per light point than with other similar shapes
- Multiple light color choice
- Good color rendering (CRI >80)
- Dimming possible down to 10%

Features

- 4-pin base
- Philips' bridging technology applied
- Fluorescent tri-phosphor technology
- Low light depreciation over lamp life
- Fast light run-up

Application

- Designed for general or supplementary lighting in professional and semi-professional environments
- Ideal for use in recessed or surface mounted downlighters, wall units, outdoor lighting
- First choice for short switching cycles, emergency lighting and deep dimming

MASTER PL-T 4 Pin

Versions



18W, GX24q-2, 4P



26W, GX24q-3, 4P



32W, GX24q-3, 4P





42W, GX24q-4, 4P



57W, GX24q-5, 4P

Dimensional drawing





Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 57W/840/4P 1CT/ 5X10BOX	41.0 mm	157.7 mm	182.0 mm	197.7 mm
MASTER PL-T 57W/830/4P 1CT/ 5X10BOX	41.0 mm	157.7 mm	182.0 mm	197.7 mm

Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 42W/840/4P 1CT/ 5X10BOX	41.0 mm	120.7 mm	145.0 mm	160.7 mm
MASTER PL-T 42W/830/4P 1CT/ 5X10BOX	41.0 mm	120.7 mm	145.0 mm	160.7 mm
MASTER PL-T 42W/827/4P 1CT/ 5X10BOX	41.0 mm	120.7 mm	145.0 mm	160.7 mm

MASTER PL-T 4 Pin

Dimensional drawing



Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 32W/840/4P 1CT/ 5X10BOX	41.0 mm	98.7 mm	123.0 mm	138.7 mm
MASTER PL-T 32W/830/4P 1CT/ 5X10BOX	41.0 mm	98.7 mm	123.0 mm	138.7 mm
MASTER PL-T 32W/827/4P 1CT/ 5X10BOX	41.0 mm	98.7 mm	123.0 mm	138.7 mm
MASTER PL-T 26W/840/4P 1CT/ 5X10BOX	41.0 mm	86.7 mm	111.0 mm	126.7 mm
MASTER PL-T 26W/830/4P 1CT/ 5X10BOX	41.0 mm	86.7 mm	111.0 mm	126.7 mm
MASTER PL-T 26W/827/4P 1CT/ 5X10BOX	41.0 mm	86.7 mm	111.0 mm	126.7 mm

Product	D (max)	A (max)	B (max)	C (max)
MASTER PL-T 18W/840/4P 1CT/ 5X10BOX	41.0 mm	71.7 mm	96.0 mm	111.7 mm
MASTER PL-T 18W/830/4P 1CT/ 5X10BOX	41.0 mm	71.7 mm	96.0 mm	111.7 mm
MASTER PL-T 18W/827/4P 1CT/ 5X10BOX	41.0 mm	71.7 mm	96.0 mm	111.7 mm

Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	1.4 mg

Controls and Dimming

Dimmable	Yes
----------	-----

General Information

Life To 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %

Light Technical

LLMF 12000 h Rated	81 %
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	86 %
LLMF 8000 h Rated	84 %

Temperature

Design Temperature (Nom)	28 °C
--------------------------	-------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
927914482771	MASTER PL-T 18W/827/4P 1CT/5X10BOX	20 kWh
927914483071	MASTER PL-T 18W/830/4P 1CT/5X10BOX	20 kWh
927914484071	MASTER PL-T 18W/840/4P 1CT/5X10BOX	20 kWh
927914682771	MASTER PL-T 26W/827/4P 1CT/5X10BOX	29 kWh
927914683071	MASTER PL-T 26W/830/4P 1CT/5X10BOX	29 kWh
927914684071	MASTER PL-T 26W/840/4P 1CT/5X10BOX	29 kWh
927914782771	MASTER PL-T 32W/827/4P 1CT/5X10BOX	35 kWh
927914783071	MASTER PL-T 32W/830/4P 1CT/5X10BOX	35 kWh
927914784071	MASTER PL-T 32W/840/4P 1CT/5X10BOX	35 kWh
927914882771	MASTER PL-T 42W/827/4P 1CT/5X10BOX	45 kWh
927914883071	MASTER PL-T 42W/830/4P 1CT/5X10BOX	45 kWh
927914884071	MASTER PL-T 42W/840/4P 1CT/5X10BOX	45 kWh
927914983071	MASTER PL-T 57W/830/4P 1CT/5X10BOX	59 kWh
927914984071	MASTER PL-T 57W/840/4P 1CT/5X10BOX	59 kWh

Operating and Electrical

MASTER PL-T 4 Pin

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927914482771	MASTER PL-T 18W/827/4P 1CT/5X10BOX	0.225 A	16.5 W
927914483071	MASTER PL-T 18W/830/4P 1CT/5X10BOX	0.225 A	16.5 W
927914484071	MASTER PL-T 18W/840/4P 1CT/5X10BOX	0.210 A	16.5 W
927914682771	MASTER PL-T 26W/827/4P 1CT/5X10BOX	0.300 A	24.0 W
927914683071	MASTER PL-T 26W/830/4P 1CT/5X10BOX	0.300 A	24.0 W
927914684071	MASTER PL-T 26W/840/4P 1CT/5X10BOX	0.300 A	24.0 W
927914782771	MASTER PL-T 32W/827/4P 1CT/5X10BOX	0.320 A	32.0 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927914783071	MASTER PL-T 32W/830/4P 1CT/5X10BOX	0.320 A	32.0 W
927914784071	MASTER PL-T 32W/840/4P 1CT/5X10BOX	0.320 A	32.0 W
927914882771	MASTER PL-T 42W/827/4P 1CT/5X10BOX	0.320 A	41.0 W
927914883071	MASTER PL-T 42W/830/4P 1CT/5X10BOX	0.320 A	41.0 W
927914884071	MASTER PL-T 42W/840/4P 1CT/5X10BOX	0.320 A	41.0 W
927914983071	MASTER PL-T 57W/830/4P 1CT/5X10BOX	0.325 A	56.0 W
927914984071	MASTER PL-T 57W/840/4P 1CT/5X10BOX	0.325 A	56.0 W

General Information

Order Code	Full Product Name	Cap-Base
927914482771	MASTER PL-T 18W/827/4P 1CT/5X10BOX	GX24Q-2
927914483071	MASTER PL-T 18W/830/4P 1CT/5X10BOX	GX24Q-2
927914484071	MASTER PL-T 18W/840/4P 1CT/5X10BOX	GX24Q-2
927914682771	MASTER PL-T 26W/827/4P 1CT/5X10BOX	GX24Q-3
927914683071	MASTER PL-T 26W/830/4P 1CT/5X10BOX	GX24Q-3
927914684071	MASTER PL-T 26W/840/4P 1CT/5X10BOX	GX24Q-3
927914782771	MASTER PL-T 32W/827/4P 1CT/5X10BOX	GX24Q-3

Order Code	Full Product Name	Cap-Base
927914783071	MASTER PL-T 32W/830/4P 1CT/5X10BOX	GX24Q-3
927914784071	MASTER PL-T 32W/840/4P 1CT/5X10BOX	GX24Q-3
927914882771	MASTER PL-T 42W/827/4P 1CT/5X10BOX	GX24Q-4
927914883071	MASTER PL-T 42W/830/4P 1CT/5X10BOX	GX24Q-4
927914884071	MASTER PL-T 42W/840/4P 1CT/5X10BOX	GX24Q-4
927914983071	MASTER PL-T 57W/830/4P 1CT/5X10BOX	GX24Q-5
927914984071	MASTER PL-T 57W/840/4P 1CT/5X10BOX	GX24Q-5

Light Technical (1/2)

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927914482771	MASTER PL-T 18W/827/4P 1CT/5X10BOX	827	Incandescent White	2700 K	82
927914483071	MASTER PL-T 18W/830/4P 1CT/5X10BOX	830	Warm White (WW)	3000 K	>80
927914484071	MASTER PL-T 18W/840/4P 1CT/5X10BOX	840	Cool White (CW)	4000 K	82
927914682771	MASTER PL-T 26W/827/4P 1CT/5X10BOX	827	Incandescent White	2700 K	82
927914683071	MASTER PL-T 26W/830/4P 1CT/5X10BOX	830	Warm White (WW)	3000 K	>80
927914684071	MASTER PL-T 26W/840/4P 1CT/5X10BOX	840	Cool White (CW)	4000 K	82

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927914782771	MASTER PL-T 32W/827/4P 1CT/5X10BOX	827	Incandescent White	2700 K	82
927914783071	MASTER PL-T 32W/830/4P 1CT/5X10BOX	830	Warm White (WW)	3000 K	>80
927914784071	MASTER PL-T 32W/840/4P 1CT/5X10BOX	840	Cool White (CW)	4000 K	82
927914882771	MASTER PL-T 42W/827/4P 1CT/5X10BOX	827	Incandescent White	2700 K	82
927914883071	MASTER PL-T 42W/830/4P 1CT/5X10BOX	830	Warm White (WW)	3000 K	>80
927914884071	MASTER PL-T 42W/840/4P 1CT/5X10BOX	840	Cool White (CW)	4000 K	82

MASTER PL-T 4 Pin

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927914983071	MASTER PL-T 57W/830/4P 1CT/5X10BOX	830	Warm White (WW)	3000 K	>80

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927914984071	MASTER PL-T 57W/840/4P 1CT/5X10BOX	840	Cool White (CW)	4000 K	82

Light Technical (2/2)

Order Code	Full Product Name	Luminous Efficacy (rated) (Min)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927914482771	MASTER PL-T 18W/827/4P 1CT/5X10BOX	67 lm/W	1200 lm	1200 lm
927914483071	MASTER PL-T 18W/830/4P 1CT/5X10BOX	67 lm/W	1200 lm	1200 lm
927914484071	MASTER PL-T 18W/840/4P 1CT/5X10BOX	67 lm/W	1200 lm	1200 lm
927914682771	MASTER PL-T 26W/827/4P 1CT/5X10BOX	66 lm/W	1800 lm	1725 lm
927914683071	MASTER PL-T 26W/830/4P 1CT/5X10BOX	66 lm/W	1800 lm	1725 lm
927914684071	MASTER PL-T 26W/840/4P 1CT/5X10BOX	66 lm/W	1800 lm	1725 lm
927914782771	MASTER PL-T 32W/827/4P 1CT/5X10BOX	75 lm/W	2400 lm	2400 lm

Order Code	Full Product Name	Luminous Efficacy (rated) (Min)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927914783071	MASTER PL-T 32W/830/4P 1CT/5X10BOX	75 lm/W	2400 lm	2400 lm
927914784071	MASTER PL-T 32W/840/4P 1CT/5X10BOX	75 lm/W	2400 lm	2400 lm
927914882771	MASTER PL-T 42W/827/4P 1CT/5X10BOX	74 lm/W	3200 lm	3050 lm
927914883071	MASTER PL-T 42W/830/4P 1CT/5X10BOX	74 lm/W	3200 lm	3050 lm
927914884071	MASTER PL-T 42W/840/4P 1CT/5X10BOX	74 lm/W	3200 lm	3050 lm
927914983071	MASTER PL-T 57W/830/4P 1CT/5X10BOX	75 lm/W	4300 lm	4200 lm
927914984071	MASTER PL-T 57W/840/4P 1CT/5X10BOX	75 lm/W	4300 lm	4200 lm

