



Spreadhead spiral shape energy saving products, preferred by over 90% of consumers

Tornado T3

Tornado has outstanding brightness which makes your colors appear more Vivid. It allows easy replacement of high wattage of incandescent lamps.

Benefits

- Outstanding brightness & Vivid Colors
- Flicker-Free start & Fast run up
- Save your money with long life-time and high energy efficiency compare to incandescent lamp

Features

- Long-Life and Energy saving alternative to Incandescent lamps
- Fast Run-up
- Recommended ambient temperature range to ensure almost constant light output (>90%): 0 and + 50°C

Application

- Replacement of incandescent lamps in both professional and home applications
- Enclosed fixtures required for outdoor applications
- Not suitable for use with dimmers or electronic devices

Tornado T3


Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Versions



Dimensional drawing



Product	C (max)	D (max)	F (max)
Tornado T3 32W WW E27 220-240V 1PF/6	152.5 mm	74 mm	61 mm
Tornado T3 32W CDL E27 220-240V 1PF/6	74 mm	152.5 mm	61 mm

Tornado T3

Approval and Application	
Energy Consumption kWh/1000 h	32 kWh
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Max)	2.5 mg
Mercury (Hg) Content (Nom)	2 mg
Controls and Dimming	
Dimmable	No
Operating and Electrical	
Lamp Current (Nom)	140 mA
Input Frequency	50 or 60 Hz
Voltage (Nom)	220-240 V
Power (Rated) (Nom)	32.0 W
Starting Time (Nom)	0.3 s
Warm Up Time To 60% Light (Max)	40 s
Warm Up Time To 60% Light (Min)	5 s
General Information	
Cap-Base	E27
Rated Lifetime (Hours)	8000 h
Switching Cycle	8,000X
Light Technical	
Colour Rendering Index (Nom)	80
Lumen Maintenance 2000 h (Nom)	88 %
Mechanical and Housing	
Bulb Shape	Spiral

General Information

Order Code	Full Product Name	Nominal Lifetime (Nom)
87628400	Tornado T3 32W WW E27 220-240V 1PF/6	-
87630700	Tornado T3 32W CDL E27 220-240V 1PF/6	8000 h

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity		Colour Code	Colour Designation
		Coordinate X (Nom)	Coordinate Y (Nom)		
87628400	Tornado T3 32W WW E27 220-240V 1PF/6	463	420	827	Warm White (WW)

Order Code	Full Product Name	Chromaticity		Colour Code	Colour Designation
		Coordinate X (Nom)	Coordinate Y (Nom)		
87630700	Tornado T3 32W CDL E27 220-240V 1PF/6	313	337	865	Cool Daylight

Light Technical (2/2)

Order Code	Full Product Name	Correlated Colour		
		Temperature (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
87628400	Tornado T3 32W WW E27 220-240V 1PF/6	2700 K	2255 lm	2255 lm

Order Code	Full Product Name	Correlated Colour		
		Temperature (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
87630700	Tornado T3 32W CDL E27 220-240V 1PF/6	6500 K	2160 lm	2160 lm

Tornado T3

