



Simply irresistable. Superior light quality from start to finish

MasterColor CDM-T T6 Elite

The Elite family is at the very top of the MasterColor CDM range, and gives a unique combination of unbeatable light quality and consistent performance over lifetime, while keeping running costs low. MasterColor metal halide lamps deliver consistent white light and higher color rendering than any standard metal halide source for architectural lighting.

Benefits

- · Energy-efficient alternative to incandescent/halogen.
- · Improved lumen maintenance over standard metal halide.
- · Lamp to lamp color consistency over life.

Features

- $\boldsymbol{\cdot}$ Lamp to lamp color consistency over life.
- · High lamp efficacy.
- · Lamp to lamp color consistency over life.
- Lamps feature FadeBlock, an integrated UV blocking medium for reduced fading of fabrics and paintings.
- · Available in 39W, 70W, 100W and 150W versions T6 shape.

Application

• Ideal for retail display lighting, general and indirect lighting, wall washing and fiberoptic systems

MasterColor CDM-T T6 Elite

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- · Lamp contains mercury.
- · Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Versions






G12 T 19mm Clear CCT of 3000K

G12 T 19mm Clear CCT of 3000K

Dimensional drawing



Product	D (max)	0	L (min)	L (max)	L	C (max)
MASTERColor CDM-T	13/16 in	3/16 in	2-3/16 in	2-1/4 in	2-1/4 in	4-1/16 in
Elite 35W/930 G12 1CT						
MASTERColor CDM-T	13/16 in	5/16 in	2-3/16 in	2-1/4 in	2-1/4 in	4-1/16 in
Elite 70W/930 G12 1CT						

MasterColor CDM-T T6 Elite

Dimmable	No
Operating and electrical	
Voltage (Max)	90 V
Voltage (Nom)	85 V
Re-Ignition Time (Min) (Max)	15 min
General information	
Cap-Base	G12
Life To 10% Failures (Nom)	14000 h
Life To 20% Failures (Nom)	16000 h
Life To 50% Failures (Nom)	20000 h
Life To 5% Failures (Nom)	12000 h
Operating Position	Universal
Luminaire design requirements	
Bulb Temperature (Max)	932 °F
Light technical	
Chromaticity Coordinate X (Nom)	0.435
Chromaticity Coordinate X (Nom) Color Code	930
Chromaticity Coordinate X (Nom) Color Code Color Designation	930 Warm White (WW
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom)	930 Warm White (WW 3000 K
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min)	930 Warm White (WW 3000 K
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom)	930 Warm White (WW 3000 K 87
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom) Lumen Maintenance 10000 h (Nom)	930 Warm White (WW 3000 K 87 90 83 %
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom) Lumen Maintenance 10000 h (Nom) Lumen Maintenance 4000 h (Nom)	930 Warm White (WW 3000 K 87 90 83 % 90 %
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom) Lumen Maintenance 10000 h (Nom)	930 Warm White (WW 3000 K 87 90 83 %
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom) Lumen Maintenance 10000 h (Nom) Lumen Maintenance 4000 h (Nom) Lumen Maintenance 5000 h (Nom)	930 Warm White (WW 3000 K 87 90 83 % 90 %
Chromaticity Coordinate X (Nom) Color Code Color Designation Correlated Color Temperature (Nom) Color Rendering Index (Min) Color Rendering Index (Nom) Lumen Maintenance 10000 h (Nom) Lumen Maintenance 4000 h (Nom)	930 Warm White (WW. 3000 K 87 90 83 % 90 %

Approval and application

		Energy Consumption kWh/	Mercury (Hg)
Order Code	Full Product Name	1000 h	Content (Nom)
409144	MASTERColor CDM-T Elite 35W/930 G12 1CT	43 kWh	4.7 mg
409151	MASTERColor CDM-T Elite 70W/930 G12 1CT	80 kWh	6.6 mg

Operating and electrical

Order		Lamp Current	Voltage	Power
Code	Full Product Name	(EM) (Nom)	(Min)	(Nom)
409144	MASTERColor CDM-T Elite	0.500 A	80 V	39.1 W
	35W/930 G12 1CT			

Order		Lamp Current	Voltage	Power
Code	Full Product Name	(EM) (Nom)	(Min)	(Nom)
409151	MASTERColor CDM-T Elite	1 A	79 V	73.2 W
	70W/930 G12 1CT			

Light technical (1/2)


	· · · · · · · · · · · · · · · · · · ·				
				Lumen	
		Chromaticity	Lumen	Maintenance	Lumen
Order	Full Product	Coordinate Y	Maintenance	12000 h	Maintenance
Code	Name	(Nom)	1000 h (Nom)	(Nom)	2000 h (Nom)
409144	MASTERColor	0.395	95 %	80 %	93 %
	CDM-T Elite				
	35W/930 G12				
	1CT				
409151	MASTERColor	0.396	97 %	82 %	95 %
	CDM-T Elite				


				Lumen	
		Chromaticity	Lumen	Maintenance	Lumen
Order	Full Product	Coordinate Y	Maintenance	12000 h	Maintenance
Code	Name	(Nom)	1000 h (Nom)	(Nom)	2000 h (Nom)
	70W/930 G12				
	1CT				

MasterColor CDM-T T6 Elite

Light technical (2/2)

Order		Luminous Efficacy	Luminous Flux
Code	Full Product Name	(rated) (Nom)	(Rated) (Nom)
409144	MASTERColor CDM-T Elite	98 lm/W	4050 lm
	35W/930 G12 1CT		
409151	MASTERColor CDM-T Elite	103 lm/W	7800 lm
	70W/930 G12 1CT		







© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

210° 180° 150°



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.