



Switch Start Metal Halide Protected

Switch Start Metal Halide Protected

An efficient, protected "O" rated lighting solution that is suitable for open-rated fixtures. Ideal for both indoor and outdoor applications.

Benefits

- Available in various bases and wattages.

Features

- Protective quartz shroud provides extra level of safety - shrouded arc tube for "O" open fixture rating.
- No shut-off required- Ideal for 24-hours a day, 7-days a week operations (relamp fixtures at or before the end of rated life)
- Extended eyelet mogul base will operate in both standard and exclusionary sockets.
- Satisfies the 2005 NEC for use in open luminaires†
- BT-56 base available in 1000 watts / ED-37 base available in 360 and 400 watts / ED 28 base available in 175 and 250 watts.
- * Relamp fixtures at or before end of rated average life. † The 2005 NEC states that luminaires that use a metal halide lamp shall be provided with either a containment barrier that encloses the lamp (historically referred to as an enclosed luminaire) or shall be provided with a means, typically a special lampholder, that will only accept ANSI Type-O metal halide lamp. (Exception—this requirement will not apply to open luminaires with thick-glass parabolic reflector PAR lamps.) For more information regarding use of Type-O, S, and E metal halide systems, please refer to the NEMA white paper on this subject that is freely available at www.nema.org

Application

- Ideal for manufacturing facilities, retail establishments and warehouses.

Switch Start Metal Halide Protected

Versions



E26/E27, Clear



E26, BD-17, Clear



EX39 BT-37, ED-37, Clear





EX39, ED-28, Clear



EX39, BT-56, Clear

Dimensional drawing




Product	D	C (max)
MP1000/BU 6PK	7 in	15.375 in


Product	D	C (max)
MP360/BU/EW 6PK	4.625 in	11.5 in
MP400/BU 6 PK	4.625 in	11.5 in

Switch Start Metal Halide Protected


Dimensional drawing



Product	D	C (max)
MP250/BU 12PK	3.5 in	8.313 in



Product	D	C (max)
MH175/U/M 3PK	2.125 in	5.438 in



Product	D (max)	L (min)	C (max)
MH 150W/640 E26 CL 1SL/24	56 mm	83 mm	138 mm
MH 100W/640 E26 CL 1SL/24	56 mm	83 mm	138 mm
MH 70W/640 E26 CL 1SL/24	56 mm	83 mm	138 mm
MH 100W/640 E26 CL	56 mm	83 mm	138 mm

Mechanical and Housing

Bulb Finish

Clear

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/		Mercury (Hg) Content (Max)	Mercury (Hg) Content (Nom)	Picogram Per Lumen Hour
		1000 h	Energy Saving Product			
928485800191	MH 70W/640 E26 CL 1SL/24	-	-	-	12 mg	-
928485900191	MH 100W/640 E26 CL 1SL/24	110 kWh	-	-	10.2 mg	-
928485900194	MH 100W/640 E26 CL	110 kWh	-	-	10.2 mg	-
928486000191	MH 150W/640 E26 CL 1SL/24	165 kWh	-	-	11 mg	-
928601122312	MH175/U/M 3PK	-	Not Applicable	24.0 mg	-	-
928601157903	MP400/BU 6 PK	-	Not Applicable	40 mg	-	76.9 pg/lm.h
928601179201	MP360/BU/EW 6PK	-	Energy Saving	-	54.5 mg	116 pg/lm.h
928601161903	MP250/BU 12PK	-	Not Applicable	30 mg	-	-

Switch Start Metal Halide Protected

Order Code	Full Product Name	Energy Consumption kWh/		Mercury (Hg) Content	Mercury (Hg) Content	Picogram Per Lumen Hour
		1000 h	Energy Saving Product	(Max)	(Nom)	
928601179601	MP1000/BU 6PK	-	-	-	145 mg	173.7 pg/lm.h

Controls and Dimming

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
928485800191	MH 70W/640 E26 CL 1SL/24	No	928601157903	MP400/BU 6 PK	-
928485900191	MH 100W/640 E26 CL 1SL/24	No	928601179201	MP360/BU/EW 6PK	-
928485900194	MH 100W/640 E26 CL	No	928601161903	MP250/BU 12PK	-
928486000191	MH 150W/640 E26 CL 1SL/24	No	928601179601	MP1000/BU 6PK	-
928601122312	MH175/U/M 3PK	-			

Operating and Electrical (1/2)

Order Code	Full Product Name	Lamp Current (EM)			Power (Rated)		Power (Rated)	
		Lamp Current (Nom)	(Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)	(Max)	(Min)
928485800191	MH 70W/640 E26 CL 1SL/24	-	0.98 A	100 V	75 V	85 V	- W	- W
928485900191	MH 100W/640 E26 CL 1SL/24	-	1.1 A	110 V	90 V	100 V	- W	- W
928485900194	MH 100W/640 E26 CL	-	1.1 A	110 V	90 V	100 V	- W	- W
928486000191	MH 150W/640 E26 CL 1SL/24	-	1.8 A	105 V	85 V	95 V	- W	- W
928601122312	MH175/U/M 3PK	1.5 A	-	147 V	117 V	132 V	-	-
928601157903	MP400/BU 6 PK	3.25 A	-	150 V	120 V	135 V	-	-
928601179201	MP360/BU/EW 6PK	3.25 A	-	130 V	110 V	120 V	-	-
928601161903	MP250/BU 12PK	2.1 A	-	148 V	118 V	133 V	-	-
928601179601	MP1000/BU 6PK	4.1 A	-	-	-	263 V	-	-

Operating and Electrical (2/2)

Order Code	Full Product Name	Power (Rated)	Re-Ignition Time	Order Code	Full Product Name	Power (Rated)	Re-Ignition Time
		(Nom)	(Min) (Max)			(Nom)	(Min) (Max)
928485800191	MH 70W/640 E26 CL 1SL/24	70.0 W	-	928601157903	MP400/BU 6 PK	-	15 min
928485900191	MH 100W/640 E26 CL 1SL/24	100.0 W	-	928601179201	MP360/BU/EW 6PK	-	15 min
928485900194	MH 100W/640 E26 CL	100.0 W	-	928601161903	MP250/BU 12PK	-	15 min
928486000191	MH 150W/640 E26 CL 1SL/24	150.0 W	-	928601179601	MP1000/BU 6PK	-	15 min
928601122312	MH175/U/M 3PK	-	15 min				

General Information

Order Code	Full Product Name	Cap-Base	Life To 50% Failures (Nom)	Life To 5% Failures (Nom)	Main Application	Operating Position	System Description
928485800191	MH 70W/640 E26 CL 1SL/24	E26	12000 h	2000 h	-	H	-
928485900191	MH 100W/640 E26 CL 1SL/24	E26	15000 h	2000 h	-	H	-
928485900194	MH 100W/640 E26 CL	E26	15000 h	2000 h	-	H	-
928486000191	MH 150W/640 E26 CL 1SL/24	E26	15000 h	2000 h	-	H	-
928601122312	MH175/U/M 3PK	E26	10000 h	-	General Lighting (G)	UNIVERSAL	-
928601157903	MP400/BU 6 PK	EX39	20000 h	-	General Lighting (G)	H15	-
928601179201	MP360/BU/EW 6PK	EX39	20000 h	-	General Lighting (G)	UNIVERSAL	-
928601161903	MP250/BU 12PK	EX39	10000 h	-	General Lighting (G)	H15	-
928601179601	MP1000/BU 6PK	EX39	12000 h	-	General Lighting (G)	H15	-

Luminaire Design Requirements

Switch Start Metal Halide Protected

Order Code	Full Product Name	Bulb Temperature (Max)
928485800191	MH 70W/640 E26 CL 1SL/24	450 °C
928485900191	MH 100W/640 E26 CL 1SL/24	450 °C
928485900194	MH 100W/640 E26 CL	450 °C
928486000191	MH 150W/640 E26 CL 1SL/24	450 °C
928601122312	MH175/U/M 3PK	450 °C

Order Code	Full Product Name	Bulb Temperature (Max)
928601157903	MP400/BU 6 PK	400 °C
928601179201	MP360/BU/EW 6PK	400 °C
928601161903	MP250/BU 12PK	400 °C
928601179601	MP1000/BU 6PK	430 °C

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity	Chromaticity	Color Code	Color Designation	Correlated Color	Correlated Color	Correlated Color Temperature (Nom)
		Coordinate X (Nom)	Coordinate Y (Nom)			Temperature (Max)	Temperature (Min)	
928485800191	MH 70W/640 E26 CL 1SL/24	385	390	640	Cool White (CW)	-	-	4000 K
928485900191	MH 100W/640 E26 CL 1SL/24	385	390	640	Cool White (CW)	-	-	4000 K
928485900194	MH 100W/640 E26 CL	385	390	640	Cool White (CW)	-	-	4000 K
928486000191	MH 150W/640 E26 CL 1SL/24	385	390	640	Cool White (CW)	-	-	4000 K
928601122312	MH175/U/M 3PK	0.385	0.390	640	Cool White (CW)	-	-	4000 K
928601157903	MP400/BU 6 PK	385	390	640	Cool White (CW)	-	-	4000 K
928601179201	MP360/BU/EW 6PK	385	390	640	Cool White (CW)	-	-	4000 K
928601161903	MP250/BU 12PK	395	395	640	Cool White (CW)	-	-	3800 K
928601179601	MP1000/BU 6PK	405	390	635	White (WH)	- K	- K	3500 K

Light Technical (2/2)

Order Code	Full Product Name	Color	Lumen	Lumen	Lumen	Luminous	Luminous	Design	Luminous	Luminous
		Rendering Index (Nom)	Maintenance 10000 h (Nom)	Maintenance 2000 h (Nom)	Maintenance 5000 h (Nom)	Efficacy (rated) (Min)	Efficacy (rated) (Nom)	Mean Lumens	Flux (Rated) (Min)	Flux (Rated) (Nom)
928485800191	MH 70W/640 E26 CL 1SL/24	60	-	73 %	-	-	80 lm/W	-	4200 lm	5600 lm
928485900191	MH 100W/640 E26 CL 1SL/24	65	55 %	70 %	62 %	-	90 lm/W	-	7200 lm	9000 lm
928485900194	MH 100W/640 E26 CL	65	55 %	70 %	62 %	-	90 lm/W	-	7200 lm	9000 lm
928486000191	MH 150W/640 E26 CL 1SL/24	65	58 %	73 %	64 %	-	90 lm/W	-	12150 lm	13500 lm
928601122312	MH175/U/M 3PK	65	-	-	-	70 lm/W	80 lm/W	9100 lm	-	14000 lm
928601157903	MP400/BU 6 PK	65	-	-	-	-	100 lm/W	26600 lm	-	40000 lm
928601179201	MP360/BU/EW 6PK	65	-	-	-	-	100 lm/W	23400 lm	-	36000 lm
928601161903	MP250/BU 12PK	62	-	-	-	77 lm/W	86 lm/W	16500 lm	19350 lm	21500 lm
928601179601	MP1000/BU 6PK	65	-	-	-	-	107 lm/W	69550 lm	-	107000 lm

Mechanical and Housing

Order Code	Full Product Name	Bulb Material	Bulb Shape
928485800191	MH 70W/640 E26 CL 1SL/24	-	ED-17
928485900191	MH 100W/640 E26 CL 1SL/24	-	ED-17
928485900194	MH 100W/640 E26 CL	-	ED-17
928486000191	MH 150W/640 E26 CL 1SL/24	-	ED-17
928601122312	MH175/U/M 3PK	Hard Glass	BD-17

Order Code	Full Product Name	Bulb Material	Bulb Shape
928601157903	MP400/BU 6 PK	Hard Glass	ED-37
928601179201	MP360/BU/EW 6PK	Hard Glass	BT-37
928601161903	MP250/BU 12PK	Hard Glass	ED-28
928601179601	MP1000/BU 6PK	Hard Glass	BT-56

Switch Start Metal Halide Protected

