



Product Description

MASTERColour CDM-TC

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Benefits

- Long lamp life compared with incandescent and halogen lamps
- UV-Block quartz outer bulb for reduced fading risks
- Stable colour impression over lifetime
- High lamp efficacy results in low operating costs and low heat generation (which enhances comfort for shoppers and staff)

Features

- Crisp white light
- Superior colour quality
- Allows very small-size luminaires designs that give high beam intensities

Application

- Accent lighting display lighting with sparkling effect
- General and decorative lighting

MASTERColour CDM-TC

Versions



CDM-TC, 35W






CDM-TC 70W /830



CDM-TC 70W /842

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-TC 70W/842 G8.5 1CT/12	15 mm	5 mm	51 mm	53 mm	52 mm	85 mm

Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-TC 35W/842 G8.5 1CT/12	15 mm	0.5 in	5 mm	51 mm	53 mm	52 mm	85 mm
MASTERColour CDM-TC 35W/830 G8.5 1CT/12	15 mm	0.5 in	5 mm	51 mm	53 mm	52 mm	85 mm

Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-TC 70W/830 G8.5 1CT/12	15 mm	0.5 in	7 mm	51 mm	53 mm	52 mm	85 mm

MASTERCcolour CDM-TC

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Re-ignition Time (Min) (Max)	15 min
------------------------------	--------

General Information

Cap-Base	G8.5
Life To 50% Failures (Nom)	12000 h
Operating Position	UNIVERSAL

Mechanical and Housing

Bulb Finish	Clear (CL)
Bulb Material	UV-Block Quartz
Bulb Shape	T14

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Energy	
			Efficiency Label (EEL)	Mercury (Hg) Content (Nom)
20000615	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	43 kWh	A	3.1 mg
20957315	MASTERCcolour CDM-TC 35W/842 G8.5 1CT/12	43 kWh	A	2.7 mg
20167615	MASTERCcolour CDM-TC 70W/830 G8.5 1CT/12	80 kWh	A+	4.6 mg
21275715	MASTERCcolour CDM-TC 70W/842 G8.5 1CT/12	80 kWh	A	7 mg

Operating and Electrical (1/2)

Order Code	Full Product Name	Lamp Current			
		(EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
20000615	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	0.53 A	96 V	80 V	88 V
20957315	MASTERCcolour CDM-TC 35W/842 G8.5 1CT/12	-	93 V	77 V	85 V

Order Code	Full Product Name	Lamp Current			
		(EM) (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
20167615	MASTERCcolour CDM-TC 70W/830 G8.5 1CT/12	-	87 V	78 V	83 V
21275715	MASTERCcolour CDM-TC 70W/842 G8.5 1CT/12	-	93 V	83 V	88 V

Operating and Electrical (2/2)

Order Code	Full Product Name	Power	
		(Rated) (Min)	(Rated) (Nom)
20000615	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	-	39.0 W
20957315	MASTERCcolour CDM-TC 35W/842 G8.5 1CT/12	39.0 W	39.0 W

Order Code	Full Product Name	Power	
		(Rated) (Min)	(Rated) (Nom)
20167615	MASTERCcolour CDM-TC 70W/830 G8.5 1CT/12	-	73 W
21275715	MASTERCcolour CDM-TC 70W/842 G8.5 1CT/12	-	73 W

General Information

Order Code	Full Product Name	Life To 10%	Life To 20%	Life To 5%
		Failures (Nom)	Failures (Nom)	Failures (Nom)
20000615	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	10000 h	11000 h	9000 h
20957315	MASTERCcolour CDM-TC 35W/842 G8.5 1CT/12	8000 h	9000 h	6000 h

Order Code	Full Product Name	Life To 10%	Life To 20%	Life To 5%
		Failures (Nom)	Failures (Nom)	Failures (Nom)
20167615	MASTERCcolour CDM-TC 70W/830 G8.5 1CT/12	8000 h	9000 h	9000 h
21275715	MASTERCcolour CDM-TC 70W/842 G8.5 1CT/12	8000 h	9000 h	9000 h

Luminaire Design Requirements

Order Code	Full Product Name	Bulb Temperature (Max)
20000615	MASTERCcolour CDM-TC 35W/830 G8.5 1CT/12	500 °C
20957315	MASTERCcolour CDM-TC 35W/842 G8.5 1CT/12	500 °C

Order Code	Full Product Name	Bulb Temperature (Max)
20167615	MASTERCcolour CDM-TC 70W/830 G8.5 1CT/12	550 °C
21275715	MASTERCcolour CDM-TC 70W/842 G8.5 1CT/12	700 °C

MASTERCLOUR CDM-TC

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity		Color		Order Code	Full Product Name	Chromaticity		Color	
		Coordinate X (Nom)	Coordinate Y (Nom)	Code	Designation			Coordinate X (Nom)	Coordinate Y (Nom)	Code	Designation
20000615	MASTERCLOUR CDM-TC 35W/830 G8.5 1CT/12	0.432	0.394	830	Warm White (WW)	20167615	MASTERCLOUR CDM-TC 70W/830 G8.5 1CT/12	0.439	0.398	830	Warm White (WW)
20957315	MASTERCLOUR CDM-TC 35W/842 G8.5 1CT/12	0.374	0.369	842	Cool White (CW)	21275715	MASTERCLOUR CDM-TC 70W/842 G8.5 1CT/12	0.362	0.363	842	Cool White (CW)

Light Technical (2/2)

Order Code	Full Product Name	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)	Lumen Maintenance 10000 h (Nom)	Lumen Maintenance 2000 h (Min)	Lumen Maintenance 2000 h (Nom)	Lumen Maintenance 5000 h (Min)	Lumen Maintenance 5000 h (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Rated) (Nom)
20957315	MASTERCLOUR CDM-TC 35W/842 G8.5 1CT/12	4200 K	85	70 %	75 %	85 %	70 %	80 %	79 lm/W	3100 lm
20167615	MASTERCLOUR CDM-TC 70W/830 G8.5 1CT/12	3000 K	83	65 %	75 %	85 %	65 %	75 %	88 lm/W	6400 lm
21275715	MASTERCLOUR CDM-TC 70W/842 G8.5 1CT/12	4200 K	89	65 %	70 %	80 %	65 %	75 %	79 lm/W	5800 lm

Colour Rendering Diagrams

