PHILIPS Lighting



Product Description

MASTER SOX-E

Low Pressure Sodium lamp with improved efficacy

Benefits

 \cdot Extremely high luminous efficacy makes these the most efficient light sources

Features

- Uniform sodium distribution in the discharge tube by means of dimples for a more stable discharge, higher efficacy and better lumen maintenance and lamp life
- Special coating of SOX-E outer tube results in higher lamp efficacy than SOX
- Monochromatic yellow colour with non-existent colour rendering

Application

- Road lighting, railway marshalling yards and crossings, airports, harbours and docks, quarries, foundries and rolling mills
- Security and orientation lighting

Versions



MASTER SOX-E

Dimensional drawing



Approval and Application	
Energy Efficiency Label (EEL)	A++
Mercury (Hg) Content (Nom)	0 mg
Controls and Dimming	
Dimmable	no
General Information	
Cap-Base	BY22D
Life To 20% Failures (Nom)	12000 h
Life To 50% Failures (Nom)	18000 h
Life To 5% Failures (Nom)	6000 h
Operating Position	P20
Luminaire Design Requirements	
Bulb Temperature (Max)	150 °C
Light Technical	
Correlated Colour Temperature (Nom)	1800 K
Lumen Maintenance 2000 h (Nom)	100 %
Lumen Maintenance 5000 h (Nom)	100 %

Product	D (max)	C (max)
MASTER SOX-E 131W BY22d 1SL/6	66 mm	1120 mm
MASTER SOX-E 36W BY22d 1SL/12	52 mm	425 mm
MASTER SOX-E 66W BY22d 1SL/12	66 mm	528 mm
MASTER SOX-E 91W BY22d 1SL/12	66 mm	775 mm

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
928145100008	MASTER SOX-E 131W BY22d 1SL/6	146 kWh
928145800008	MASTER SOX-E 36W BY22d 1SL/12	40 kWh
928145900008	MASTER SOX-E 66W BY22d 1SL/12	75 kWh
928146100008	MASTER SOX-E 91W BY22d 1SL/12	104 kWh

Operating and Electrical

				Power
		Lamp Current	Voltage	(Rated)
Order Code	Full Product Name	(EM) (Nom)	(Nom)	(Nom)
928145100008	MASTER SOX-E 131W	0.54 A	250 V	127.0 W
	BY22d 1SL/6			
928145800008	MASTER SOX-E 36W	0.32 A	120 V	36.0 W
	BY22d 1SL/12			

				Power
		Lamp Current	Voltage	(Rated)
Order Code	Full Product Name	(EM) (Nom)	(Nom)	(Nom)
928145900008	MASTER SOX-E 66W	0.6 A	123 V	65.0 W
	BY22d 1SL/12			
928146100008	MASTER SOX-E 91W	0.54 A	173 V	90.0 W
	BY22d 1SL/12			

Light Technical

		Luminous Efficacy	Luminous Flux
Order Code	Full Product Name	(rated) (Nom)	(Rated) (Nom)
928145100008	MASTER SOX-E 131W BY22d	206 lm/W	26200 lm
	1SL/6		

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Rated) (Nom)
928145800008	MASTER SOX-E 36W BY22d	164 lm/W	6100 lm
	1SL/12		

MASTER SOX-E

		Luminous Efficacy	Luminous Flux
Order Code	Full Product Name	(rated) (Nom)	(Rated) (Nom)
928145900008	MASTER SOX-E 66W BY22d	170 lm/W	11000 lm
	1SL/12		

		Luminous Efficacy	Luminous Flux
Order Code	Full Product Name	(rated) (Nom)	(Rated) (Nom)
928146100008	MASTER SOX-E 91W BY22d	192 lm/W	17400 lm
	1SL/12		

150°

30°


120°

90°

60°

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
928145100008	MASTER SOX-E 131W BY22d 1SL/6	T65
928145800008	MASTER SOX-E 36W BY22d 1SL/12	Т50
928145900008	MASTER SOX-E 66W BY22d 1SL/12	T65
928146100008	MASTER SOX-E 91W BY22d 1SL/12	T65





© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2018, September 2 - data subject to change