



# Put people and merchandise in the best light

# Long Life IR PAR30S

Optically advanced Halogen PAR lamps are designed with innovative technologies that provide superior light performance while reducing operating costs.

#### Benefits

- · Delivers consistent quality lamp-to-lamp and throughout lifetime.
- · Increased uniform beam intensity without hot spots.
- · Superior beam control for effective accent lighting.

#### **Features**

- Philips reflector technology provide optimal beam control and uniform beam intensity without hot spots.
- $\boldsymbol{\cdot}$  Features IRC coating technology.
- 6000 Hour Rated Average Life †
- · Available in 45 Watts Spot, Flood, Wide Flood.
- †This excludes the 130V 50W PAR30 Short which has 3000 hours.Rated average lifeis the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not

### **Application**

 Ideal for retail, residential, and commercial applications. For indoor and outdoor use.

# Long Life IR PAR30S

## Versions






E26, PAR30/PAR30S, Wide Flood, Med

E26, PAR30/PAR30S

## Dimensional drawing



| Product                                    | D       | C (max) |
|--|---------|---------|
| Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1 | 3.75 in | 4.5 in  |
| Long Life IR 50PAR30L/IRC+/SP10 120V 15/1  | 3.75 in | 4.5 in  |

# Long Life IR PAR30S

| Approval and Application           |              |
|------------------------------------|--------------|
| Estimated Energy Cost Per Year     | 6.02\$       |
|                                    |              |
| Operating and Electrical           |              |
| Voltage (Nom)                      | 120 V        |
| Power (Rated) (Nom)                | 50 W         |
|                                    |              |
| General Information                |              |
| Cap-Base                           | E26          |
| Life With 3 Hour Per Day Use       | 3.8 a        |
| Main Application                   | Accent &     |
|                                    | Downlighting |
| Operating Position                 | UNIVERSAL    |
| Rated Lifetime (Hours)             | 4200 h       |
|                                    |              |
| Light Technical                    |              |
| Correlated Color Temperature (Nom) | 2750 K       |
| Color Rendering Index (Nom)        | 100          |
| Luminous Flux (Nom)                | 900 lm       |
|                                    |              |
| Mechanical and Housing             |              |
| Bulb Finish                        | Clear        |
| Bulb Material                      | Hard Glass   |
| Bulb Shape                         | PAR30L       |
| Reflector Finish                   | Aluminized   |

## **Light Technical**

|              |   | Beam Angle |                  | Luminous        |
|--------------|---|------------|------------------|-----------------|
| Order Code   | Full Product Name                             | (Nom)      | Beam Description | Intensity (Nom) |
| 924757141301 | Long Life IR 50PAR30L/IRC+/WFL40<br>120V 15/1 | 40 °       | Wide Flood       | 1550 cd         |
| 924757141401 | Long Life IR 50PAR30L/IRC+/SP10<br>120V 15/1  | 10 °       | Spot             | 12000 cd        |

