



ComfortVision – asymmetric downlighting

ComfortVision SNF111

ComfortVision is a high-efficiency, asymmetric floodlight, distributing a low-glare beam evenly and accurately. It can accommodate metal-halide lamps for good color rendering or a high-pressure sodium lamp for economical performance. Available in medium- or narrow-beam versions, the floodlight accepts a single 1000 or two 400 or 600 W lamps. The twin-lamp version offers switching flexibility that permits tailoring to the user's needs while allowing energy savings. ComfortVision's rugged all-weather construction is designed for easy aiming, simple cleaning and speedy servicing. For optimal downlighting, the luminaire should be mounted horizontally at a height of 15-25 meters. It has an adjustment range of $\pm 12^\circ$ from the horizontal. A universal mounting bracket allows mounting to headframes, ceilings and walls.

Benefits

- High-efficiency asymmetrical floodlight that distributes a low-glare beam evenly and accurately
- Maximum flexibility with a choice of medium- or narrow-beam versions and a single 1000 W or two switchable 400 or 600 W lamps
- Rugged, all-weather construction designed for easy aiming, simple cleaning and speedy servicing

Features

- Rugged, all-weather construction
- Single 1000 W or two switchable 400 or 600 W lamps
- Medium or narrow beam
- Adjustment range of $\pm 12^\circ$ from the horizontal
- Universal mounting bracket

ComfortVision SNF111

Application


- Industrial areas
- Roundabouts
- Car parks
- Sports lighting

Specifications

| | |
|----------------------|--------------------|
| Aiming Horizontal | to ° |
| Aiming Vertical | to ° |
| Ballast | Conventional(CONV) |
| Material of Bracket | Bracket: |
| Material of Gear box | Gear box: |

| | |
|-----------------------|------------|
| Material | Housing: |
| Material of Reflector | Reflector: |
| Material | : |
| Material | : |

Versions



Product details

