


TBS769 Exclusive

Exclusive TBS769

Innovative miniature luminaire with a built-in height of only 55mm for TL5 fluorescent lamp(s) with a choice of 5 optics, of which three are omni-directional luminance control (OLC) optics.This luminaire provide outstanding lighting efficiency and comfort. All luminaires have an integrated top reflector provided with air sleeves.This widest choice in recessed TL5 luminaires offers many possibilities for customers, like freedom in design due to the small and innovative optic(s), energy efficiency, ease of installation and environmental friendliness.

Features

- OLC optics:The special concave curves ensure constant luminance control in all directions, while the 3-D lamella optimizes beam spread and light distribution
- M7/C7/D7 louvre: offers optimum glare control, good uniformity and highest efficiency
- Built-in height of 55 mm: creates more void space and lowers the total height of the building
- Integrated top reflector with air-handling slots: ensure best lamp working temperatures to deliver optimal light output ratios
- Perforated in-fill plate: dedicated effects of the light emitting holes creates an added elegant ambience
- T5 lamps & electronic ballast: 25% less energy consumption than conventional systems

Application

- 'Hive' offices: open-plan administration offices, helpdesks and call centers
- 'Cell' offices: one or twoperson offices
- 'Club' offices: medium-sized open-plan offices
- 'Meet' office spaces: reception desks, conference rooms, and consultation rooms
- 'Lobby' office spaces: corridors, staircases, lifts, entrance halls and cafes

Dimensional drawing

TBS769

Product	A	B
TBS769 3xTL5-14W HFA C7	597 mm	597 mm
TBS769 2xTL5-28W HFA M7	1197 mm	297 mm
TBS769 2xTL5-14W HFE M7		
TBS769 2xTL5-35W HFE D7	1497 mm	297 mm
TBS769 3xTL5-14W HFE C7	597 mm	597 mm
TBS769 3xTL5-14W 2x HFA C7 FU	597 mm	597 mm
TBS769 2xTL5-35W HFE M-D	1497 mm	297 mm
TBS769 3xTL5-14W HFE D7	597 mm	597 mm
TBS769 2xTL5-28W HFA C7	1197 mm	297 mm
TBS769 3xTL5-28W HFA M7	1197 mm	597 mm
TBS769 3xTL5-28W HFE M-D	1197 mm	597 mm
TBS769 4xTL5-14W HFA C7	597 mm	597 mm
TBS769 1xTL5-35W HFA M7	1497 mm	147 mm
TBS769 2xTL5-14W HFA D7		
TBS769 1xTL5-35W HFA D7	1497 mm	147 mm
TBS769 3xTL5-28W HFE D7	1197 mm	597 mm
TBS769 2xTL5-28W HFA D7	1197 mm	297 mm
TBS769 4xTL5-14W HFE C7	597 mm	597 mm
TBS769 2xTL5-14W HFE C7		
TBS769 2xTL5-28W HFE M-D	1197 mm	297 mm
TBS769 2xTL5-35W HFE M7	1497 mm	297 mm
TBS769 1xTL5-35W HFE M7	1497 mm	147 mm
TBS769 2xTL5-28W HFA M-D	1197 mm	297 mm
TBS769 1xTL5-35W HFA M-D	1497 mm	147 mm
TBS769 3xTL5-14W HFA D7	597 mm	597 mm
TBS769 3xTL5-14W HFE M-D	597 mm	597 mm
TBS769 2xTL5-28W 2x HFR D7 FU	1197 mm	297 mm
TBS769 1xTL5-35W HFA C7	1497 mm	147 mm
TBS769 1xTL5-35W HFE M-D	1497 mm	147 mm
TBS769 3xTL5-14W 2x HFA D7 FU	597 mm	597 mm
TBS769 4xTL5-14W HFA M7	597 mm	597 mm
TBS769 3xTL5-14W 2x HFR C7 FU	597 mm	597 mm
TBS769 4xTL5-14W HFA M-D	597 mm	597 mm
TBS769 3xTL5-28W HFA C7	1197 mm	597 mm
TBS769 1xTL5-28W HFE M-D	1197 mm	147 mm
TBS769 4xTL5-14W HFE M-D	597 mm	597 mm
TBS769 2xTL5-28W HFE M7	1197 mm	297 mm
TBS769 1xTL5-35W HFE C7	1497 mm	147 mm
TBS769 2xTL5-14W HFA M-D		
TBS769 3xTL5-14W HFA M-D	597 mm	597 mm
TBS769 2xTL5-28W HFE D7	1197 mm	297 mm
TBS769 3xTL5-28W HFE M7	1197 mm	597 mm
TBS769 4xTL5-14W HFE M7	597 mm	597 mm
TBS769 2xTL5-28W 2x HFR C7 FU	1197 mm	297 mm
TBS769 1xTL5-28W HFA C7	1197 mm	147 mm
TBS769 3xTL5-14W HFE M7	597 mm	597 mm
TBS769 2xTL5-35W HFE C7	1497 mm	297 mm
TBS769 3xTL5-14W 2x HFR D7 FU	597 mm	597 mm
TBS769 1xTL5-28W HFE C7	1197 mm	147 mm
TBS769 4xTL5-14W HFA D7	597 mm	597 mm

Exclusive TBS769

Dimensional drawing

Product	A	B
TBS769 2xTL5-28W HFE C7	1197 mm	297 mm
TBS769 3xTL5-28W HFA M-D	1197 mm	597 mm
TBS769 3xTL5-14W HFA M7	597 mm	597 mm
TBS769 3xTL5-28W HFE C7	1197 mm	597 mm
TBS769 2xTL5-14W HFA C7		
TBS769 1xTL5-28W HFA M7	1197 mm	147 mm
TBS769 2xTL5-14W HFE M-D		
TBS769 2xTL5-14W HFA M7		
TBS769 1xTL5-28W HFE D7	1197 mm	147 mm
TBS769 1xTL5-28W HFE M7	1197 mm	147 mm
TBS769 2xTL5-14W HFE D7		
TBS769 2xTL5-28W 2x HFA D7 FU	1197 mm	297 mm
TBS769 1xTL5-28W HFA D7	1197 mm	147 mm
TBS769 4xTL5-14W HFE D7	597 mm	597 mm
TBS769 1xTL5-35W HFE D7	1497 mm	147 mm
TBS769 1xTL5-28W HFA M-D	1197 mm	147 mm
TBS769 2xTL5-28W 2x HFA C7 FU	1197 mm	297 mm
TBS769 3xTL5-28W HFA D7	1197 mm	597 mm

Approval and Application

Ingress protection code	IP20

General Information

Kombipack	-
Lamp family code	TL5
Lamp power	28
Optic type	M7
Product Family Code	TBS769

General Information

order code	Gear	Number of gear units	Number of light sources
911400623580	HFE	-	2

order code	Gear	Number of gear units	Number of light sources
911400979580	HFA	1 unit	1

© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.