



Waterproof TCW060 – just light

TCW060 C

Designed for use in demanding environments, TCW060 is an economical, compact waterproof luminaire. Dedicated versions are available for TL-D and TL5 lamps.Ingress-protected to a level of IP65 and operating solely on electronic gear, this is a competitive energy-saving solution for wet spaces — at the same cost as an electromagnetic solution. A flexible ceiling clip facilitates easy installation and maintenance.

Benefits

- Economical, compact waterproof luminaire designed for use in demanding environments
- Operating solely on electronic gear, this is a competitive energy-saving solution for wet spaces at the same cost as a standard electromagnetic solution
- · Dedicated versions available for TL5 and TL-D lamps

Features

- Dedicated housings for TLD and for TL5 types
- Fully complies with IP65 ingress protection norms provides protection against moderate to challenging impact of moisture and dust
- · Available in 1- and 2-lamp TL-D and TL5 versions
- · Electronic HF driver is energy efficient and produces less noise and flicker
- · Easy-to-use clippers ensure flexibility in installation and ease in maintenance

Application

- · Car parks
- Warehouses
- · General industrial applications
- \cdot Food and beverage industry

Specifications

TCW060 C

| Туре | TCW060 |
|---------------|-----------------------------------|
| Light source | Fluorescent: |
| | - 1 or 2 x TL5 / G5 / 28 W |
| | - 1 or 2 x TL-D / G13 / 18, 36 W |
| Lamp included | No |
| Ballast | Electronic, 220-240 V / 50-60 Hz: |
| | - High Frequency (HF) |
| Optical cover | Polycarbonate |
| Connection | Screw connector |


| Material | Housing: polycarbonate, grey | |
|-------------------|--|--|
| | Cover: polycarbonate, UV-resistant | |
| | Ceiling clips: stainless steel | |
| | Cover clips: polycarbonate, grey | |
| Installation | Surface mounted | |
| | Operating temperature: -15°C < T | |
| Maintenance | Hingeable cover for easy lamp replacement | |
| Main applications | Wet environments, light industries, parkings | |
| | | |

Versions



Waterproof TCW060 surfacemounted/suspended luminaire for TL5 fluorescent lamp(s)

Dimensional drawing



Suspension bracket

| Product | Α | В |
|----------------------------|--------|---------|
| TCW060 C 2xTL5-28W HF 220V | 800 mm | 1215 mm |

Product details





Cover clip

TCW060 C



© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.