



The world's most efficient fluorescent lighting

MASTER TL5 High Efficiency Eco

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HE Eco lamp offers excellent lumen maintenance and colour rendering. Application areas vary from offices and industry to schools and retail environments.

Benefits

- Up to 10 % energy saving with simply changing the lamp
- The same quality of light as compared with MASTER TL5 HE lamps
- All benefits of regular TL5 lamps

Features

- High lamp efficacies up to 114 lm/W
- Up to 10% power reduction in comparison with standard MASTER TL5 HE lamps
- Fluorescent Super 80 light quality

Application


- Ideally suited for recessed, surface-mounted and suspended luminaires e.g. in offices, shops, schools, public buildings and industry (low ceiling), wherever high-quality, energy-efficient lighting is required

MASTER TL5 High Efficiency Eco

Versions



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE Eco 25=28W/840 1SL/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HE Eco 13=14W/840 1SL/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

MASTER TL5 High Efficiency Eco

Approval and Application

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	1.4 mg

Controls and Dimming

Dimmable	yes
----------	-----

Operating and Electrical

Lamp Current (Nom)	0.170 A
--------------------	---------

General Information

Cap-Base	G5
Life To 50% Failures Preheat (Nom)	25000 h
LSF Preheat 16000 h Rated	99 %
LSF Preheat 20000 h Rated	94 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %

Light Technical

Colour Code	840
Colour Designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Colour Rendering Index (Max)	85
Colour Rendering Index (Min)	80
Colour Rendering Index (Nom)	82
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 2000 h Rated	96 %
LLMF 20000 h Rated	90 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %

Mechanical and Housing

Bulb Shape	T5
------------	----

Temperature

Design Temperature (Nom)	35 °C
--------------------------	-------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
927989884033	MASTER TL5 HE Eco 13=14W/840 1SL/40	14 kWh
927990984033	MASTER TL5 HE Eco 25=28W/840 1SL/40	28 kWh

Operating and Electrical

Order Code	Full Product Name	Power (Rated) (Nom)	Order Code	Full Product Name	Power (Rated) (Nom)
927989884033	MASTER TL5 HE Eco 13=14W/840 1SL/40	13 W	927990984033	MASTER TL5 HE Eco 25=28W/840 1SL/40	25.2 W

Light Technical

MASTER TL5 High Efficiency Eco

Order Code	Full Product Name	Luminous Efficacy (@	Luminous Efficacy	Luminous Flux	
		Max Lumen, Rated) (Nom)	(rated) (Nom)	Luminous Flux (Nom)	(Rated) (Nom)
927989884033	MASTER TL5 HE Eco 13=14W/840 1SL/40	108 lm/W	92 lm/W	1350 lm	1150 lm
927990984033	MASTER TL5 HE Eco	114 lm/W	103 lm/W	2900 lm	2600 lm

Order Code	Full Product Name	Luminous Efficacy (@	Luminous Efficacy	Luminous Flux	
		Max Lumen, Rated) (Nom)	(rated) (Nom)	Luminous Flux (Nom)	(Rated) (Nom)
	25=28W/840 1SL/40				

