



The world's brightest fluorescent lighting

MASTER TL5 High Output

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Benefits

- Allows system miniaturization and maximum luminaire design freedom
- Lamp lengths enable easy fitting into ceiling module systems
- Optimized for installations which need high luminous flux
- Virtually constant lumen level with excellent lumen maintenance
- Good color rendering

Features


- 40% thinner than TL-D lamps
- Designed for high light output and system miniaturization
- Highly efficient 3-band fluorescent coating in combination with precoating
- Specifically designed for operation with electronic gear and well-suited for dimming
- Maximum light output reached at approximately 35 °C in free-burning position if an electronic driver with cut-off feature is used
- Can be ignited from -15 to +50 °C

Application

- The combination of a compact lamp and high lumen package of the MASTER TL5 HO offers exciting opportunities for architectural lighting and customized solutions
- Offers economic solutions with high-ceiling lighting in shops, industry and department stores
- The high luminous flux gives optimal results in aesthetic pendants and furniture-mounted luminaires in offices, workshops, restaurants and reception areas

MASTER TL5 High Output


Versions



G5, T5

MASTER TL5 High Output

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 80W/865 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 80W/840 SLV/20	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 80W/840 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 80W/840 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 80W/830 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 80W/830 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 54W/865 SLV/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/840 SLV/20	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/840 SLV/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/840 UNP/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/830 SLV/20	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/830 SLV/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 54W/830 UNP/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm
MASTER TL5 HO 39W/865 SLV/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
MASTER TL5 HO 39W/840 SLV/20	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
MASTER TL5 HO 39W/840 SLV/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
MASTER TL5 HO 39W/840 UNP/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
MASTER TL5 HO 39W/830 SLV/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm
MASTER TL5 HO 24W/865 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 24W/840 1SL/20	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 24W/840 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 24W/840 UNP/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 24W/830 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 24W/830 UNP/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HO 49W/865 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

MASTER TL5 High Output

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 49W/840 SLV/20	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 49W/840 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 49W/840 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 49W/830 SLV/20	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 49W/830 SLV/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm
MASTER TL5 HO 49W/830 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg
Controls and Dimming	
Dimmable	Yes
General Information	
Cap-Base	G5
Life To 50% Failures Preheat (Nom)	30000 h
LSF Preheat 16000 h Rated	97 %
LSF Preheat 20000 h Rated	84 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
System Description	High Output
Light Technical	
Color Rendering Index (Max)	85
Color Rendering Index (Min)	80
LLMF 12000 h Rated	92 %
LLMF 2000 h Rated	96 %
LLMF 20000 h Rated	90 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
Mechanical and Housing	
Bulb Shape	T5
Temperature	
Design Temperature (Nom)	35 °C

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/ 1000 h	Energy Efficiency Label (EEL)
927927583018	MASTER TL5 HO 49W/830 UNP/40	54 kWh	A+
927927583055	MASTER TL5 HO 49W/830 SLV/40	54 kWh	A+
927927583061	MASTER TL5 HO 49W/830 SLV/20	54 kWh	A+
927927584018	MASTER TL5 HO 49W/840 UNP/40	54 kWh	A+
927927584055	MASTER TL5 HO 49W/840 SLV/40	54 kWh	A+
927927584061	MASTER TL5 HO 49W/840 SLV/20	54 kWh	A+
927927586555	MASTER TL5 HO 49W/865 SLV/40	54 kWh	A+
927928083018	MASTER TL5 HO 24W/830 UNP/40	25 kWh	A
927928083055	MASTER TL5 HO 24W/830 SLV/40	25 kWh	A
927928084018	MASTER TL5 HO 24W/840 UNP/40	25 kWh	A
927928084055	MASTER TL5 HO 24W/840 SLV/40	25 kWh	A
927928084061	MASTER TL5 HO 24W/840 1SL/20	25 kWh	A
927928086555	MASTER TL5 HO 24W/865 SLV/40	25 kWh	A
927928583055	MASTER TL5 HO 39W/830 SLV/40	42 kWh	A+
927928584018	MASTER TL5 HO 39W/840 UNP/40	42 kWh	A+
927928584055	MASTER TL5 HO 39W/840 SLV/40	42 kWh	A+
927928584061	MASTER TL5 HO 39W/840 SLV/20	42 kWh	A+
927928586555	MASTER TL5 HO 39W/865 SLV/40	42 kWh	A
927929083018	MASTER TL5 HO 54W/830 UNP/40	59 kWh	A+
927929083055	MASTER TL5 HO 54W/830 SLV/40	59 kWh	A+
927929083061	MASTER TL5 HO 54W/830 SLV/20	59 kWh	A+
927929084018	MASTER TL5 HO 54W/840 UNP/40	59 kWh	A+
927929084055	MASTER TL5 HO 54W/840 SLV/40	59 kWh	A+
927929084061	MASTER TL5 HO 54W/840 SLV/20	59 kWh	A+
927929086555	MASTER TL5 HO 54W/865 SLV/40	59 kWh	A
927929583018	MASTER TL5 HO 80W/830 UNP/40	88 kWh	A
927929583057	MASTER TL5 HO 80W/830 SLV/40	88 kWh	A
927929584018	MASTER TL5 HO 80W/840 UNP/40	88 kWh	A
927929584057	MASTER TL5 HO 80W/840 SLV/40	88 kWh	A
927929584061	MASTER TL5 HO 80W/840 SLV/20	88 kWh	A
927929586557	MASTER TL5 HO 80W/865 SLV/40	88 kWh	A

Operating and Electrical

MASTER TL5 High Output

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927927583018	MASTER TL5 HO 49W/830 UNP/40	0.255 A	49.2 W
927927583055	MASTER TL5 HO 49W/830 SLV/40	0.255 A	49.2 W
927927583061	MASTER TL5 HO 49W/830 SLV/20	0.255 A	49.2 W
927927584018	MASTER TL5 HO 49W/840 UNP/40	0.255 A	49.2 W
927927584055	MASTER TL5 HO 49W/840 SLV/40	0.255 A	49.2 W
927927584061	MASTER TL5 HO 49W/840 SLV/20	0.255 A	49.2 W
927927586555	MASTER TL5 HO 49W/865 SLV/40	0.255 A	49.2 W
927928083018	MASTER TL5 HO 24W/830 UNP/40	0.295 A	22.5 W
927928083055	MASTER TL5 HO 24W/830 SLV/40	0.295 A	22.5 W
927928084018	MASTER TL5 HO 24W/840 UNP/40	0.295 A	22.5 W
927928084055	MASTER TL5 HO 24W/840 SLV/40	0.295 A	22.5 W
927928084061	MASTER TL5 HO 24W/840 1SL/20	0.295 A	22.5 W
927928086555	MASTER TL5 HO 24W/865 SLV/40	0.295 A	22.5 W
927928583055	MASTER TL5 HO 39W/830 SLV/40	0.325 A	38.0 W
927928584018	MASTER TL5 HO 39W/840 UNP/40	0.325 A	38.0 W
927928584055	MASTER TL5 HO 39W/840 SLV/40	0.325 A	38.0 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
927928584061	MASTER TL5 HO 39W/840 SLV/20	0.325 A	38.0 W
927928586555	MASTER TL5 HO 39W/865 SLV/40	0.325 A	38.0 W
927929083018	MASTER TL5 HO 54W/830 UNP/40	0.455 A	54.1 W
927929083055	MASTER TL5 HO 54W/830 SLV/40	0.455 A	54.1 W
927929083061	MASTER TL5 HO 54W/830 SLV/20	0.455 A	54.1 W
927929084018	MASTER TL5 HO 54W/840 UNP/40	0.455 A	54.1 W
927929084055	MASTER TL5 HO 54W/840 SLV/40	0.455 A	54.1 W
927929084061	MASTER TL5 HO 54W/840 SLV/20	0.455 A	54.1 W
927929086555	MASTER TL5 HO 54W/865 SLV/40	0.455 A	54.1 W
927929583018	MASTER TL5 HO 80W/830 UNP/40	0.530 A	79.8 W
927929583057	MASTER TL5 HO 80W/830 SLV/40	0.530 A	79.8 W
927929584018	MASTER TL5 HO 80W/840 UNP/40	0.530 A	79.8 W
927929584057	MASTER TL5 HO 80W/840 SLV/40	0.530 A	79.8 W
927929584061	MASTER TL5 HO 80W/840 SLV/20	0.530 A	79.8 W
927929586557	MASTER TL5 HO 80W/865 SLV/40	0.530 A	80 W

Light Technical (1/2)

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927927583018	MASTER TL5 HO 49W/830 UNP/40	830	Warm White (WW)	3000 K	82
927927583055	MASTER TL5 HO 49W/830 SLV/40	830	Warm White (WW)	3000 K	82
927927583061	MASTER TL5 HO 49W/830 SLV/20	830	Warm White (WW)	3000 K	82
927927584018	MASTER TL5 HO 49W/840 UNP/40	840	Cool White (CW)	4000 K	82
927927584055	MASTER TL5 HO 49W/840 SLV/40	840	Cool White (CW)	4000 K	82
927927584061	MASTER TL5 HO 49W/840 SLV/20	840	Cool White (CW)	4000 K	82
927927586555	MASTER TL5 HO 49W/865 SLV/40	865	Cool Daylight	6500 K	82
927928083018	MASTER TL5 HO 24W/830 UNP/40	830	Warm White (WW)	3000 K	82
927928083055	MASTER TL5 HO 24W/830 SLV/40	830	Warm White (WW)	3000 K	82

Order Code	Full Product Name	Color Code	Color Designation	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)
927928084018	MASTER TL5 HO 24W/840 UNP/40	840	Cool White (CW)	4000 K	82
927928084055	MASTER TL5 HO 24W/840 SLV/40	840	Cool White (CW)	4000 K	82
927928084061	MASTER TL5 HO 24W/840 1SL/20	840	Cool White (CW)	4000 K	82
927928086555	MASTER TL5 HO 24W/865 SLV/40	865	Cool Daylight	6500 K	82
927928583055	MASTER TL5 HO 39W/830 SLV/40	830	Warm White (WW)	3000 K	82
927928584018	MASTER TL5 HO 39W/840 UNP/40	840	Cool White (CW)	4000 K	82
927928584055	MASTER TL5 HO 39W/840 SLV/40	840	Cool White (CW)	4000 K	82
927928584061	MASTER TL5 HO 39W/840 SLV/20	840	Cool White (CW)	4000 K	82
927928586555	MASTER TL5 HO 39W/865 SLV/40	865	Cool Daylight	6500 K	82

MASTER TL5 High Output

Order Code	Full Product Name	Color Code	Color Designation	Correlated	Color
				Color Temperature (Nom)	Rendering Index (Nom)
927929083018	MASTER TL5 HO 54W/830 UNP/40	830	Warm White (WW)	3000 K	85
927929083055	MASTER TL5 HO 54W/830 SLV/40	830	Warm White (WW)	3000 K	85
927929083061	MASTER TL5 HO 54W/830 SLV/20	830	Warm White (WW)	3000 K	85
927929084018	MASTER TL5 HO 54W/840 UNP/40	840	Cool White (CW)	4000 K	85
927929084055	MASTER TL5 HO 54W/840 SLV/40	840	Cool White (CW)	4000 K	85
927929084061	MASTER TL5 HO 54W/840 SLV/20	840	Cool White (CW)	4000 K	85
927929086555	MASTER TL5 HO 54W/865 SLV/40	865	Cool Daylight	6500 K	85

Order Code	Full Product Name	Color Code	Color Designation	Correlated	Color
				Color Temperature (Nom)	Rendering Index (Nom)
927929583018	MASTER TL5 HO 80W/830 UNP/40	830	Warm White (WW)	3000 K	82
927929583057	MASTER TL5 HO 80W/830 SLV/40	830	Warm White (WW)	3000 K	82
927929584018	MASTER TL5 HO 80W/840 UNP/40	840	Cool White (CW)	4000 K	82
927929584057	MASTER TL5 HO 80W/840 SLV/40	840	Cool White (CW)	4000 K	82
927929584061	MASTER TL5 HO 80W/840 SLV/20	840	Cool White (CW)	4000 K	82
927929586557	MASTER TL5 HO 80W/865 SLV/40	865	Cool Daylight	6500 K	82

Light Technical (2/2)

Order Code	Full Product Name	LLMF Rated	Luminous Efficacy (@)			
			Max Lumen (Rated) (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927927583018	MASTER TL5 HO 49W/830 UNP/40	91 %	99 lm/W	89 lm/W	4900 lm	4375 lm
927927583055	MASTER TL5 HO 49W/830 SLV/40	91 %	99 lm/W	89 lm/W	4900 lm	4375 lm
927927583061	MASTER TL5 HO 49W/830 SLV/20	91 %	99 lm/W	89 lm/W	4900 lm	4375 lm
927927584018	MASTER TL5 HO 49W/840 UNP/40	90 %	99 lm/W	89 lm/W	4900 lm	4375 lm
927927584055	MASTER TL5 HO	90 %	99 lm/W	89 lm/W	4900 lm	4375 lm

Order Code	Full Product Name	LLMF Rated	Luminous Efficacy (@)			
			Max Lumen (Rated) (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927927584061	MASTER TL5 HO 49W/840 SLV/40	90 %	99 lm/W	89 lm/W	4900 lm	4375 lm
927927586555	MASTER TL5 HO 49W/865 SLV/40	91 %	92 lm/W	83 lm/W	4550 lm	4075 lm
927928083018	MASTER TL5 HO 24W/830 UNP/40	91 %	87 lm/W	76 lm/W	1950 lm	1700 lm
927928083055	MASTER TL5 HO 24W/830 SLV/40	91 %	87 lm/W	76 lm/W	1950 lm	1700 lm

MASTER TL5 High Output

Order Code	Full Product Name	Luminous Efficacy (@				
		LLMF 16000 h Rated	Max Lumen, (Rated) (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
927928084018	MASTER TL5 HO 24W/840 UNP/40	91 %	87 lm/W	76 lm/W	1950 lm	1700 lm
927928084055	MASTER TL5 HO 24W/840 SLV/40	91 %	87 lm/W	76 lm/W	1950 lm	1700 lm
927928084061	MASTER TL5 HO 24W/840 1SL/20	91 %	87 lm/W	76 lm/W	1950 lm	1700 lm
927928086555	MASTER TL5 HO 24W/865 SLV/40	91 %	81 lm/W	72 lm/W	1825 lm	1575 lm
927928583055	MASTER TL5 HO 39W/830 SLV/40	91 %	92 lm/W	82 lm/W	3500 lm	3100 lm
927928584018	MASTER TL5 HO 39W/840 UNP/40	91 %	92 lm/W	82 lm/W	3500 lm	3100 lm
927928584055	MASTER TL5 HO 39W/840 SLV/40	91 %	92 lm/W	82 lm/W	3500 lm	3100 lm
927928584061	MASTER TL5 HO 39W/840 SLV/20	91 %	92 lm/W	82 lm/W	3500 lm	3100 lm
927928586555	MASTER TL5 HO 39W/865 SLV/40	91 %	86 lm/W	76 lm/W	3250 lm	2875 lm
927929083018	MASTER TL5 HO 54W/830 UNP/40	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm
927929083055	MASTER TL5 HO 54W/830 SLV/40	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm
927929083061	MASTER TL5 HO	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm

Order Code	Full Product Name	Luminous Efficacy (@				
		LLMF 16000 h Rated	Max Lumen, (Rated) (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
	54W/830 SLV/20					
927929084018	MASTER TL5 HO 54W/840 UNP/40	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm
927929084055	MASTER TL5 HO 54W/840 SLV/40	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm
927929084061	MASTER TL5 HO 54W/840 SLV/20	91 %	93 lm/W	83 lm/W	5000 lm	4500 lm
927929086555	MASTER TL5 HO 54W/865 SLV/40	91 %	86 lm/W	78 lm/W	4650 lm	4200 lm
927929583018	MASTER TL5 HO 80W/830 UNP/40	91 %	88 lm/W	82 lm/W	7000 lm	6550 lm
927929583057	MASTER TL5 HO 80W/830 SLV/40	91 %	88 lm/W	82 lm/W	7000 lm	6550 lm
927929584018	MASTER TL5 HO 80W/840 UNP/40	91 %	88 lm/W	82 lm/W	7000 lm	6550 lm
927929584057	MASTER TL5 HO 80W/840 SLV/40	91 %	88 lm/W	82 lm/W	7000 lm	6550 lm
927929584061	MASTER TL5 HO 80W/840 SLV/20	91 %	88 lm/W	82 lm/W	7000 lm	6550 lm
927929586557	MASTER TL5 HO 80W/865 SLV/40	91 %	83 lm/W	79 lm/W	6300 lm	6300 lm

MASTER TL5 High Output

