



# T12 lamp with reliable ignition

# **TL Rapid Start Standard Colours**

The TL RS (Rapid Start) lamp (tube diameter 38 mm) has an external silicon coating. It is suitable for situations where high humidity requires fast and stable ignition but color rendering is not important. Rapid Start lamps can be ignited without a starter.

#### **Benefits**

- · Creating atmospheres from warm white to cool daylight
- Fast, well-defined ignition at low temperatures

#### **Features**

- · RS (Rapid Start) lamps with an external silicon coating
- · Standard colors with moderate color rendering
- · Available in varying color designations

#### **Application**

· Mostly used in applications where color rendering is not an important factor

### Versions



# **TL Rapid Start Standard Colours**

## Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL RS 40W/54-765	40.5 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm
1SL/25					



© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.