



Product Description

Architectural MSD

Architectural MSD – single ended night colours The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent colour rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

Benefits

- High lumen output
- Low cost of ownership
- Excellent colours

Features

- Long lifetime
- Compact arc
- Excellent colour characteristics
- Universal burning position

Application



- Display lighting
- Architectural lighting
- Studio and disco lighting
- Fibre-optic lighting

Architectural MSD

Versions



Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD	42.5 mm	14.0	84 mm	86 mm	85	183 mm	54 mm	53	52 mm
1200.1CT/3		mm			mm			mm	

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD	40 mm	10.0	84 mm	86 mm	85	175 mm	54 mm	53	52 mm
700.1CT/3		mm			mm			mm	

General Information

Cap-Base	G22
Main Application	Studio/Disco
Operating Position	UNIVERSAL
System Description	na

Light Technical

Colour Code	-
Correlated Colour Temperature (Nom)	6000 K

Controls and Dimming

Architectural MSD

Order Code	Full Product Name	Dimmable
928170405114	MSD 700.1CT/3	yes

Order Code	Full Product Name	Dimmable
928172005114	MSD 1200.1CT/3	no

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928170405114	MSD 700.1CT/3	11 A	700 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928172005114	MSD 1200.1CT/3	13.8 A	1200 W

General Information

Order Code	Full Product Name	Life To 50% Failures (Nom)
928170405114	MSD 700.1CT/3	3000 h

Order Code	Full Product Name	Life To 50% Failures (Nom)
928172005114	MSD 1200.1CT/3	2000 h

Light Technical

Order Code	Full Product Name	Colour Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928170405114	MSD 700.1CT/3	75	46000 lm	50500 lm

Order Code	Full Product Name	Colour Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928172005114	MSD 1200.1CT/3	80	-	92000 lm

Colour Rendering Diagrams

