



# MSD Platinum – The power to light your creativity

## MSD Platinum (Touring/Stage)

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

### Vorteile

- High beam intensity
- Freedom to create smaller and lighter fixtures
- High perceived brightness
- A long and reliable performance

### Merkmale

- Very short arc
- Compact system
- High correlated color temperature
- Philips Platinum technology

### Anwendung





- Events
- Shows/Theater
- Tourneen/Bühne

# MSD Platinum (Touring/Stage)

## Versions



## Abmessungsskizzen






Product	D (max)	O	C (max)
MSD Platinum 400L Flex 1CT/8	54 mm	1,2 mm	60 mm
MSD Platinum 25 R 1CT/8	54 mm	1,4 mm	60 mm
MSD Platinum 21 R 1CT/8	54 mm	1,2 mm	60 mm

Product	D (max)	T (max)	O	C (max)
MSD Platinum 11 R 1CT/8	51,5 mm	10 mm	0,95 mm	53 mm

# MSD Platinum (Touring/Stage)

## Abmessungsskizzen



Product	D (max)	O	C (max)	T
MSD Platinum 200 Flex 1CT/8	56,5 mm	0,8 mm	60 mm	7 mm

Product	D (max)	T (max)	O	C (max)
MSD Platinum 14 R 1CT/8	51,5 mm	6,8 mm	0,95 mm	57,1 mm
MSD Platinum 5 R 1CT/8	51,4 mm	6,8 mm	1,0 mm	57,1 mm

### Dimmen

Dimmbar Ja

### Allgemeine Eigenschaften

Betriebsstellung UNIVERSAL

### Lichttechnische Daten

Farbcode 2

## Elektrische Kenndaten

Order Code	Full Product Name	Spannung (max.)	Spannung (min.)	Nennleistung (nom.)
93070200	MSD Platinum 5 R 1CT/8	-	-	189 W
44061200	MSD Platinum 14 R 1CT/8	-	-	280 W
53976700	MSD Platinum 11 R 1CT/8	80 V	55 V	250 W
67826800	MSD Platinum 21 R 1CT/8	-	-	470 W

Order Code	Full Product Name	Spannung (max.)	Spannung (min.)	Nennleistung (nom.)
80813900	MSD Platinum 200 Flex 1CT/8	-	55 V	240 W
61403400	MSD Platinum 25 R 1CT/8	115 V	85 V	550 W
65196100	MSD Platinum 400L Flex 1CT/8	110 V	85 V	470 W

## Allgemeine Eigenschaften

## MSD Platinum (Touring/Stage)

Order Code	Full Product Name	Sockel	Lebensdauer			Order Code	Full Product Name	Sockel	Lebensdauer		
			bis 50 % Ausfall (nom.)	Hauptanwendungsgebiet	Systembeschreibung				bis 50 % Ausfall (nom.)	Hauptanwendungsgebiet	Systembeschreibung
93070200	MSD Platinum 5 R 1CT/8	-	3000 h	Stage/Touring	Reflector-E20.6	21 R 1CT/8	-	-	-	-	
44061200	MSD Platinum 14 R 1CT/8	-	2000 h	Stage/Touring	Reflector-E20.6	200 Flex 1CT/8	-	-	-	-	
53976700	MSD Platinum 11 R 1CT/8	-	2000 h	Stage/Touring	Reflector-E20.9	25 R 1CT/8	-	1500 h	Stage/Touring	-	
67826800	MSD Platinum	-	1500 h	Stage/Touring	-	400L Flex 1CT/8	-	1500 h	Stage/Touring	-	

### Lichttechnische Daten

Order Code	Full Product Name	Ähnlichste			
		Farbtemperatur (nom.)	Farbwiedergabeindex (nom.)	Lichtstrom (min.)	Lichtstrom (nom.)
93070200	MSD Platinum 5 R 1CT/8	8000 K	-	7100 lm	7950 lm
44061200	MSD Platinum 14 R 1CT/8	7800 K	-	-	12350 lm
53976700	MSD Platinum 11 R 1CT/8	7800 K	-	-	12000 lm
67826800	MSD Platinum	8000 K	-	14100 lm	15600 lm

Order Code	Full Product Name	Ähnlichste			
		Farbtemperatur (nom.)	Farbwiedergabeindex (nom.)	Lichtstrom (min.)	Lichtstrom (nom.)
21 R 1CT/8					
80813900	MSD Platinum 200 Flex 1CT/8	7800 K	-	-	12000 lm
61403400	MSD Platinum 25 R 1CT/8	8000 K	-	22100 lm	24500 lm
65196100	MSD Platinum 400L Flex 1CT/8	8000 K	-	22100 lm	24500 lm

