



Product Description

MSR

MSR – bright vivid colours, always The high colour rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colours of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Benefits

- High luminous efficacy
- Compact arc (6 - 10 mm)
- Good colour rendering
- Dimmable with a stable colour temperature

Features

- Run-up time 2 minutes
- Restrike time 5 - 10 minutes, depending on cooling conditions



Application

- Studios and discos

Versions



Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm
MSR 1200/2.1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 400	23 mm	6.0	61 mm	63 mm	62	112 mm	36 mm	35	34 mm
1CT/4		mm			mm			mm	
MSR 575/2	30 mm	7.0	64 mm	66 mm	65	125 mm	36 mm	35	34 mm
10H 1CT/4		mm			mm			mm	

Controls and Dimming	
Dimmable	no
General Information	
Main Application	Studio/Disco
Operating Position	UNIVERSAL
System Description	Cold Strike

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928077905115	MSR 400 1CT/4	6.9 A	400 W
928171605115	MSR 575/2 10H 1CT/4	6.75 A	575 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928078105114	MSR 1200 1CT/3	13.8 A	1200 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928171805114	MSR 1200/2.1CT/3	13.8 A	1200 W

General Information

Order Code	Full Product Name	Cap-Base	Life To 50% Failures (Nom)
928077905115	MSR 400 1CT/4	GX9.5	1000 h
928171605115	MSR 575/2 10H 1CT/4	GX9.5	1000 h

Order Code	Full Product Name	Cap-Base	Life To 50% Failures (Nom)
928078105114	MSR 1200 1CT/3	G22	800 h
928171805114	MSR 1200/2.1CT/3	G22	800 h

Light Technical

Order Code	Full Product Name	Colour Code	Correlated Colour Temperature (Nom)	Colour Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928077905115	MSR 400 1CT/4	-	5900 K	95	28500 lm	32000 lm
928171605115	MSR 575/2 10H 1CT/4	2	6990 K	70	42750 lm	47500 lm
928078105114	MSR 1200 1CT/3	-	5900 K	80	94000 lm	110000 lm
928171805114	MSR 1200/2.1CT/3	2	7200 K	85	93600 lm	104000 lm

Colour Rendering Diagrams

