



Product Description

Halogen reflector

Quartz halogen lamps with integral reflector which serves as an efficient mirror condenser system

Benefits

- · Negligible depreciation in light output during lifetime
- $\boldsymbol{\cdot}$ High efficacy gives low energy consumption

Features

- Dichroic coating on glass reflector radiates about 75% of the generated heat backwards, keeping temperatures within safe limits
- Halogen burner is precisely aligned using an optical system, so no realignment is needed when the lamp is replaced

Application

- 8/16 mm film projection
- · Slide projection
- Enlargers
- · Minilabs/colour printers
- · Overhead projection
- Medical equipment
- Solar simulation
- Measuring equipment
- · Fibre optical applications

Halogen reflector

Versions









XPPR XHOPDI 0005



Halogen spot

Dimensional drawing





Light Technical	
Color rendering index (CRI)	100
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Material	Quartz-UV Open

General Information

Product	D (max)	C (max)
13629 150W GX5.3 21V 1CT/24	50.7 mm	44.5 mm
6423FO 150W GZ6.35 15V 1CT/10X5F	50 mm	42 mm
6834FO 100W GZ6.35 12V 1CT/10X5F	50 mm	42 mm
JCR 15V 150W H5 24 PACK	50 mm	43 mm

Product	D (max)	C (max)
13528 15W GZ4 6V 1CT/24	35 mm	42 mm

Halogen reflector

Order Code	Full Product Name	Cap-Base	Operating Position
924010319894	13629 150W GX5.3 21V 1CT/24	GX5.3	S90
924793618594	JCR 15V 150W H5 24 PACK	GZ6.35	S90
923883810105	13528 15W GZ4 6V 1CT/24	GZ4	S105

Order Code	Full Product Name	Cap-Base	Operating Position
924048218504	6423FO 150W GZ6.35 15V 1CT/10X5F	GZ6.35	P90/P15
924048417104	6834FO 100W GZ6.35 12V 1CT/10X5F	GZ6.35	P90/P15

Light Technical

		Correlated Color	
Order Code	Full Product Name	Temperature (Nom)	Luminous Flux
924010319894	13629 150W GX5.3 21V 1CT/24	-	-
924793618594	JCR 15V 150W H5 24 PACK	3100 K	-
923883810105	13528 15W GZ4 6V 1CT/24	2900 K	-
924048218504	6423FO 150W GZ6.35 15V 1CT/	3380 K	840 lm
	10X5F		

		Correlated Color	
Order Code	Full Product Name	Temperature (Nom)	Luminous Flux
924048417104	6834FO 100W GZ6.35 12V 1CT/	3330 K	-
	10X5F		

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
924010319894	13629 150W GX5.3 21V 1CT/24	21 V	150 W
924793618594	JCR 15V 150W H5 24 PACK	15 V	150 W
923883810105	13528 15W GZ4 6V 1CT/24	6 V	15 W
924048218504	6423FO 150W GZ6.35 15V 1CT/	15 V	150 W
	10X5F		

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
924048417104	6834FO 100W GZ6.35 12V 1CT/	12 V	100 W
	10X5F		

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
924010319894	13629 150W GX5.3 21V 1CT/24	-
924793618594	JCR 15V 150W H5 24 PACK	R50
923883810105	13528 15W GZ4 6V 1CT/24	R35

Order Code	Full Product Name	Bulb Shape
924048218504	6423FO 150W GZ6.35 15V 1CT/10X5F	R50
924048417104	6834FO 100W GZ6.35 12V 1CT/10X5F	R50



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.