



Actinic BL TL-D(K) Secura – additional safety and HACCP approval

Actinic BL TL-D(K) Secura

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL-D(K) Secura lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. In addition, they have a special "Secura" sleeve that keeps all glass and components together in the case of accidental breakage. This eliminates the risk of glass splinters showering down on food preparation areas, for example. And that is why it meets the strict HACCP requirements. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice.

Benefits

- Perfectly matches the eye sensitivity of houseflies and in this way attracts more insects
- Safe for use
- Good environmental choice
- No risk of glass particles

Features

- Emits long-wave UV-A radiation in the 350-400nm range
- UV-B/UV-A ratio less than 0.1 % (UV-B 280-315nm)
- 100% lead-free
- Low mercury content
- Shatterproof sleeve

Actinic BL TL-D(K) Secura


Application

- Insect traps, Electronic Fly Killers (EFKs)

Versions



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-D TL-D 18W/10 Secura 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm
Actinic BL TL-D TL-D 15W/10 Secura 1SL/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

General Information

Cap-Base	G13
Useful Life (Nom)	9000 h
Main Application	Reprography (R)

Light Technical

Colour Code	10
Colour Designation	Actinic

Mechanical and Housing

Bulb Shape	T26
------------	-----

UV

UV-B/UV-A (IEC)	0.2 %
-----------------	-------

Approval and Application

Order Code	Full Product Name	Mercury (Hg) Content (Nom)	Order Code	Full Product Name	Mercury (Hg) Content (Nom)
89858640	Actinic BL TL-D TL-D 15W/10 Secura 1SL/25	5.5 mg	85383400	Actinic BL TL-D TL-D 18W/10 Secura 1SL/25	5.0 mg

Actinic BL TL-D(K) Secura

Operating and Electrical

Order Code	Full Product Name	Lamp		Power
		Current (Nom)	Voltage (Nom)	(Rated) (Nom)
89858640	Actinic BL TL-D TL-D 15W/10 Secura 1SL/25	0.335 A	51 V	15 W

Order Code	Full Product Name	Lamp		Power
		Current (Nom)	Voltage (Nom)	(Rated) (Nom)
85383400	Actinic BL TL-D TL-D 18W/10 Secura 1SL/25	0.36 A	59 V	18 W

General Information

Order Code	Full Product Name	Life To 50% Failures (Nom)
89858640	Actinic BL TL-D TL-D 15W/10 Secura 1SL/25	11000 h

Order Code	Full Product Name	Life To 50% Failures (Nom)
85383400	Actinic BL TL-D TL-D 18W/10 Secura 1SL/25	13000 h

UV

Order Code	Full Product Name	UV-A Radiation 100Hr (IEC)
89858640	Actinic BL TL-D TL-D 15W/10 Secura 1SL/25	3.15 W

Order Code	Full Product Name	UV-A Radiation 100Hr (IEC)
85383400	Actinic BL TL-D TL-D 18W/10 Secura 1SL/25	4.5 W

