



Illuminating the exterior efficiently

Essential SmartBright LED

Philips Essential SmartBright LED Floodlight not only ensures savings on initial capital, but also delivers reliable operational savings.

Benefits

- Use with peace of mind
- Long-lasting performance
- High quality material and design
- Wide selection

Features

- 4KV surge protection
- IP65/IK07 protection
- 30khrs life
- Wide operating temperature range (-40°C to 45°C)
- High-quality exposed flat lense enhances safety
- Pressure die-cast housing offers excellent corrosion-resistance and robustness
- Multiple choice of colour temperature - warm white (3000k), neutral (4000k) and cool white (5700k)
- Multiple choice of lumen packages

Application

- Area lighting, bill-board, façade, industry area, recreational sports and other general applications

Essential Smartbright LED

Versions



BVP161 LED 100 W GREY

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Approval and Application

Mech. impact protection code	IK07
Surge Protection (Common/Differential)	EN61547 (L-L 2kV, L-G 4kV) kV

Controls and Dimming

Dimmable	No
----------	----

General Information

Luminaire light beam spread	30° x 80°
CE mark	CE mark
Optical cover/lens type	Micro-lens optic in polycarbonate cover, wide
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Lamp family code	LED90
Light source replaceable	No
Number of gear units	1 unit
Optic type	Symmetrical

Initial Performance (IEC Compliant)

Init. Colour Rendering Index	>80
Initial luminous flux	9000 lm

Light Technical

Standard tilt angle side entry	-
Standard tilt angle posttop	-
Upward light output ratio	0

Mechanical and Housing

Colour	grey
--------	------

General Information

Order Code	Full Product Name	Light source colour
911401823398	BVP161 LED90/CW 100W 220-240V WB GREY GM	857 daylight
911401823498	BVP161 LED90/NW 100W 220-240V WB GREY GM	840 neutral white

Initial Performance (IEC Compliant)

Essential Smartbright LED

Order Code	Full Product Name	Init. Corr. Colour Temperature
911401823398	BVP161 LED90/CW 100W 220-240V WB GREY GM	5700 K

Order Code	Full Product Name	Init. Corr. Colour Temperature
911401823498	BVP161 LED90/NW 100W 220-240V WB GREY GM	4000 K

