



Energy-efficient lighting for industrial and commercial applications

GreenPerform Trunking

With Philips GreenPerform Trunking, industry and supermarket owners have an innovative LED solution that intelligently combines high-performance lighting features with maximised energy savings. This solution is designed to boost productivity and enhance shopping experience without compromising performance and energy efficiency. Suitable for a wide range of applications, GreenPerform Trunking is safe, reliable, and versatile, the perfect direct replacement for conventional fluorescent trunking.

Benefits

- A system efficacy of 108lm/w, providing up to 50% energy saving when replacing 2 x 58w fluorescent trunking. Designed for 70% lumen maintenance over 50,000 hours ensuring reliable performance over the product lifetime.
- Specially designed plastic caps improve uniformity along the length leading to a more uniform lighting distribution.
- 3 different beam angles available (Double asymmetric / Wide-beam / Opal) enabling you to choose the most optimum solution for different applications.
- An integrated modular design with 3-phase 5-wire connection ensuring easy and flexible installation, and the possibility of controlling each phase separately.

Features

- Philips Fortimo LED Line 1R for high efficiency and reliability
- Advanced optics enable precise and energy-saving beam shapes
- Requires much less packaging than fluorescent

GreenPerform Trunking

Application

- Supermarkets
- Warehouses
- Production facilities

Versions



LL120X LED35/LED70 L1500



LL120X LED70/LED140 L3000

Application Conditions

Ambient temperature range	-20 to +35 °C
Suitable for random switching	No

Approval and Application

Mech. impact protection code	IK02
Ingress protection code	IP20

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Voltage	220-240 V
---------------	-----------

General Information

Beam angle of light source	90 x 90 °
CE mark	CE mark
Protection class IEC	Safety class I (I)
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Gear	-
Glow-wire test	650/30
Light source replaceable	No
UL mark	-

Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM <5
Init. Corr. Colour Temperature	4000 K
Init. Colour Rendering Index	80
Initial LED luminaire efficacy	108.571 lm/W
Luminous flux tolerance	+/-7.5%

Mechanical and Housing

Colour	White
--------	-------

Over Time Performance (IEC Compliant)

Median useful life L80B50	40000 h
Median useful life L90B50	20000 h

General Information

Order Code	Full Product Name	Optical cover/ lens type	Lamp family code	Number of gear units	Optic type
01582021	LL120X LED70 L1500 NW PSU 5 OP ENG	O	LED76S	1 unit	WB
01582121	LL120X LED70 L1500 NW PSU 5 DA ENG	LIN-PC	LED76S	1 unit	DA
01584521	LL120X LED140 L3000 NW PSU 5 OP ENG	O	LED152	2 units	WB
01584721	LL120X LED140 L3000 NW PSU 5 DA ENG	LIN-PC	LED152	2 units	DA

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial luminous flux	Initial input power
01582021	LL120X LED70 L1500 NW PSU 5 OP ENG	7600 lm	70 W
01582121	LL120X LED70 L1500 NW PSU 5 DA ENG	7600 lm	70 W

Order Code	Full Product Name	Initial luminous flux	Initial input power
01584521	LL120X LED140 L3000 NW PSU 5 OP ENG	15200 lm	140 W
01584721	LL120X LED140 L3000 NW PSU 5 DA ENG	15200 lm	140 W

