



Energy-efficient lighting for industrial and commercial applications

GreenUp Highbay

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Actilume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W highbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Actilume Wireless, GreenUp BY550 provide connected lighting with daylight, occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

Benefits

- Energy savings of fix version up to 75% vs. HID 400W Systems and up to 56% vs. T5 Highbay
- Comfortable light with low glare and accurate color
- Easy to use, easy to design in and low installation cost

Features

- High system efficiency
- Reliable
- Wide Beam, Narrow Beam & High Rack Optic Beam
- Unique air convection design enables efficient heat dissipation
- Connected lighting

Application

- General Industry Application
- High Rack Warehouse

Versions



BY550P LED140

BY550P LED200

Application Conditions	
Ambient temperature range	-20 to +40 °C
Maximum dim level	Not applicable
Approval and Application	
Mech. impact protection code	IK03
Ingress protection code	IP20
Controls and Dimming	
Dimmable	No
Operating and Electrical	
Input Voltage	220-240 V
General Information	
CE mark	CE mark
Protection class IEC	Safety class I (I)
Optical cover/lens type	PCC
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Gear	-
Glow-wire test	650/30
Light source replaceable	No
Number of gear units	2 units
Optic type	WB
UL mark	-
Initial Performance (IEC Compliant)	
Initial chromaticity	-
Init. Corr. Colour Temperature	4000 K
Init. Colour Rendering Index	>85
Luminous flux tolerance	+/-7.5%
Mechanical and Housing	
Colour	white

General Information

Order Code	Full Product Name	Lamp family code
01524821	BY550P LED140/NW PSU WB	LED140
01525421	BY550P LED200/NW PSU WB	LED206

Initial Performance (IEC Compliant)

GreenUp Highbay

Order Code	Full Product Name	Initial input power	Order Code	Full Product Name	Initial input power
01524821	BY550P LED140/NW PSU WB	110 W	01525421	BY550P LED200/NW PSU WB	160 W

