



Best Area Lighting Luminaire within Your Budget

Tango G2 LED

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Benefits

- Energy saving: more than 50% of energy saving when compared to conventional floodlight
- Free from lamp replacement
- Low maintenance cost: IP65 housing ensures low maintenance with no need for internal cleaning, resulting in a lower total cost of ownership

Features


- Optical beam choice of symmetric and asymmetric fulfils majority needs of lighting application
- Painted non-corrosive die-cast aluminum housing and steel bracket
- Universal "U" shape mounting bracket

Application

- Area lighting
- Industry area
- Façade

Tango G2 LED

Versions



BVP283 220-240V

Approval and Application

Mech. impact protection code	IK08
------------------------------	------

General Information

CE mark	CE mark
Light source colour	740 neutral white
Optical cover/lens type	PC-MLO
Driver included	Yes

Initial Performance (IEC Compliant)

Init. Corr. Colour Temperature	4000 K
Init. Colour Rendering Index	>70
Initial luminous flux	43000 lm

Mechanical and Housing

Colour	Aluminium and Grey
--------	--------------------

Controls and Dimming

Order Code	Full Product Name	Dimmable
911401697705	BVP283 LED430/NW 335W 220-240V AWB	No
911401697905	BVP283 LED430/NW 335W 220-240V NB	No
911401698005	BVP283 LED430/NW 335W 220-240V SWB	No
911401698105	BVP283 LED430/NW 335W AWB P7 GM	Yes

