



Illuminating the future. High performance floodlight solution.

Tempo LED Floodlight

Tempo LED Floodlights are highly versatile and are designed to meet diverse application requirements, including advertising hoardings, high mast poles, building facade, sport stadiums (non professional), parking spaces, or indoor industrial workspaces. Not only do Tempo LED Floodlights provide illumination of high performance, they also combine functionality with aesthetics, without compromising on cost efficiency and reliability.

Benefits

- Designed to optimise advertising hoarding illumination as well as meet other diverse application requirements
- Modern design, outstanding quality
- Energy-saving, easy replacement

Features

- 6KV high surge protection
- Up to 100lm/w high system efficacy
- Able to replace up to 400 HID floodlight
- Warm white (3000K), Neutral (4000K), Cool white (5700K)
- UV-resistant, and IP65 dust and jet water-proof flat lens

Application

- Area lighting, bill-board, façade, industry area, recreational sports and other general applications

Tempo LED Floodlight

Versions



BVP162/BVP163 220-240V SWB



BVP162 LED110

Approval and Application

Mech. impact protection code IK07

Controls and Dimming

Dimmable No

General Information

CE mark CE mark

Optical cover/lens type PC

Driver included Yes

Flammability mark F

Light source replaceable No

Initial Performance (IEC Compliant)

Init. Colour Rendering Index >70

Mechanical and Housing

Colour Gray

General Information

Order Code	Full Product Name	Light source colour
30462599	BVP163 LED220/NW 220W 220-240V SWB GM	740 neutral white
30464999	BVP163 LED200/WW 220W 220-240V SWB GM	730 warm white
30465699	BVP162 LED100/WW 110W 220-240V SWB GM	730 warm white
30466399	BVP163 LED220/CW 220W 220-240V SWB GM	757 cool white
30467099	BVP162 LED110/CW 110W 220-240V SWB GM	757 cool white
30463299	BVP162 LED110/NW 110W 220-240V SWB GM	740 neutral white

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux
30462599	BVP163 LED220/NW 220W 220-240V SWB GM	4000 K	22000 lm
30464999	BVP163 LED200/WW 220W 220-240V SWB GM	3000 K	20000 lm
30465699	BVP162 LED100/WW 110W 220-240V SWB GM	3000 K	10000 lm

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux
30466399	BVP163 LED220/CW 220W 220-240V SWB GM	5700 K	22000 lm
30467099	BVP162 LED110/CW 110W 220-240V SWB GM	5700 K	11000 lm
30463299	BVP162 LED110/NW 110W 220-240V SWB GM	4000 K	11000 lm

Tempo LED Floodlight

