



# Illuminating the future. High performance floodlight solution.

## Tempo LED Floodlight

Tempo LED Floodlights are highly versatile and are designed to meet diverse application requirements, including advertising hoardings, high mast poles, building facade, sport stadiums(non professional), parking spaces, or indoor industrial workspaces. Not only do Tempo LED Floodlights provide illumination of high performance, they also combine functionality with aesthetics, without compromising on cost efficiency and reliability.

### Benefits

- Designed to optimise advertising hoarding illumination as well as meet other diverse application requirements
- Modern design, outstanding quality
- Energy-saving, easy replacement

### Features

- 6KV high surge protection
- Up to 100lm/w high system efficacy
- Able to replace up to 400 HID floodlight
- Warm white (3000K), Neutral (4000K), Cool white (5700K)
- UV-resistant, and IP65 dust and jet water-proof flat lens

### Application

- Area lighting, bill-board, façade, industry area, recreational sports and other general applications

# Tempo LED Floodlight

## Versions



### BVP162/BVP163 220-240V SWB

#### Approval and Application

Mech. impact protection code	IK07
------------------------------	------

#### Controls and Dimming

Dimmable	No
----------	----

#### General Information

CE mark	CE mark
Optical cover/lens type	PC
Driver included	Yes
Flammability mark	F
Light source replaceable	No

#### Initial Performance (IEC Compliant)

Init. Colour Rendering Index	>70
------------------------------	-----

#### Mechanical and Housing

Colour	Grey
--------	------

#### General Information

Order Code	Full Product Name	Light source colour
911401688002	BVP162 LED100/WW 110W 220-240V SWB	730 warm white
911401697202	BVP163 LED220/CW 220W 220-240V SWB GM	757 cool white
911401697302	BVP162 LED110/CW 110W 220-240V SWB GM	757 cool white

#### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux
911401688002	BVP162 LED100/WW 110W 220-240V SWB	3000 K	10000 lm



## Tempo LED Floodlight

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux
911401697202	BVP163 LED220/CW 220W 220-240V SWB GM	5700 K	22000 lm
911401697302	BVP162 LED110/CW 110W 220-240V SWB GM	5700 K	11000 lm

