



CitySoul gen2 LED – a versatile identity

CitySoul gen2 LED Large

CitySoul gen2 LED is one of the most versatile and inspirational urban street lighting families designed by Philips to date. This highly efficient range delivers excellent lighting levels whilst also providing the right ambiance for all urban application areas, from the outskirts of the city right through to the city center. By evolving the modularity of the CitySoul family and adding new innovations like the Lyre and the Accent bracket, Philips has made this range the ideal toolbox for every urban context. The design is flatter, completely round, and the transitions with the spigot and bracket entirely flush, thereby giving your cityscape a coherent, elegant and discreet identity. Designed around its LED engine, CitySoul gen2 LED is highly efficient and easy to maintain. It comes in two sizes and is suitable for side-entry, post-top, catenary and suspended mounting.

Benefits

- An integrated UrbanStyling lighting toolbox designed for many different urban applications
- Luminaires, brackets and poles are designed as one integrated concept to ensure coherence
- Future-proof thanks to excellent lighting performance and product quality

Features

- A broad range of elegant, dedicated and complete sets, including poles and brackets, a tiltable option, double post-top and catenary versions
- Various features to deliver the most efficient and comfortable lighting level
- Compatible with all Philips' standard and advanced lighting controls
- Easy maintenance on-site
- Compatible with existing CitySoul pole and bracket range Flip, Morph, Jump, Sweep

CitySoul gen2 LED Large

Application

- City centers
- Parks and plazas
- Roads and streets
- Commercial districts

Specifications

Type	BPP531 (post top version)
	BRP531 (side entry version)
	BSP531 (catenary or suspended version)
	BVP531 (dedicated for Right Curve bracket)
	BGP531 MBA CD (dedicated for Graphic and East bracket)
Light source	Integral LED-module
Power	GreenLine (GRN): 38-138 W depending on configuration
Luminous flux (system)	4250-13,000 lm (3000 K)
	4600-14,800 lm (4000 K)
Luminaire efficacy (system)	Up to 110 lm/W
Correlated Color	3000 K, warm white
Temperature	4000 K, neutral white
Color Rendering Index	≥ 70, neutral white
	≥ 80, warm white

Maintenance of lumen output - L80B10	100,000 hours
Operating temperature range	-20 to +35 °C
Driver	Built-in (self ballasted LED-module)
Mains voltage	210-240 V / 50-60 Hz
Inrush current	80 A / 150 µs (75 W driver)
	108 A / 140 µs (150 W driver)
Dimming	DynaDimmer
	LumiStep
	CLO
Controls system input	DALI
	StarSense RF
	LightWave (GPRS)

Versions



Product details



CitySoul gen2 LED Large

Product details



CitySoul gen2 LED Large

Product details

