



# CoreLine Downlight – The clear choice for LED

## CoreLine Downlight

The CoreLine Downlight range of recessed luminaires is designed to replace CFL-ni/CFL-i based downlight luminaires. Their attractive TCO helps customers to make the switch to LED. These luminaires create a natural lighting effect for use in general lighting applications. They also deliver instant energy savings and have a much longer lifetime, creating a real value-for-money and environmentally friendly solution. They are easy to install thanks to their standard cut-out size and push-in connectors.

### Benefits

- Reduced operating costs thanks to energy saving and longer lifetime
- One-to-one replacement, facilitating the switch from conventional to LED luminaires
- Suitable for professional applications thanks to DALI dimming and aluminum reflector

### Features

- Available in 1100 and 2100 lumen versions
- Energy-efficient: up to 100 lm/W
- DALI version available
- Choice of color temperature: 3000 and 4000 K
- Protected glass available as an option (also enables IP44 protection)

### Application

- General lighting in corridors
- Retail stores
- Reception areas
- Indoor circulation areas

# CoreLine Downlight

## Specifications

<b>Type</b>	DN130B (version with white reflector) DN131B (version with aluminum reflector)
<b>Ceiling type</b>	Plaster (board) ceiling
<b>Light source</b>	Non replaceable LED module
<b>Power</b>	11 W (1100 lm) 22 W (2100 lm)
<b>Efficacy</b>	Up to 100 lm/W
<b>Luminous flux</b>	1100 lm 2100 lm
<b>Correlated Color</b>	3000 K (Warm white)
<b>Temperature</b>	4000 K (Neutral white)
<b>Color Rendering Index</b>	80
<b>Median useful life</b>	50,000 hours
<b>L70B50</b>	
<b>Median useful life</b>	30,000 hours
<b>L80B50</b>	
<b>Median useful life</b>	15,000 hours
<b>L90B50</b>	
<b>Driver failure rate</b>	1.5% per 5000 hours
<b>Average ambient temperature</b>	+25 °C

<b>Operating temperature range</b>	-10 to +40 °C
<b>Driver</b>	Built-in External, with DALI interface
<b>Mains voltage</b>	230 or 240 V / 50-60 Hz
<b>Dimming</b>	DALI dimmable Not dimmable
<b>Controls system input</b>	DALI
<b>Material</b>	Housing: plastic Reflector: plastic
<b>Color</b>	DN130B: white reflector / white rim DN131B: aluminium reflector / white rim
<b>Optic</b>	Reflector, white / aluminum
<b>Connection</b>	Push-in connector with pull relief
<b>Installation</b>	Fixation by spring fasteners Through-wiring possible (not for DALI version)
<b>Accessories</b>	Protected glass also creating IP44
<b>Remarks</b>	DALI version has external driver

## Versions



# CoreLine Downlight

## Approval and Application

Mech. impact protection code	IK02
------------------------------	------

## Operating and Electrical

Input Voltage	220-240 V
---------------	-----------

## General Information

Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class I (I)
Driver included	Yes
ENEC mark	-
Flammability mark	F
Glow-wire test	850/5
Light source replaceable	No
Number of gear units	1 unit

## Initial Performance (IEC Compliant)

Init. Colour Rendering Index	≥80
Luminous flux tolerance	+/-10%

## Mechanical and Housing

Colour	White RAL 9003
--------	----------------

## Application Conditions

Order Code	Full Product Name	Ambient temperature range	Maximum dim level
32580400	DN140B LED10S/830 PSU WR PI6	-20 to +40 °C	Not applicable
32581100	DN140B LED10S/840 PSU WR PI6	-20 to +40 °C	Not applicable
32582899	DN140B LED10S/830 PSD-E WR	-20 to +40 °C	1%
32583599	DN140B LED10S/840 PSD-E WR	-20 to +40 °C	1%
32832400	DN140B LED10S/840 PSD-E WR ELB3	0 to +35 °C	1%
32584200	DN140B LED20S/830 PSU WR PI6	-20 to +40 °C	Not applicable
32585900	DN140B LED20S/840 PSU WR PI6	-20 to +40 °C	Not applicable
32586699	DN140B LED20S/830 PSD-E WR	-20 to +40 °C	1%
32587399	DN140B LED20S/840 PSD-E WR	-20 to +40 °C	1%
32612200	DN140B LED20S/830 WR IA1	-20 to +40 °C	1%
32613900	DN140B LED20S/840 WR IA1	-20 to +40 °C	1%
32834800	DN140B LED20S/840 PSD-E WR ELB3	0 to +35 °C	1%
32588000	DN140B LED10S/830 PSU C PI6	-20 to +40 °C	Not applicable
32589700	DN140B LED10S/840 PSU C PI6	-20 to +40 °C	Not applicable
32590399	DN140B LED10S/830 PSD-E C	-20 to +40 °C	1%
32591099	DN140B LED10S/840 PSD-E C	-20 to +40 °C	1%
32592700	DN140B LED20S/830 PSU C PI6	-20 to +40 °C	Not applicable
32593400	DN140B LED20S/840 PSU C PI6	-20 to +40 °C	Not applicable
32594199	DN140B LED20S/830 PSD-E C	-20 to +40 °C	1%
32595899	DN140B LED20S/840 PSD-E C	-20 to +40 °C	1%
32614600	DN140B LED20S/830 C IA1	-20 to +40 °C	1%
32615300	DN140B LED20S/840 C IA1	-20 to +40 °C	1%
32838600	DN140B LED20S/840 PSD-E C ELB3	0 to +35 °C	1%
32596500	DN140B LED10S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32597200	DN140B LED10S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32598900	DN140B LED10S/830 PSD-E WR IP54	-20 to +40 °C	1%
32599600	DN140B LED10S/840 PSD-E WR IP54	-20 to +40 °C	1%
32600900	DN140B LED20S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32601600	DN140B LED20S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32602300	DN140B LED20S/830 PSD-E WR IP54	-20 to +40 °C	1%
32603000	DN140B LED20S/840 PSD-E WR IP54	-20 to +40 °C	1%
32604700	DN140B LED10S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32605400	DN140B LED10S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32606100	DN140B LED10S/830 PSD-E C IP54	-20 to +40 °C	1%
32607800	DN140B LED10S/840 PSD-E C IP54	-20 to +40 °C	1%
32608500	DN140B LED20S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32609200	DN140B LED20S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32610800	DN140B LED20S/830 PSD-E C IP54	-20 to +40 °C	1%
32611500	DN140B LED20S/840 PSD-E C IP54	-20 to +40 °C	1%

## Approval and Application

Order Code	Full Product Name	Ingress protection code	Order Code	Full Product Name	Ingress protection code
32580400	DN140B LED10S/830 PSU WR PI6	IP20	32586699	DN140B LED20S/830 PSD-E WR	IP20
32581100	DN140B LED10S/840 PSU WR PI6	IP20	32587399	DN140B LED20S/840 PSD-E WR	IP20
32582899	DN140B LED10S/830 PSD-E WR	IP20	32612200	DN140B LED20S/830 WR IA1	IP20
32583599	DN140B LED10S/840 PSD-E WR	IP20	32613900	DN140B LED20S/840 WR IA1	IP20
32832400	DN140B LED10S/840 PSD-E WR ELB3	IP20	32834800	DN140B LED20S/840 PSD-E WR ELB3	IP20
32584200	DN140B LED20S/830 PSU WR PI6	IP20	32588000	DN140B LED10S/830 PSU C PI6	IP20
32585900	DN140B LED20S/840 PSU WR PI6	IP20	32589700	DN140B LED10S/840 PSU C PI6	IP20

## CoreLine Downlight

Order Code	Full Product Name	Ingress protection code
32590399	DN140B LED10S/830 PSD-E C	IP20
32591099	DN140B LED10S/840 PSD-E C	IP20
32592700	DN140B LED20S/830 PSU C PI6	IP20
32593400	DN140B LED20S/840 PSU C PI6	IP20
32594199	DN140B LED20S/830 PSD-E C	IP20
32595899	DN140B LED20S/840 PSD-E C	IP20
32614600	DN140B LED20S/830 C IA1	IP20
32615300	DN140B LED20S/840 C IA1	IP20
32838600	DN140B LED20S/840 PSD-E C ELB3	IP20
32596500	DN140B LED10S/830 PSU WR IP54 PI6	IP20/54
32597200	DN140B LED10S/840 PSU WR IP54 PI6	IP20/54
32598900	DN140B LED10S/830 PSD-E WR IP54	IP20/54
32599600	DN140B LED10S/840 PSD-E WR IP54	IP20/54

Order Code	Full Product Name	Ingress protection code
32600900	DN140B LED20S/830 PSU WR IP54 PI6	IP20/54
32601600	DN140B LED20S/840 PSU WR IP54 PI6	IP20/54
32602300	DN140B LED20S/830 PSD-E WR IP54	IP20/54
32603000	DN140B LED20S/840 PSD-E WR IP54	IP20/54
32604700	DN140B LED10S/830 PSU C IP54 PI6	IP20/54
32605400	DN140B LED10S/840 PSU C IP54 PI6	IP20/54
32606100	DN140B LED10S/830 PSD-E C IP54	IP20/54
32607800	DN140B LED10S/840 PSD-E C IP54	IP20/54
32608500	DN140B LED20S/830 PSU C IP54 PI6	IP20/54
32609200	DN140B LED20S/840 PSU C IP54 PI6	IP20/54
32610800	DN140B LED20S/830 PSD-E C IP54	IP20/54
32611500	DN140B LED20S/840 PSD-E C IP54	IP20/54

### Controls and Dimming

Order Code	Full Product Name	Dimmable
32580400	DN140B LED10S/830 PSU WR PI6	No
32581100	DN140B LED10S/840 PSU WR PI6	No
32582899	DN140B LED10S/830 PSD-E WR	Yes
32583599	DN140B LED10S/840 PSD-E WR	Yes
32832400	DN140B LED10S/840 PSD-E WR ELB3	Yes
32584200	DN140B LED20S/830 PSU WR PI6	No
32585900	DN140B LED20S/840 PSU WR PI6	No
32586699	DN140B LED20S/830 PSD-E WR	Yes
32587399	DN140B LED20S/840 PSD-E WR	Yes
32612200	DN140B LED20S/830 WR IA1	Yes
32613900	DN140B LED20S/840 WR IA1	Yes
32834800	DN140B LED20S/840 PSD-E WR ELB3	Yes
32588000	DN140B LED10S/830 PSU C PI6	No
32589700	DN140B LED10S/840 PSU C PI6	No
32590399	DN140B LED10S/830 PSD-E C	Yes
32591099	DN140B LED10S/840 PSD-E C	Yes
32592700	DN140B LED20S/830 PSU C PI6	No
32593400	DN140B LED20S/840 PSU C PI6	No
32594199	DN140B LED20S/830 PSD-E C	Yes
32595899	DN140B LED20S/840 PSD-E C	Yes

Order Code	Full Product Name	Dimmable
32614600	DN140B LED20S/830 C IA1	Yes
32615300	DN140B LED20S/840 C IA1	Yes
32838600	DN140B LED20S/840 PSD-E C ELB3	Yes
32596500	DN140B LED10S/830 PSU WR IP54 PI6	No
32597200	DN140B LED10S/840 PSU WR IP54 PI6	No
32598900	DN140B LED10S/830 PSD-E WR IP54	Yes
32599600	DN140B LED10S/840 PSD-E WR IP54	Yes
32600900	DN140B LED20S/830 PSU WR IP54 PI6	No
32601600	DN140B LED20S/840 PSU WR IP54 PI6	No
32602300	DN140B LED20S/830 PSD-E WR IP54	Yes
32603000	DN140B LED20S/840 PSD-E WR IP54	Yes
32604700	DN140B LED10S/830 PSU C IP54 PI6	No
32605400	DN140B LED10S/840 PSU C IP54 PI6	No
32606100	DN140B LED10S/830 PSD-E C IP54	Yes
32607800	DN140B LED10S/840 PSD-E C IP54	Yes
32608500	DN140B LED20S/830 PSU C IP54 PI6	No
32609200	DN140B LED20S/840 PSU C IP54 PI6	No
32610800	DN140B LED20S/830 PSD-E C IP54	Yes
32611500	DN140B LED20S/840 PSD-E C IP54	Yes

### General Information

Order Code	Full Product Name	Optic type	Product Family Code
32580400	DN140B LED10S/830 PSU WR PI6	WR	-
32581100	DN140B LED10S/840 PSU WR PI6	WR	-
32582899	DN140B LED10S/830 PSD-E WR	WR	DN140B
32583599	DN140B LED10S/840 PSD-E WR	WR	DN140B
32832400	DN140B LED10S/840 PSD-E WR ELB3	WR	DN140B
32584200	DN140B LED20S/830 PSU WR PI6	WR	-
32585900	DN140B LED20S/840 PSU WR PI6	WR	-
32586699	DN140B LED20S/830 PSD-E WR	WR	DN140B
32587399	DN140B LED20S/840 PSD-E WR	WR	DN140B
32612200	DN140B LED20S/830 WR IA1	WR	-

Order Code	Full Product Name	Optic type	Product Family Code
32613900	DN140B LED20S/840 WR IA1	WR	-
32834800	DN140B LED20S/840 PSD-E WR ELB3	WR	DN140B
32588000	DN140B LED10S/830 PSU C PI6	C	-
32589700	DN140B LED10S/840 PSU C PI6	C	-
32590399	DN140B LED10S/830 PSD-E C	C	DN140B
32591099	DN140B LED10S/840 PSD-E C	C	DN140B
32592700	DN140B LED20S/830 PSU C PI6	C	-
32593400	DN140B LED20S/840 PSU C PI6	C	-
32594199	DN140B LED20S/830 PSD-E C	C	DN140B
32595899	DN140B LED20S/840 PSD-E C	C	DN140B

## CoreLine Downlight

Order Code	Full Product Name	Optic type	Product Family Code
32614600	DN140B LED20S/830 C IA1	C	-
32615300	DN140B LED20S/840 C IA1	C	-
32838600	DN140B LED20S/840 PSD-E C ELB3	C	DN140B
32596500	DN140B LED10S/830 PSU WR IP54 PI6	WR	-
32597200	DN140B LED10S/840 PSU WR IP54 PI6	WR	-
32598900	DN140B LED10S/830 PSD-E WR IP54	WR	DN140B
32599600	DN140B LED10S/840 PSD-E WR IP54	WR	DN140B
32600900	DN140B LED20S/830 PSU WR IP54 PI6	WR	-
32601600	DN140B LED20S/840 PSU WR IP54 PI6	WR	-
32602300	DN140B LED20S/830 PSD-E WR IP54	WR	DN140B

Order Code	Full Product Name	Optic type	Product Family Code
32603000	DN140B LED20S/840 PSD-E WR IP54	WR	DN140B
32604700	DN140B LED10S/830 PSU C IP54 PI6	C	-
32605400	DN140B LED10S/840 PSU C IP54 PI6	C	-
32606100	DN140B LED10S/830 PSD-E C IP54	C	DN140B
32607800	DN140B LED10S/840 PSD-E C IP54	C	DN140B
32608500	DN140B LED20S/830 PSU C IP54 PI6	C	-
32609200	DN140B LED20S/840 PSU C IP54 PI6	C	-
32610800	DN140B LED20S/830 PSD-E C IP54	C	DN140B
32611500	DN140B LED20S/840 PSD-E C IP54	C	DN140B

### Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32580400	DN140B LED10S/830 PSU WR PI6	(0.435,0.405)	3000 K	116 lm/W	1100 lm
32581100	DN140B LED10S/840 PSU WR PI6	(0.381,0.379)	4000 K	116 lm/W	1100 lm
32582899	DN140B LED10S/830 PSD-E WR	(0.435,0.405)	3000 K	96 lm/W	1100 lm
32583599	DN140B LED10S/840 PSD-E WR	(0.381,0.379)	4000 K	96 lm/W	1100 lm
32832400	DN140B LED10S/840 PSD-E WR ELB3	(0.381,0.379)	4000 K	76 lm/W	1100 lm
32584200	DN140B LED20S/830 PSU WR PI6	(0.435,0.404)	3000 K	116 lm/W	2200 lm
32585900	DN140B LED20S/840 PSU WR PI6	(0.380,0.377)	4000 K	116 lm/W	2200 lm
32586699	DN140B LED20S/830 PSD-E WR	(0.435,0.404)	3000 K	107 lm/W	2200 lm
32587399	DN140B LED20S/840 PSD-E WR	(0.380,0.377)	4000 K	107 lm/W	2200 lm
32612200	DN140B LED20S/830 WR IA1	(0.435,0.404)	3000 K	100 lm/W	2200 lm
32613900	DN140B LED20S/840 WR IA1	(0.380,0.377)	4000 K	100 lm/W	2200 lm
32834800	DN140B LED20S/840	(0.380,0.377)	4000 K	94 lm/W	2200 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32588000	DN140B LED10S/830 PSU C PI6	(0.433,0.405)	3000 K	116 lm/W	1100 lm
32589700	DN140B LED10S/840 PSU C PI6	(0.379,0.379)	4000 K	116 lm/W	1100 lm
32590399	DN140B LED10S/830 PSD-E C	(0.433,0.405)	3000 K	96 lm/W	1100 lm
32591099	DN140B LED10S/840 PSD-E C	(0.379,0.379)	4000 K	96 lm/W	1100 lm
32592700	DN140B LED20S/830 PSU C PI6	(0.432,0.404)	3000 K	116 lm/W	2200 lm
32593400	DN140B LED20S/840 PSU C PI6	(0.378,0.377)	4000 K	116 lm/W	2200 lm
32594199	DN140B LED20S/830 PSD-E C	(0.432,0.404)	3000 K	107 lm/W	2200 lm
32595899	DN140B LED20S/840 PSD-E C	(0.378,0.377)	4000 K	107 lm/W	2200 lm
32614600	DN140B LED20S/830 C IA1	(0.432,0.404)	3000 K	100 lm/W	2200 lm
32615300	DN140B LED20S/840 C IA1	(0.378,0.377)	4000 K	100 lm/W	2200 lm
32838600	DN140B LED20S/840 PSD-E C ELB3	(0.378,0.377)	4000 K	94 lm/W	2200 lm

## CoreLine Downlight

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32596500	DN140B LED10S/830 PSU WR IP54 P16	(0.435,0.405)	3000 K	116 lm/W	1100 lm
32597200	DN140B LED10S/840 PSU WR IP54 P16	(0.381,0.379)	4000 K	116 lm/W	1100 lm
32598900	DN140B LED10S/830 PSD-E WR IP54	(0.435,0.405)	3000 K	96 lm/W	1100 lm
32599600	DN140B LED10S/840 PSD-E WR IP54	(0.381,0.379)	4000 K	96 lm/W	1100 lm
32600900	DN140B LED20S/830 PSU WR IP54 P16	(0.435,0.404)	3000 K	116 lm/W	2200 lm
32601600	DN140B LED20S/840 PSU WR IP54 P16	(0.380,0.377)	4000 K	116 lm/W	2200 lm
32602300	DN140B LED20S/830 PSD-E WR IP54	(0.435,0.404)	3000 K	107 lm/W	2200 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32603000	DN140B LED20S/840 PSD-E WR IP54	(0.380,0.377)	4000 K	107 lm/W	2200 lm
32604700	DN140B LED10S/830 PSU C IP54 P16	(0.433,0.405)	3000 K	116 lm/W	1100 lm
32605400	DN140B LED10S/840 PSU C IP54 P16	(0.379,0.379)	4000 K	116 lm/W	1100 lm
32606100	DN140B LED10S/830 PSD-E C IP54	(0.433,0.405)	3000 K	96 lm/W	1100 lm
32607800	DN140B LED10S/840 PSD-E C IP54	(0.379,0.379)	4000 K	96 lm/W	1100 lm
32608500	DN140B LED20S/830 PSU C IP54 P16	(0.432,0.404)	3000 K	116 lm/W	2200 lm
32609200	DN140B LED20S/840 PSU C IP54 P16	(0.378,0.377)	4000 K	116 lm/W	2200 lm
32610800	DN140B LED20S/830 PSD-E C IP54	(0.432,0.404)	3000 K	107 lm/W	2200 lm
32611500	DN140B LED20S/840 PSD-E C IP54	(0.378,0.377)	4000 K	107 lm/W	2200 lm

### Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial input power
32580400	DN140B LED10S/830 PSU WR P16	9.5 W
32581100	DN140B LED10S/840 PSU WR P16	9.5 W
32582899	DN140B LED10S/830 PSD-E WR	11.5 W
32583599	DN140B LED10S/840 PSD-E WR	11.5 W
32832400	DN140B LED10S/840 PSD-E WR ELB3	14.5 W
32584200	DN140B LED20S/830 PSU WR P16	19 W
32585900	DN140B LED20S/840 PSU WR P16	19 W
32586699	DN140B LED20S/830 PSD-E WR	20.5 W
32587399	DN140B LED20S/840 PSD-E WR	20.5 W
32612200	DN140B LED20S/830 WR IA1	22 W
32613900	DN140B LED20S/840 WR IA1	22 W
32834800	DN140B LED20S/840 PSD-E WR ELB3	23.5 W
32588000	DN140B LED10S/830 PSU C P16	9.5 W
32589700	DN140B LED10S/840 PSU C P16	9.5 W
32590399	DN140B LED10S/830 PSD-E C	11.5 W
32591099	DN140B LED10S/840 PSD-E C	11.5 W
32592700	DN140B LED20S/830 PSU C P16	19 W
32593400	DN140B LED20S/840 PSU C P16	19 W

Order Code	Full Product Name	Initial input power
32594199	DN140B LED20S/830 PSD-E C	20.5 W
32595899	DN140B LED20S/840 PSD-E C	20.5 W
32614600	DN140B LED20S/830 C IA1	22 W
32615300	DN140B LED20S/840 C IA1	22 W
32838600	DN140B LED20S/840 PSD-E C ELB3	23.5 W
32596500	DN140B LED10S/830 PSU WR IP54 P16	9.5 W
32597200	DN140B LED10S/840 PSU WR IP54 P16	9.5 W
32598900	DN140B LED10S/830 PSD-E WR IP54	11.5 W
32599600	DN140B LED10S/840 PSD-E WR IP54	11.5 W
32600900	DN140B LED20S/830 PSU WR IP54 P16	19 W
32601600	DN140B LED20S/840 PSU WR IP54 P16	19 W
32602300	DN140B LED20S/830 PSD-E WR IP54	20.5 W
32603000	DN140B LED20S/840 PSD-E WR IP54	20.5 W
32604700	DN140B LED10S/830 PSU C IP54 P16	9.5 W
32605400	DN140B LED10S/840 PSU C IP54 P16	9.5 W
32606100	DN140B LED10S/830 PSD-E C IP54	11.5 W
32607800	DN140B LED10S/840 PSD-E C IP54	11.5 W
32608500	DN140B LED20S/830 PSU C IP54 P16	19 W

## CoreLine Downlight

Order Code	Full Product Name	Initial input power
32609200	DN140B LED20S/840 PSU C IP54 P16	19 W
32610800	DN140B LED20S/830 PSD-E C IP54	20.5 W

Order Code	Full Product Name	Initial input power
32611500	DN140B LED20S/840 PSD-E C IP54	20.5 W

### Over Time Performance (IEC Compliant)

Order Code	Full Product Name	Median useful life L80B50	Median useful life L90B50
32580400	DN140B LED10S/830 PSU WR P16	-	-
32581100	DN140B LED10S/840 PSU WR P16	-	-
32582899	DN140B LED10S/830 PSD-E WR	43000 h	20000 h
32583599	DN140B LED10S/840 PSD-E WR	43000 h	20000 h
32832400	DN140B LED10S/840 PSD-E WR ELB3	43000 h	20000 h
32584200	DN140B LED20S/830 PSU WR P16	-	-
32585900	DN140B LED20S/840 PSU WR P16	-	-
32586699	DN140B LED20S/830 PSD-E WR	43000 h	20000 h
32587399	DN140B LED20S/840 PSD-E WR	43000 h	20000 h
32612200	DN140B LED20S/830 WR IA1	43000 h	20000 h
32613900	DN140B LED20S/840 WR IA1	43000 h	20000 h
32834800	DN140B LED20S/840 PSD-E WR ELB3	43000 h	20000 h
32588000	DN140B LED10S/830 PSU C P16	-	-
32589700	DN140B LED10S/840 PSU C P16	-	-
32590399	DN140B LED10S/830 PSD-E C	43000 h	20000 h
32591099	DN140B LED10S/840 PSD-E C	43000 h	20000 h
32592700	DN140B LED20S/830 PSU C P16	-	-
32593400	DN140B LED20S/840 PSU C P16	-	-
32594199	DN140B LED20S/830 PSD-E C	43000 h	20000 h
32595899	DN140B LED20S/840 PSD-E C	43000 h	20000 h

Order Code	Full Product Name	Median useful life L80B50	Median useful life L90B50
32614600	DN140B LED20S/830 C IA1	43000 h	20000 h
32615300	DN140B LED20S/840 C IA1	43000 h	20000 h
32838600	DN140B LED20S/840 PSD-E C ELB3	43000 h	20000 h
32596500	DN140B LED10S/830 PSU WR IP54 P16	-	-
32597200	DN140B LED10S/840 PSU WR IP54 P16	-	-
32598900	DN140B LED10S/830 PSD-E WR IP54	43000 h	20000 h
32599600	DN140B LED10S/840 PSD-E WR IP54	43000 h	20000 h
32600900	DN140B LED20S/830 PSU WR IP54 P16	-	-
32601600	DN140B LED20S/840 PSU WR IP54 P16	-	-
32602300	DN140B LED20S/830 PSD-E WR IP54	43000 h	20000 h
32603000	DN140B LED20S/840 PSD-E WR IP54	43000 h	20000 h
32604700	DN140B LED10S/830 PSU C IP54 P16	-	-
32605400	DN140B LED10S/840 PSU C IP54 P16	-	-
32606100	DN140B LED10S/830 PSD-E C IP54	43000 h	20000 h
32607800	DN140B LED10S/840 PSD-E C IP54	43000 h	20000 h
32608500	DN140B LED20S/830 PSU C IP54 P16	-	-
32609200	DN140B LED20S/840 PSU C IP54 P16	-	-
32610800	DN140B LED20S/830 PSD-E C IP54	43000 h	20000 h
32611500	DN140B LED20S/840 PSD-E C IP54	43000 h	20000 h

