



Reliable Compact Fluorescent lamp nonintegrated

PL-L Essential.

Energy-saving compact fluorescent non-integrated lamp

Benefits

- · Good color rendering (CRI >80)
- · Long life and sustainable light output

Features

- · 4-pin base without starter and capacitor
- · Fluorescent tri-phosphor technology

Application


 $\boldsymbol{\cdot}$ Designed for use in general lighting in shops and residential areas

PL-L Essential.

Versions



Dimensional drawing



General Information	
Cap-Base	2G11
Light Technical	
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Color rendering index (CRI)	80
Luminous Efficacy (rated) (Nom)	69 lm/W
Controls and Dimming	
Dimmable	Yes
Approval and Application	

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
PL-L Essential 36W/865/4P 1CT/50	37.5 mm	16.9 mm	382.2 mm	408 mm	415.0 mm
PL-L Essential 55W/865/4P1CT/50	37 5 mm	16 9 mm	507.2 mm	532 mm	539 0 mm

Light Technical

Order Code	Full Product Name	Luminous Flux
927933686503	PL-L Essential 36W/865/4P 1CT/50	2,550 lm

3.0 mg

Order Code	Full Product Name	Luminous Flux
927933786503	PL-L Essential 55W/865/4P 1CT/50	3,900 lm

Operating and Electrical

Mercury (Hg) Content (Nom)

PL-L Essential.

		Lamp		
		Current Voltage Power		
Order Code	Full Product Name	(Nom)	(Nom)	Consumption
927933686503	PL-L Essential 36W/	0.435 A	106 V	36 W
	865/4P 1CT/50			

		Lamp		
		Current Voltage Power		
Order Code	Full Product Name	(Nom)	(Nom)	Consumption
927933786503	PL-L Essential 55W/	0.550 A	101 V	55 W
	865/4P 1CT/50			

