



# Energy saving upgrade without sacrifice

## Halogen PAR

Halogen PAR lamps reduce energy consumption without sacrificing the qualities of a traditional PAR lamp. They uniquely produce light more efficiently. They work with dimmer switches and are available in the familiar PAR20, PAR30S, PAR30L, and PAR38 shapes. Use them in existing fixtures just as you would standard halogen PAR lamps.

### Benefits

- A bright, energy saving alternative to standard halogen PAR lamps.

### Features

- Provides at least 13% energy savings
- Fully dimmable and Instant-on
- Mercury Free
- Rated average life of 1100 hours

### Application

- Ideal for residential use in living rooms, bedrooms, hallways, bathrooms, dining rooms, offices and kitchens, as well as for commercial use in offices and retail spaces. Can be used for indoor or outdoor applications.

# Halogen PAR

## Versions



E26/50x39, PAR38



E26, PAR30L, Clear






E26, PAR20, Spot



E26, PAR30S, Flood

## Dimensional drawing



### Product

Halogen 72PAR38/EVP/FL25 120V 12/1

Halogen 53PAR38/EVP/FL25 120V 12/1

### Product

Halogen 39PAR20/EVP/SP10 120V 15/1

### Product


Halogen 53PAR30S/EVP/WFL40 120V 15/1

Halogen 39PAR30S/EVP/FL25 120V 15/1

Halogen 53PAR30S/EVP/FL25 120V 15/1

# Halogen PAR

## Dimensional drawing



Product
Halogen 53PAR30L/EVP/FL25 120V 15/1
Halogen 53PAR30L/EV/FL25 120V 16/2 TP
Halogen 53PAR30L/EVP/WFL40 120V 15/1
Halogen 39PAR30L/EVP/FL25 120V 15/1

Operating and Electrical	
Voltage (Nom)	120 V
General Information	
Operating Position	Universal
Rated Lifetime (Hours)	1100 h
Light Technical	
Color Rendering Index (Nom)	100
Mechanical and Housing	
Bulb Finish	Clear (CL)
Bulb Material	Hard Glass
Reflector Finish	Aluminized

## Operating and Electrical

Order Code	Full Product Name	Power (Rated) (Nom)
428854	Halogen 53PAR38/EVP/FL25 120V 12/1	53 W
428938	Halogen 72PAR38/EVP/FL25 120V 12/1	72 W
428920	Halogen 53PAR30L/EVP/FL25 120V 15/1	53 W
429365	Halogen 53PAR30L/EV/FL25 120V 16/2 TP	53 W
428952	Halogen 53PAR30L/EVP/WFL40 120V 15/1	53 W

Order Code	Full Product Name	Power (Rated) (Nom)
428870	Halogen 39PAR30L/EVP/FL25 120V 15/1	39 W
425124	Halogen 39PAR20/EVP/SP10 120V 15/1	39 W
428960	Halogen 39PAR30S/EVP/FL25 120V 15/1	39 W
428904	Halogen 53PAR30S/EVP/FL25 120V 15/1	53 W
428986	Halogen 53PAR30S/EVP/WFL40 120V 15/1	53 W

## General Information

Order Code	Full Product Name	Cap-Base	Use	Main Application	Life With 3 Hour Per Day
428854	Halogen 53PAR38/EVP/FL25 120V 12/1	E26/50X39	-	Outdoor (OD)	
428938	Halogen 72PAR38/EVP/FL25 120V 12/1	E26/50X39	-	Outdoor (OD)	
428920	Halogen 53PAR30L/EVP/FL25 120V 15/1	E26	-	Indoor Reflector	
429365	Halogen 53PAR30L/EV/FL25 120V 16/2 TP	E26	-	Indoor Reflector	
428952	Halogen 53PAR30L/EVP/WFL40 120V 15/1	E26	2.7 a	Indoor Reflector	

Order Code	Full Product Name	Cap-Base	Use	Main Application	Life With 3 Hour Per Day
428870	Halogen 39PAR30L/EVP/FL25 120V 15/1	E26	-	Track, Downlighting & Outdoor	
425124	Halogen 39PAR20/EVP/SP10 120V 15/1	E26	-	Track, Downlighting & Outdoor	
428960	Halogen 39PAR30S/EVP/FL25 120V 15/1	E26	2.7 a	Track, Downlighting & Outdoor	
428904	Halogen 53PAR30S/EVP/FL25 120V 15/1	E26	-	Indoor Reflector	

# Halogen PAR

Order Code	Full Product Name	Cap-Base	Life With 3 Hour Per Day	
			Use	Main Application
428986	Halogen 53PAR30S/EVP/ WFL40 120V 15/1	E26	-	Indoor Reflector

## Light Technical

Order Code	Full Product Name	Beam Angle	Beam Description	Correlated Color	Luminous Flux	Luminous Flux	Luminous Intensity
		(Nom)		Temperature (Nom)	Lamp @ 120V	(Nom)	(Nom)
428854	Halogen 53PAR38/EVP/FL25 120V 12/1	25 °	Flood	2900 K	-	920 lm	2000 cd
428938	Halogen 72PAR38/EVP/FL25 120V 12/1	25 °	Flood	2900 K	-	1350 lm	2000 cd
428920	Halogen 53PAR30L/EVP/FL25 120V 15/1	25 °	Flood	2900 K	920 lm	920 lm	3100 cd
429365	Halogen 53PAR30L/EV/FL25 120V 16/2 TP	25 °	Flood	2900 K	920 lm	920 lm	3100 cd
428952	Halogen 53PAR30L/EVP/WFL40 120V 15/1	40 °	Wide Flood	2790 K	-	920 lm	950 cd
428870	Halogen 39PAR30L/EVP/FL25 120V 15/1	25 °	Flood	2900 K	-	520 lm	2350 cd
425124	Halogen 39PAR20/EVP/SPI10 120V 15/1	10 °	Spot	2900 K	-	500 lm	4150 cd
428960	Halogen 39PAR30S/EVP/FL25 120V 15/1	25 °	Flood	2790 K	-	530 lm	2250 cd
428904	Halogen 53PAR30S/EVP/FL25 120V 15/1	25 °	Flood	2900 K	920 lm	920 lm	-
428986	Halogen 53PAR30S/EVP/WFL40 120V 15/1	40 °	Wide Flood	2900 K	920 lm	920 lm	-

## Mechanical and Housing

Order Code	Full Product Name	Bulb Shape	Order Code	Full Product Name	Bulb Shape
428854	Halogen 53PAR38/EVP/FL25 120V 12/1	PAR38	428870	Halogen 39PAR30L/EVP/FL25 120V 15/1	PAR30L
428938	Halogen 72PAR38/EVP/FL25 120V 12/1	PAR38	425124	Halogen 39PAR20/EVP/SPI10 120V 15/1	PAR20
428920	Halogen 53PAR30L/EVP/FL25 120V 15/1	PAR30L	428960	Halogen 39PAR30S/EVP/FL25 120V 15/1	PAR30S
429365	Halogen 53PAR30L/EV/FL25 120V 16/2 TP	PAR30L	428904	Halogen 53PAR30S/EVP/FL25 120V 15/1	PAR30S
428952	Halogen 53PAR30L/EVP/WFL40 120V 15/1	PAR30L	428986	Halogen 53PAR30S/EVP/WFL40 120V 15/1	PAR30S

## Approval and Application

Order Code	Full Product Name	Estimated Energy Cost Per Year
428854	Halogen 53PAR38/EVP/FL25 120V 12/1	-
428938	Halogen 72PAR38/EVP/FL25 120V 12/1	-
428920	Halogen 53PAR30L/EVP/FL25 120V 15/1	-
429365	Halogen 53PAR30L/EV/FL25 120V 16/2 TP	-
428952	Halogen 53PAR30L/EVP/WFL40 120V 15/1	6.02 \$

Order Code	Full Product Name	Estimated Energy Cost Per Year
428870	Halogen 39PAR30L/EVP/FL25 120V 15/1	-
425124	Halogen 39PAR20/EVP/SPI10 120V 15/1	6.02 \$
428960	Halogen 39PAR30S/EVP/FL25 120V 15/1	6.02 \$
428904	Halogen 53PAR30S/EVP/FL25 120V 15/1	-
428986	Halogen 53PAR30S/EVP/WFL40 120V 15/1	-

## Halogen PAR

