



Philips Ledinaire wall-mounted WL060V – for your everyday lighting jobs.

Ledinaire Wall-mounted WL060V

The Philips Ledinaire wall-mounted family has a reputation for simply great LED lighting. The popular, off-the-shelf LED luminaires in this range promise Philips' high-quality levels at a very competitive price. Reliable, energy-efficient and affordable, Ledinaire WL060V wall-mounted luminaires are designed to cover a wide range of indoor applications from corridors to public entrances. The modern, unobtrusive design also comes in a choice of two sizes and lumen packages, so you can create a uniform look and feel wherever you need wall-mounted LEDs.

Benefits

- Energy-saving LEDs
- Philips quality and reliability
- Competitive price
- Wide range of indoor applications

Features

- Modern, unobtrusive design
- Two lumen packages and sizes; 1,100 lm 30 cm, 1,700 lm 35 cm
- The IP44 rating is perfect for indoor applications
- Full opal cover for a homogeneous light effect
- Optional motion detection and daylight sensor

Ledinaire Wall-mounted WL060V

Application

- Corridors
- Staircases
- Public entrance areas

Specifications

Ambient Temperature	-20 to +40 °C
Beam spread luminaire	120°
Main colour of the luminaire	White
Dimming	No
Driver	Power supply unit (PSU)
Initial input power	12 W, 18.5 W
Initial luminous flux	1100 lm, 1700 lm

Installation	Through-wiring possible
Light source colour	830 warm white, 840 neutral white
Light source replaceable	No
Material	Housing: polypropylene
Optical cover	Polymethyl methacrylate
Warranty period	3 years

Versions



Product details



Ledinaire Wall-mounted detail product photo



Ledinaire Wall-mounted detail product photo

Ledinaire Wall-mounted WL060V

Application conditions

Ambient temperature range	-20 to +40 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

Approval and application

Mech. impact protection code	IK03
Ingress protection code	IP44

Controls and dimming

Dimmable	No
----------	----

Operating and electrical

Input Voltage	220-240 V
---------------	-----------

General information

Beam angle of light source	120 °
CE mark	Yes
Protection class IEC	Safety class II (II)
Driver included	Yes
ENEC mark	-
Flammability mark	NO
Glow-wire test	650/30
Light source replaceable	No
Number of gear units	1 unit
Optic type	120

Initial performance (IEC compliant)

Init. Colour rendering index	>80
Initial LED luminaire efficacy	90 lm/W
Luminous flux tolerance	+/-10%

Mechanical and housing

Colour	White
--------	-------

Over time performance (IEC compliant)

Driver failure rate at 5,000 hours	0.005 %
------------------------------------	---------

Initial performance (IEC compliant)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial luminous flux	Initial input power
33909299	WL060V LED11S/830 PSU II WH	(0.43, 0.40) SDCM ≤5	3000 K	1100 lm	12 W
33910899	WL060V LED11S/840 PSU II WH	(0.38, 0.38) SDCM ≤5	4000 K	1100 lm	12 W
33911599	WL060V LED17S/830 PSU II WH	(0.43, 0.40) SDCM ≤5	3000 K	1700 lm	18.5 W
33912299	WL060V LED17S/840 PSU II WH	(0.38, 0.38) SDCM ≤5	4000 K	1700 lm	18.5 W

