



High quality light helps to save more energy

SmartBright Highbay G2

SmartBright Highbay G2 is a high efficient and reliable LED luminaire. Designed as the point to point replacement for HPI 250W/400W luminaires, it offers customers all the benefits of LED lighting – reduced energy consumption, longer service time and less maintenance. In addition, with using high quality of the optical plate, it provides an excellent quality of light, which effectively improves the comfort of your environment.

Benefits

- Energy saving up to 64% comparing to HPI-P system
- Comfort light quality
- Safe & Reliable
- Easy installation and retrofitting

Features

- High efficacy: 90 lumens per watt
- High quality optical plate ensure good uniformity
- Lifetime of 50,000 hours @ Ta35°C with end-to-end Philips production quality assurance
- Full family is in compliance with CB and EMC norms
- Suitable for pole and hook mounting

Application

- Industry area: Factories, warehouses, workshops, assembly lines, etc.
- High ceiling indoor: Shopping centres, airports, stadium, etc.

SmartBright Highbay G2

Versions



BY228P LED90/NW PSU



BY228P LED180/NW PSU



BY228P LED50/NW PSU

Product details

GreenUp Lowbay G2 BY288Z Hook



GreenUp Lowbay G2 BY288P Back



SmartBright Highbay G2

Product details



Accessories



BY218Z Hook

Ordercode 01561721

SmartBright Highbay G2

Application Conditions

Ambient temperature range	-20 to +40 °C
Suitable for random switching	No

Approval and Application

Mech. impact protection code	IK03
Ingress protection code	IP20

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Voltage	220-240 V
---------------	-----------

General Information

CE mark	CE mark
Protection class IEC	Safety class I (I)
Driver included	Yes
ENEC mark	-
Flammability mark	F
Glow-wire test	650/5
Light source replaceable	No
Optic type	WB

Initial Performance (IEC Compliant)

Initial chromaticity	SDCM<5
Init. Colour Rendering Index	≥80
Initial LED luminaire efficacy	90 lm/W
Luminous flux tolerance	+/-10%

Mechanical and Housing

Colour	Gray and gray
--------	---------------

Over Time Performance (IEC Compliant)

Median useful life L80B50	25000 h
Median useful life L90B50	15000 h

General Information

Order Code	Full Product Name	Number of gear units
01596631	BY228P LED90/CW PSU	1 unit
01596731	BY228P LED180/NW PSU	2 units
01596931	BY228P LED180/CW PSU	2 units
01596831	BY228P LED50/CW PSU	2 units

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux	Initial input power
01596631	BY228P LED90/CW PSU	6500 K	9000 lm	100 W
01596731	BY228P LED180/NW PSU	4000 K	18000 lm	200 W

Order Code	Full Product Name	Init. Corr. Colour Temperature	Initial luminous flux	Initial input power
01596931	BY228P LED180/CW PSU	6500 K	18000 lm	200 W
01596831	BY228P LED50/CW PSU	6500 K	5400 lm	60 W

SmartBright Highbay G2

