



# Ledinaire Floodlight Simply great LED

## Ledinaire floodlight maxi

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

### Benefits

- Philips quality and reliability
- Energy saving: 1:1 retrofit up to HPI-TP 400W
- Quick installation without opening the floodlight
- Philips high-quality finish, robust and fully reliable

### Features

- Highly efficient : 100 lm/W Two system flux models : 10 klm/100W and 20 klm/200W Long lifetime of 50 000 hours (Ta 25°C) Robust (IK08) and waterproof (IP65) floodlights 0.5 m prewired cable (class1) Standing-up or hanging-down mounting Compliant with CE, CB, ROHS Salt spray 500 hours Clear tempered glass LOR >86

### Application

- Car parks
- Industrial areas
- Dockyards
- Security / amenity lighting

### Specifications

## Ledinaire floodlight maxi

Aiming possibilities from the horizontal	to °
Aiming possibilities from the vertical	to °
Ambient Temperature	-25 to +40 °C
Beam spread luminaire	100° x 100°
Main color of the Luminaire	Gray and gray Gray painting RAL 7043
Connection	Flying leads/wires (Flying leads/wires)
Dimming	No
Driver	Power supply unit (Power supply unit)
Driver failure rate at 5000 h in %	0.15% per 5000 hours
Initial correlated color temperature	4000 K 4000 K
Initial LED luminaire efficacy	100 lm/W 100 lm/W
Initial luminous flux	10000, 20000 lm
Input frequency	50 to 60 Hz

Input voltage	220 to 240 V
Inrush current (A)	38, 43 A
Light Source	SMD LED
Light source replaceable	No
Maintenance	Maintenance c
Material	Housing: aluminum die cast
Material	Reflector: aluminum
Optic	Beam category A1 Specular aluminium reflector
Remarks	Installation on mast-head frame/wall or on roof or ceiling / wall. Standing-up or hanging-down mounting. U-shaped mounting bracket with foot-print suitable for 3-point fixation by means of M20 bolts.
Surge protection	Luminaire surge protection level until 4 kV differential mode and 4 kV common mode
Warranty period	3 years

### Versions



LED Module, system flux 20,000  
lm - LED - 100° x 100°

### Product details



Ledinaire-  
BVP106\_Led200-1DPP.TIF



Ledinaire-  
BVP106\_Led200-2DPP.TIF

# Ledinaire floodlight maxi

## Product details



Ledinaire-  
BVP106\_Led200-3DPP.TIF



Ledinaire-  
BVP106\_Led200-4DPP.TIF



Ledinaire-  
BVP106\_Led200-5DPP.TIF

