



# Miniaturized downlight with leading optical performance and great diversity

## LuxSpace G4

LuxSpace Gen4 is the a new LED downlight range combining light comfort and leading performance with luxury looking

### Benefits

- Visual comfort
- Multiple options for various applications
- Smart lighting

### Features

- Miniaturized form factor
- High optical efficiency
- Great product diversity
- Tunable white

### Application

- Office
- shopping mall
- hotel
- retail

## Versions



DN58XB DN59XB D150 D200

### Application Conditions

Ambient temperature range	-20 to +40 °C
Maximum dim level	1%

### Approval and Application

Mech. impact protection code	IK03
Ingress protection code	IP54/20

### Controls and Dimming

Dimmable	Yes
----------	-----

### Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

### General Information

CE mark	CE mark
Protection class IEC	Safety class I (I)
Optical cover/lens type	Reflector
Driver included	Yes
Flammability mark	F
Glow-wire test	650/30
Light source replaceable	No
Number of gear units	1 unit
Optic type	Facetted reflector with beam angle 60°

### Initial Performance (IEC Compliant)

Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Luminous flux tolerance	+/-10%

### Mechanical and Housing

Color	White and black
-------	-----------------

### Over Time Performance (IEC Compliant)

Median useful life L80B50	50000 h
Median useful life L90B50	21000 h

### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
911401551041	DN591B LED20/840 PSD C D200 WH WB WP GM	113 lm/W	2040 lm	18 W
911401551241	DN594B LED40/840 PSD C D200 WH WB WP GM	103 lm/W	4090 lm	39.7 W

