

RTA61 – enhancing your project's unique style

Pole (RTA61)

Made from a 12 flute, mandrel-formed, aluminum tapered shaft 5” round (127 mm) welded to a 8 5/8” round (219 mm) extruded aluminum pole base which them is welded to both the top andbottom of a cast aluminum anchor plate. After tapering, forming and welding, the entire shaft assembly is heat-treated to T6 temper. A 4 1/2” by 10” (114 by 254 mm) maintenance opening is completewith cover and copper ground lug. ~LT~a href="http://www.lumec.com/Lumec3Dv2/home/index_en.php" target="_blank"~GT~~LT~b~GT~Lumec3D: Online 3D Configurator~LT~/b~GT~~LT~/a~GT~

Benefits

- Built to withstand harsh environmental conditions
- Superior corrosion resistance
- Optimal strength and durability

Features

- Round tapered fluted
- Aluminum construction
- Available in various heights ranging from 10' to 15'

Application

- Bridges, Monuments, Facades
- Road and Street

Pole (RTA61)

Versions



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.