PHILIPS

Lighting



It delivers super flexibility, complete product range and seamlessly system integration to Hospitality customers..

Greenspace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Benefits

- Complete portfolio covering from 400lm to 3000lm, 3CCT and 3 beam angles.
- Super flexibility with modular design, and different trims to suit different application.
- Smart connectivity to seamlessly integration with Interact Hospitality.
- Deep recess for visual comfort
- Easy installation and maintenance

Greenspace Flex

Features

- 6w ~42w (400lm~3200lm)
- CRI 90, SDCM <3
- Beam Angle: NB, MB, WB
- CCT: 2700K, 3000K, 4000K
- High reliability, 50Khrs (L80B50@25°C)

Application

- Guest room
- Bath room
- Corridor
- Lobby

Specifications

Mounting type	Recessed
Operating Temperature range	-20 to +45 ºC
Light Source	COB
Mains Voltage	220-240V AC/ 50-60Hz
Optical Accessories	available through ETO
Dimming	PSU: non-dimmable
	PSD: dimmable via Dali protocol
	PSR: trailing dimmable
	PSR 1-10V: 1-10v dimmable
	DMX: dimmable via DMX protocol
Control system input	DALI / 1-10V / DMX / trailing edge
Material	Heat sink: die-cast aluminum
Main color of the luminaire	Housing: dark Grey
	Reflector: color available through ETO
Lumen maintenance at median useful life 50.000h	L80
Luminous flux	468-3990lm
Power consumption	6W-42W

Correlated color temperature - CCT	2700K, 3000K, 4000K
Color Rendering index - CRI	90
Beam angle	NB (Narrow Beam): 15-18°
	MB (Medium Beam): 20-24°
	WB (Wide Beam): 30-40°
	VWB (Very Wide Beam): 50°
Protection Class IEC61140	Class II & Class III for MR16 version
Mechanical impact protection	IK04
Ingress protection	IP20 / IP54(Front side) for selected SKU only
Light source replaceable	No
Driver replaceable	yes
Overall diameter	D55-D150
Installation	recessed
	Fixation by means of spring fasteners

Versions



RS378B P11 M55





RS378B P6 M55





RS378B P15 M55


Dimensional drawing













Modular Type	D, mm	H, mm
RS378B P6/P11 M55	55	49
RS378B P15 M55	55	49
RS378B P24 M70	70	90
RS378B P33 M87	87	107
RS378B P42 M102	102	116





General Information	
CE mark	-
ENEC mark	-
Flammability mark	-
Light Technical	
Optical cover type	-
Color rendering index (CRI)	>90
Optic type	-
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Temperature	
Ambient temperature range	-20 to +45 °C
Mechanical and Housing	
Housing Color	Dark gray
Approval and Application	
Protection class IEC	Safety class II
Mech. impact protection code	IK04
Ingress protection code	IP20
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

General Information

Order Code	Full Product Name	Driver included	Glow-wire test	Number of gear units
911401535971	RS378B P11 927 PSD-E MB M55	-	-	-
911401720892	RS378B P6 927 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720902	RS378B P6 930 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720932	RS378B P6 930 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720942	RS378B P6 940 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720952	RS378B P6 927 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720962	RS378B P6 930 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720972	RS378B P6 940 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401720982	RS378B P11 927 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721002	RS378B P11 940 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721012	RS378B P11 927 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721022	RS378B P11 930 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721032	RS378B P11 940 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721042	RS378B P11 927 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721052	RS378B P11 930 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721062	RS378B P11 940 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721072	RS378B P6 927 PSR-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721102	RS378B P6 927 PSR-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721112	RS378B P6 930 PSR-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721132	RS378B P6 927 PSR-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721172	RS378B P11 930 PSR-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721192	RS378B P11 927 PSR-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721222	RS378B P11 927 PSR-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721622	RS378B P42 930 PSU-E NB M102	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721632	RS378B P42 940 PSU-E NB M102	Yes	Temperature 600 °C, duration 30 s	1 unit

Order Code	Full Product Name	Driver included	Glow-wire test	Number of gear units
911401721642	RS378B P42 927 PSU-E MB M102	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721652	RS378B P42 930 PSU-E MB M102	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721662	RS378B P42 940 PSU-E MB M102	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721692	RS378B P42 940 PSU-E WB M102	Yes	Temperature 600 °C, duration 30 s	1 unit
911401535471	RS378B P6 930 PSD-E WB M55	-	-	-
911401721432	RS378B P24 927 PSU-E NB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721442	RS378B P24 930 PSU-E NB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721452	RS378B P24 940 PSU-E NB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721462	RS378B P24 927 PSU-E MB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721482	RS378B P24 940 PSU-E MB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721512	RS378B P24 940 PSU-E WB M70	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721532	RS378B P33 930 PSU-E NB M87	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721542	RS378B P33 940 PSU-E NB M87	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721562	RS378B P33 930 PSU-E MB M87	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721572	RS378B P33 940 PSU-E MB M87	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721602	RS378B P33 940 PSU-E WB M87	Yes	Temperature 600 °C, duration 30 s	1 unit
911401536871	RS378B P15 927 PSD-E MB M55	-	-	-
911401721262	RS378B P15 930 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721272	RS378B P15 940 PSU-E NB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721302	RS378B P15 940 PSU-E MB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721322	RS378B P15 930 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721332	RS378B P15 940 PSU-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit
911401721412	RS378B P15 930 PSR-E WB M55	Yes	Temperature 600 °C, duration 30 s	1 unit

Light Technical

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux
911401535971	RS378B P11 927 PSD-E MB M55	-	2700 K	87 lm/W	957 lm
911401720892	RS378B P6 927 PSU-E NB M55	- degree(s)	2700 K	75 lm/W	450 lm
911401720902	RS378B P6 930 PSU-E NB M55	- degree(s)	3000 K	78 lm/W	468 lm
911401720932	RS378B P6 930 PSU-E MB M55	- degree(s)	3000 K	78 lm/W	468 lm
911401720942	RS378B P6 940 PSU-E MB M55	- degree(s)	4000 K	82 lm/W	492 lm
911401720952	RS378B P6 927 PSU-E WB M55	- degree(s)	2700 K	90 lm/W	595 lm
911401720962	RS378B P6 930 PSU-E WB M55	- degree(s)	3000 K	78 lm/W	468 lm
911401720972	RS378B P6 940 PSU-E WB M55	- degree(s)	4000 K	82 lm/W	492 lm
911401720982	RS378B P11 927 PSU-E NB M55	-	2700 K	76 lm/W	836 lm
911401721002	RS378B P11 940 PSU-E NB M55	-	4000 K	87 lm/W	957 lm
911401721012	RS378B P11 927 PSU-E MB M55	-	2700 K	87 lm/W	957 lm
911401721022	RS378B P11 930 PSU-E MB M55	-	3000 K	92 lm/W	1,012 lm
911401721032	RS378B P11 940 PSU-E MB M55	-	4000 K	100 lm/W	1,100 lm
911401721042	RS378B P11 927 PSU-E WB M55	-	2700 K	87 lm/W	957 lm
911401721052	RS378B P11 930 PSU-E WB M55	-	3000 K	92 lm/W	1,012 lm
911401721062	RS378B P11 940 PSU-E WB M55	-	4000 K	100 lm/W	1,100 lm
911401721072	RS378B P6 927 PSR-E NB M55	-	2700 K	58 lm/W	348 lm
911401721102	RS378B P6 927 PSR-E MB M55	-	2700 K	58 lm/W	348 lm
911401721112	RS378B P6 930 PSR-E MB M55	-	3000 K	60 lm/W	360 lm
911401721132	RS378B P6 927 PSR-E WB M55	-	2700 K	58 lm/W	348 lm
911401721172	RS378B P11 930 PSR-E NB M55	-	3000 K	78 lm/W	858 lm
911401721192	RS378B P11 927 PSR-E MB M55	-	2700 K	87 lm/W	957 lm
911401721222	RS378B P11 927 PSR-E WB M55	-	2700 K	87 lm/W	957 lm
911401721622	RS378B P42 930 PSU-E NB M102	-	3000 K	95 lm/W	3,990 lm
911401721632	RS378B P42 940 PSU-E NB M102	-	4000 K	101 lm/W	4,242 lm
911401721642	RS378B P42 927 PSU-E MB M102	-	2700 K	90 lm/W	3,780 lm
911401721652	RS378B P42 930 PSU-E MB M102	- degree(s)	3000 K	95 lm/W	3,990 lm
911401721662	RS378B P42 940 PSU-E MB M102	- degree(s)	4000 K	101 lm/W	4,242 lm
911401721692	RS378B P42 940 PSU-E WB M102	- degree(s)	4000 K	101 lm/W	4,242 lm
911401535471	RS378B P6 930 PSD-E WB M55	-	3000 K	73 lm/W	438 lm
911401721432	RS378B P24 927 PSU-E NB M70	-	2700 K	80 lm/W	1,920 lm
911401721442	RS378B P24 930 PSU-E NB M70	-	3000 K	83 lm/W	1,992 lm
911401721452	RS378B P24 940 PSU-E NB M70	-	4000 K	90 lm/W	2,160 lm
911401721462	RS378B P24 927 PSU-E MB M70	-	2700 K	80 lm/W	1,920 lm
911401721482	RS378B P24 940 PSU-E MB M70	-	4000 K	90 lm/W	2,160 lm
911401721512	RS378B P24 940 PSU-E WB M70	-	4000 K	90 lm/W	2,160 lm

Order Code	Full Product Name	Beam angle of light source	Correlated Color Temperature (Nom)	Luminous Efficacy (rated) (Nom)	Luminous Flux
911401721532	RS378B P33 930 PSU-E NB M87	-	3000 K	83 lm/W	2,739 lm
911401721542	RS378B P33 940 PSU-E NB M87	-	4000 K	90 lm/W	2,970 lm
911401721562	RS378B P33 930 PSU-E MB M87	-	3000 K	83 lm/W	2,739 lm
911401721572	RS378B P33 940 PSU-E MB M87	-	4000 K	90 lm/W	2,970 lm
911401721602	RS378B P33 940 PSU-E WB M87	-	4000 K	90 lm/W	2,970 lm
911401536871	RS378B P15 927 PSD-E MB M55	-	2700 K	78 lm/W	1,170 lm
911401721262	RS378B P15 930 PSU-E NB M55	-	3000 K	78 lm/W	1,170 lm
911401721272	RS378B P15 940 PSU-E NB M55	-	4000 K	87 lm/W	1,305 lm
911401721302	RS378B P15 940 PSU-E MB M55	-	4000 K	87 lm/W	1,305 lm
911401721322	RS378B P15 930 PSU-E WB M55	-	3000 K	78 lm/W	1,170 lm
911401721332	RS378B P15 940 PSU-E WB M55	-	4000 K	87 lm/W	1,305 lm
911401721412	RS378B P15 930 PSR-E WB M55	-	3000 K	78 lm/W	1,170 lm

Operating and Electrical

Order Code	Full Product Name	Power Consumption
911401535971	RS378B P11 927 PSD-E MB M55	11 W
911401720892	RS378B P6 927 PSU-E NB M55	6 W
911401720902	RS378B P6 930 PSU-E NB M55	6 W
911401720932	RS378B P6 930 PSU-E MB M55	6 W
911401720942	RS378B P6 940 PSU-E MB M55	6 W
911401720952	RS378B P6 927 PSU-E WB M55	6 W
911401720962	RS378B P6 930 PSU-E WB M55	6 W
911401720972	RS378B P6 940 PSU-E WB M55	6 W
911401720982	RS378B P11 927 PSU-E NB M55	11 W
911401721002	RS378B P11 940 PSU-E NB M55	11 W
911401721012	RS378B P11 927 PSU-E MB M55	11 W
911401721022	RS378B P11 930 PSU-E MB M55	11 W
911401721032	RS378B P11 940 PSU-E MB M55	11 W
911401721042	RS378B P11 927 PSU-E WB M55	11 W
911401721052	RS378B P11 930 PSU-E WB M55	11 W
911401721062	RS378B P11 940 PSU-E WB M55	11 W
911401721072	RS378B P6 927 PSR-E NB M55	6 W
911401721102	RS378B P6 927 PSR-E MB M55	6 W
911401721112	RS378B P6 930 PSR-E MB M55	6 W
911401721132	RS378B P6 927 PSR-E WB M55	6 W
911401721172	RS378B P11 930 PSR-E NB M55	11 W
911401721192	RS378B P11 927 PSR-E MB M55	11 W
911401721222	RS378B P11 927 PSR-E WB M55	11 W
911401721622	RS378B P42 930 PSU-E NB M102	42 W
911401721632	RS378B P42 940 PSU-E NB M102	42 W
911401721642	RS378B P42 927 PSU-E MB M102	42 W
911401721652	RS378B P42 930 PSU-E MB M102	42 W
911401721662	RS378B P42 940 PSU-E MB M102	42 W
911401721692	RS378B P42 940 PSU-E WB M102	42 W
911401535471	RS378B P6 930 PSD-E WB M55	6 W
911401721432	RS378B P24 927 PSU-E NB M70	24 W
911401721442	RS378B P24 930 PSU-E NB M70	24 W
911401721452	RS378B P24 940 PSU-E NB M70	24 W
911401721462	RS378B P24 927 PSU-E MB M70	24 W
911401721482	RS378B P24 940 PSU-E MB M70	24 W
911401721512	RS378B P24 940 PSU-E WB M70	24 W
911401721532	RS378B P33 930 PSU-E NB M87	33 W
911401721542	RS378B P33 940 PSU-E NB M87	33 W
911401721562	RS378B P33 930 PSU-E MB M87	33 W
911401721572	RS378B P33 940 PSU-E MB M87	33 W
911401721602	RS378B P33 940 PSU-E WB M87	33 W
911401536871	RS378B P15 927 PSD-E MB M55	15 W
911401721262	RS378B P15 930 PSU-E NB M55	15 W
911401721272	RS378B P15 940 PSU-E NB M55	15 W
911401721302	RS378B P15 940 PSU-E MB M55	15 W
911401721322	RS378B P15 930 PSU-E WB M55	15 W
911401721332	RS378B P15 940 PSU-E WB M55	15 W
911401721412	RS378B P15 930 PSR-E WB M55	15 W

Controls and Dimming

Order Code	Full Product Name	Dimmable
911401535971	RS378B P11 927 PSD-E MB M55	Yes
911401720892	RS378B P6 927 PSU-E NB M55	No
911401720902	RS378B P6 930 PSU-E NB M55	No
911401720932	RS378B P6 930 PSU-E MB M55	No
911401720942	RS378B P6 940 PSU-E MB M55	No
911401720952	RS378B P6 927 PSU-E WB M55	No
911401720962	RS378B P6 930 PSU-E WB M55	No
911401720972	RS378B P6 940 PSU-E WB M55	No
911401720982	RS378B P11 927 PSU-E NB M55	No
911401721002	RS378B P11 940 PSU-E NB M55	No
911401721012	RS378B P11 927 PSU-E MB M55	No
911401721022	RS378B P11 930 PSU-E MB M55	No
911401721032	RS378B P11 940 PSU-E MB M55	No
911401721042	RS378B P11 927 PSU-E WB M55	No
911401721052	RS378B P11 930 PSU-E WB M55	No
911401721062	RS378B P11 940 PSU-E WB M55	No
911401721072	RS378B P6 927 PSR-E NB M55	Yes
911401721102	RS378B P6 927 PSR-E MB M55	Yes
911401721112	RS378B P6 930 PSR-E MB M55	Yes
911401721132	RS378B P6 927 PSR-E WB M55	Yes
911401721172	RS378B P11 930 PSR-E NB M55	Yes
911401721192	RS378B P11 927 PSR-E MB M55	Yes
911401721222	RS378B P11 927 PSR-E WB M55	Yes
911401721622	RS378B P42 930 PSU-E NB M102	No

Order Code	Full Product Name	Dimmable
911401721632	RS378B P42 940 PSU-E NB M102	No
911401721642	RS378B P42 927 PSU-E MB M102	No
911401721652	RS378B P42 930 PSU-E MB M102	No
911401721662	RS378B P42 940 PSU-E MB M102	No
911401721692	RS378B P42 940 PSU-E WB M102	No
911401535471	RS378B P6 930 PSD-E WB M55	Yes
911401721432	RS378B P24 927 PSU-E NB M70	No
911401721442	RS378B P24 930 PSU-E NB M70	No
911401721452	RS378B P24 940 PSU-E NB M70	No
911401721462	RS378B P24 927 PSU-E MB M70	No
911401721482	RS378B P24 940 PSU-E MB M70	No
911401721512	RS378B P24 940 PSU-E WB M70	No
911401721532	RS378B P33 930 PSU-E NB M87	No
911401721542	RS378B P33 940 PSU-E NB M87	No
911401721562	RS378B P33 930 PSU-E MB M87	No
911401721572	RS378B P33 940 PSU-E MB M87	No
911401721602	RS378B P33 940 PSU-E WB M87	No
911401536871	RS378B P15 927 PSD-E MB M55	Yes
911401721262	RS378B P15 930 PSU-E NB M55	No
911401721272	RS378B P15 940 PSU-E NB M55	No
911401721302	RS378B P15 940 PSU-E MB M55	No
911401721322	RS378B P15 930 PSU-E WB M55	No
911401721332	RS378B P15 940 PSU-E WB M55	No
911401721412	RS378B P15 930 PSR-E WB M55	Yes

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial chromaticity
911401535971	RS378B P11 927 PSD-E MB M55	-
911401720892	RS378B P6 927 PSU-E NB M55	SDCM<3
911401720902	RS378B P6 930 PSU-E NB M55	SDCM<3
911401720932	RS378B P6 930 PSU-E MB M55	SDCM<3
911401720942	RS378B P6 940 PSU-E MB M55	SDCM<3
911401720952	RS378B P6 927 PSU-E WB M55	SDCM<3
911401720962	RS378B P6 930 PSU-E WB M55	SDCM<3
911401720972	RS378B P6 940 PSU-E WB M55	SDCM<3
911401720982	RS378B P11 927 PSU-E NB M55	SDCM<3
911401721002	RS378B P11 940 PSU-E NB M55	SDCM<3
911401721012	RS378B P11 927 PSU-E MB M55	SDCM<3
911401721022	RS378B P11 930 PSU-E MB M55	SDCM<3
911401721032	RS378B P11 940 PSU-E MB M55	SDCM<3
911401721042	RS378B P11 927 PSU-E WB M55	SDCM<3
911401721052	RS378B P11 930 PSU-E WB M55	SDCM<3
911401721062	RS378B P11 940 PSU-E WB M55	SDCM<3
911401721072	RS378B P6 927 PSR-E NB M55	SDCM<3
911401721102	RS378B P6 927 PSR-E MB M55	SDCM<3
911401721112	RS378B P6 930 PSR-E MB M55	SDCM<3
911401721132	RS378B P6 927 PSR-E WB M55	SDCM<3
911401721172	RS378B P11 930 PSR-E NB M55	SDCM<3
911401721192	RS378B P11 927 PSR-E MB M55	SDCM<3
911401721222	RS378B P11 927 PSR-E WB M55	SDCM<3
911401721622	RS378B P42 930 PSU-E NB M102	SDCM<3

Order Code	Full Product Name	Initial chromaticity
911401721632	RS378B P42 940 PSU-E NB M102	SDCM<3
911401721642	RS378B P42 927 PSU-E MB M102	SDCM<3
911401721652	RS378B P42 930 PSU-E MB M102	SDCM<3
911401721662	RS378B P42 940 PSU-E MB M102	SDCM<3
911401721692	RS378B P42 940 PSU-E WB M102	SDCM<3
911401535471	RS378B P6 930 PSD-E WB M55	-
911401721432	RS378B P24 927 PSU-E NB M70	SDCM<3
911401721442	RS378B P24 930 PSU-E NB M70	SDCM<3
911401721452	RS378B P24 940 PSU-E NB M70	SDCM<3
911401721462	RS378B P24 927 PSU-E MB M70	SDCM<3
911401721482	RS378B P24 940 PSU-E MB M70	SDCM<3
911401721512	RS378B P24 940 PSU-E WB M70	SDCM<3
911401721532	RS378B P33 930 PSU-E NB M87	SDCM<3
911401721542	RS378B P33 940 PSU-E NB M87	SDCM<3
911401721562	RS378B P33 930 PSU-E MB M87	SDCM<3
911401721572	RS378B P33 940 PSU-E MB M87	SDCM<3
911401721602	RS378B P33 940 PSU-E WB M87	SDCM<3
911401536871	RS378B P15 927 PSD-E MB M55	-
911401721262	RS378B P15 930 PSU-E NB M55	SDCM<3
911401721272	RS378B P15 940 PSU-E NB M55	SDCM<3
911401721302	RS378B P15 940 PSU-E MB M55	SDCM<3
911401721322	RS378B P15 930 PSU-E WB M55	SDCM<3
911401721332	RS378B P15 940 PSU-E WB M55	SDCM<3
911401721412	RS378B P15 930 PSR-E WB M55	SDCM<3

Over Time Performance (IEC Compliant)

Order Code	Full Product Name	Median useful life L80B50
911401535971	RS378B P11 927 PSD-E MB M55	-
911401720892	RS378B P6 927 PSU-E NB M55	50,000 hour(s)
911401720902	RS378B P6 930 PSU-E NB M55	50,000 hour(s)
911401720932	RS378B P6 930 PSU-E MB M55	50,000 hour(s)
911401720942	RS378B P6 940 PSU-E MB M55	50,000 hour(s)
911401720952	RS378B P6 927 PSU-E WB M55	50,000 hour(s)
911401720962	RS378B P6 930 PSU-E WB M55	50,000 hour(s)
911401720972	RS378B P6 940 PSU-E WB M55	50,000 hour(s)
911401720982	RS378B P11 927 PSU-E NB M55	50,000 hour(s)
911401721002	RS378B P11 940 PSU-E NB M55	50,000 hour(s)
911401721012	RS378B P11 927 PSU-E MB M55	50,000 hour(s)
911401721022	RS378B P11 930 PSU-E MB M55	50,000 hour(s)
911401721032	RS378B P11 940 PSU-E MB M55	50,000 hour(s)
911401721042	RS378B P11 927 PSU-E WB M55	50,000 hour(s)
911401721052	RS378B P11 930 PSU-E WB M55	50,000 hour(s)
911401721062	RS378B P11 940 PSU-E WB M55	50,000 hour(s)
911401721072	RS378B P6 927 PSR-E NB M55	50,000 hour(s)
911401721102	RS378B P6 927 PSR-E MB M55	50,000 hour(s)
911401721112	RS378B P6 930 PSR-E MB M55	50,000 hour(s)
911401721132	RS378B P6 927 PSR-E WB M55	50,000 hour(s)
911401721172	RS378B P11 930 PSR-E NB M55	50,000 hour(s)
911401721192	RS378B P11 927 PSR-E MB M55	50,000 hour(s)
911401721222	RS378B P11 927 PSR-E WB M55	50,000 hour(s)
911401721622	RS378B P42 930 PSU-E NB M102	50,000 hour(s)

Order Code	Full Product Name	Median useful life L80B50
911401721632	RS378B P42 940 PSU-E NB M102	50,000 hour(s)
911401721642	RS378B P42 927 PSU-E MB M102	50,000 hour(s)
911401721652	RS378B P42 930 PSU-E MB M102	50,000 hour(s)
911401721662	RS378B P42 940 PSU-E MB M102	50,000 hour(s)
911401721692	RS378B P42 940 PSU-E WB M102	50,000 hour(s)
911401535471	RS378B P6 930 PSD-E WB M55	-
911401721432	RS378B P24 927 PSU-E NB M70	50,000 hour(s)
911401721442	RS378B P24 930 PSU-E NB M70	50,000 hour(s)
911401721452	RS378B P24 940 PSU-E NB M70	50,000 hour(s)
911401721462	RS378B P24 927 PSU-E MB M70	50,000 hour(s)
911401721482	RS378B P24 940 PSU-E MB M70	50,000 hour(s)
911401721512	RS378B P24 940 PSU-E WB M70	50,000 hour(s)
911401721532	RS378B P33 930 PSU-E NB M87	50,000 hour(s)
911401721542	RS378B P33 940 PSU-E NB M87	50,000 hour(s)
911401721562	RS378B P33 930 PSU-E MB M87	50,000 hour(s)
911401721572	RS378B P33 940 PSU-E MB M87	50,000 hour(s)
911401721602	RS378B P33 940 PSU-E WB M87	50,000 hour(s)
911401536871	RS378B P15 927 PSD-E MB M55	-
911401721262	RS378B P15 930 PSU-E NB M55	50,000 hour(s)
911401721272	RS378B P15 940 PSU-E NB M55	50,000 hour(s)
911401721302	RS378B P15 940 PSU-E MB M55	50,000 hour(s)
911401721322	RS378B P15 930 PSU-E WB M55	50,000 hour(s)
911401721332	RS378B P15 940 PSU-E WB M55	50,000 hour(s)
911401721412	RS378B P15 930 PSR-E WB M55	50,000 hour(s)

Application Conditions

Order Code	Full Product Name	Maximum dim level	Suitable for random switching
911401535971	RS378B P11 927 PSD-E MB M55	-	-
911401720892	RS378B P6 927 PSU-E NB M55	Not applicable	No
911401720902	RS378B P6 930 PSU-E NB M55	Not applicable	No
911401720932	RS378B P6 930 PSU-E MB M55	Not applicable	No
911401720942	RS378B P6 940 PSU-E MB M55	Not applicable	No
911401720952	RS378B P6 927 PSU-E WB M55	Not applicable	No
911401720962	RS378B P6 930 PSU-E WB M55	Not applicable	No
911401720972	RS378B P6 940 PSU-E WB M55	Not applicable	No
911401720982	RS378B P11 927 PSU-E NB M55	Not applicable	No
911401721002	RS378B P11 940 PSU-E NB M55	Not applicable	No
911401721012	RS378B P11 927 PSU-E MB M55	Not applicable	No
911401721022	RS378B P11 930 PSU-E MB M55	Not applicable	No
911401721032	RS378B P11 940 PSU-E MB M55	Not applicable	No
911401721042	RS378B P11 927 PSU-E WB M55	Not applicable	No
911401721052	RS378B P11 930 PSU-E WB M55	Not applicable	No
911401721062	RS378B P11 940 PSU-E WB M55	Not applicable	No
911401721072	RS378B P6 927 PSR-E NB M55	10%	No
911401721102	RS378B P6 927 PSR-E MB M55	10%	No
911401721112	RS378B P6 930 PSR-E MB M55	10%	No
911401721132	RS378B P6 927 PSR-E WB M55	10%	No

Order Code	Full Product Name	Maximum dim level	Suitable for random switching
911401721172	RS378B P11 930 PSR-E NB M55	10%	No
911401721192	RS378B P11 927 PSR-E MB M55	10%	No
911401721222	RS378B P11 927 PSR-E WB M55	10%	No
911401721622	RS378B P42 930 PSU-E NB M102	Not applicable	No
911401721632	RS378B P42 940 PSU-E NB M102	Not applicable	No
911401721642	RS378B P42 927 PSU-E MB M102	Not applicable	No
911401721652	RS378B P42 930 PSU-E MB M102	Not applicable	No
911401721662	RS378B P42 940 PSU-E MB M102	Not applicable	No
911401721692	RS378B P42 940 PSU-E WB M102	Not applicable	No
911401535471	RS378B P6 930 PSD-E WB M55	-	-
911401721432	RS378B P24 927 PSU-E NB M70	Not applicable	No
911401721442	RS378B P24 930 PSU-E NB M70	Not applicable	No
911401721452	RS378B P24 940 PSU-E NB M70	Not applicable	No
911401721462	RS378B P24 927 PSU-E MB M70	Not applicable	No
911401721482	RS378B P24 940 PSU-E MB M70	Not applicable	No
911401721512	RS378B P24 940 PSU-E WB M70	Not applicable	No
911401721532	RS378B P33 930 PSU-E NB M87	Not applicable	No
911401721542	RS378B P33 940 PSU-E NB M87	Not applicable	No
911401721562	RS378B P33 930 PSU-E MB M87	Not applicable	No
911401721572	RS378B P33 940 PSU-E MB M87	Not applicable	No

Greenspace Flex

Order Code	Full Product Name	Maximum dim level	Suitable for random switching
911401721602	RS378B P33 940 PSU-E WB M87	Not applicable	No
911401536871	RS378B P15 927 PSD-E MB M55	-	-
911401721262	RS378B P15 930 PSU-E NB M55	Not applicable	No
911401721272	RS378B P15 940 PSU-E NB M55	Not applicable	No

Order Code	Full Product Name	Maximum dim level	Suitable for random switching
911401721302	RS378B P15 940 PSU-E MB M55	Not applicable	No
911401721322	RS378B P15 930 PSU-E WB M55	Not applicable	No
911401721332	RS378B P15 940 PSU-E WB M55	Not applicable	No
911401721412	RS378B P15 930 PSR-E WB M55	10%	No

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.