



Extending the home feel onto the street

TownTune Asymmetric Lyre

As a luminaire family prepared for existing and scalable urban spaces, TownTune offers all the recent lighting innovations in terms of performance, quality of light and connectivity. The Philips TownTune family consists of three members: a central post top, an asymmetric spigot version and a version using an extending lyre post top bracket. Each of these three can be customized with a choice of different shapes for housing and an optional of decorative ring which comes in two colors. By having these options available you can create your very own lighting signature and give distinctive identity to districts and cities. The luminaire family is also equipped with the QR code-based Philips Service tag, which supports installation and maintenance work and enables you to create your digital library of lighting assets and spare parts. TownTune also makes use of the Philips Ledgine optimized lighting platform ensuring that you always have the right amount and direction of light on your street. Furthermore, thanks to being SR (System Ready), TownTune is also future-proof and is ready to be paired with both standalone and advanced control and lighting software applications such as Interact City.

Benefits

- Delivers visual comfort, and comfortable lighting experiences in urban spaces through its dedicatedly designed bowl
- Simple, pure design making it possible to integrate it into various urban environments and the option for customization through a wide range of accessories, lets cities create a unique light signature, which can also become part of the urban furniture in daytime
- Wide application coverage and offers great performance by using the latest Ledgine LED platform and providing access to a wide range of light distributions
- Ease of serviceability thanks to the Philips Service tag and ready to be paired with lighting control and software applications, by being equipped with the Philips SR (System Ready) socket

TownTune Asymmetric Lyre

Features

- Optimized Total Cost of Ownership and option of CLO (Constant Light Output)
- Excellent quality of light enabled by the Philips Ledgine optimized platform, and further optimization in L-Tune is also possible
- Choice of different shapes for housing (cone, dome), option of decorative ring and color (clear and golden)
- Ready to be paired with standalone lighting controls such as LumiStep, DynaDimmer, and LineSwitch and advanced system and software application such as Interact City
- Wide choice of lumen packages, ranging from 600 to 12,000 lumens
- Choice of color temperature: 3000 K (warm white) or 4000 K (neutral white)
- Long lifetime of 100,000 hours at minimum L80
- Suitable for new and retrofit installations
- IK08, IP66

Application

- Urban and residential areas
- City centers and main streets
- Cycle paths, footpaths and pedestrian crossings
- Car parks

Versions



BDP270, TownTune with lyre

Product details



The cable is masked in the Lyre bracket by an easy to install plastic strip



Interact ready, motion sensor installed on bottom SR socket.

TownTune Asymmetric Lyre

Product details




Connection and maintenance by opening the bowl (6 screws) and taking out the white frame.



Interact ready, CityTouch OLC for communication installed on SR socket.



Louver for obtrusive backlight available. Can also be used as retrofit.



By removing the six break-outs from the bowl, the decorative ring can be installed using a bayonet motion.



Dedicated designed bowl, virtually flat, with a unique internal texturing pattern for optimized visual comfort and a general feeling of well-being.

TownTune Asymmetric Lyre

Application Conditions

Maximum dim level 10%

Approval and Application

Mech. impact protection code IK09
 Surge Protection (Common/Differential) Philips standard surge protection level

Controls and Dimming

Dimmable Yes

General Information

CE mark CE mark
 Optical cover/lens type Polycarbonate bowl/cover UV-resistant
 Driver included Yes
 ENEC mark ENEC mark
 Flammability mark For mounting on normally flammable surfaces
 Light source replaceable Yes
 Number of gear units 1 unit
 Product Family Code BDP270

Light Technical

Standard tilt angle side entry -
 Standard tilt angle posttop 0°
 Upward light output ratio 0

Mechanical and Housing

Color Dark gray

General Information

Order Code	Full Product Name	Luminaire light beam spread	Light source color	Lamp	Optic type
				family code	
912300024206	BDP270 LED40-4S/830	6° - 79° × 154°	830 warm	LED40	Distribution medium 50
	DM50 CLO DDF3 62P				
912300024210	BDP270 LED12-4S/740	12° - 59° × 158°	740 neutral	LED120	Distribution narrow 10
	DN10 CLO SRT SRB 62P				

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial luminous flux
912300024206	BDP270	3000 K	>80	2812 lm
	LED40-4S/830			
	DM50 CLO DDF3 62P			

Order Code	Full Product Name	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial luminous flux
912300024210	BDP270	4000 K	>70	897 lm
	LED12-4S/740 DN10			
	CLO SRT SRB 62P			

TownTune Asymmetric Lyre

