



# Extending the home feel onto the street

## TownTune Asymmetric Lyre DTD

As a luminaire family prepared for existing and scalable urban spaces, TownTune offers all the recent lighting innovations in terms of performance, quality of light and connectivity. The Philips TownTune family consists of three members: a central post top, an asymmetric spigot version and a version using an extending lyre post-top bracket. Each of these three can be customised with a choice of different shapes for housing and an optional decorative ring which comes in two colours. By having these options available, you can create your very own lighting signature and give a distinctive identity to districts and cities. The luminaire family is also equipped with the QR code-based Philips Service tag, which supports installation and maintenance work and enables you to create a digital library of lighting assets and spare parts. TownTune also makes use of the Philips Ledgine optimised lighting platform, ensuring that you always have the right amount and direction of light on your street. Furthermore, thanks to being SR (System-Ready), TownTune is also future-proof and is ready to be paired with both standalone and advanced control and lighting software applications, such as Interact City.

### Benefits

- Delivers visual comfort, and comfortable lighting experiences in urban spaces through its dedicatedly designed bowl
- A simple, pure design, making it possible to integrate it into various urban environments and the option for customisation through a wide range of accessories, lets cities create a unique light signature, which can also become part of the urban furniture in the daytime
- Wide application coverage and offers great performance by using the latest Ledgine LED platform and providing access to a wide range of light distributions
- Ease of serviceability thanks to the Philips Service tag, and ready to be paired with lighting control and software applications by being equipped with the Philips SR (System Ready) socket

# TownTune Asymmetric Lyre DTD

## Features

- Optimised Total Cost of Ownership and option of CLO (Constant Light Output)
- Excellent quality of light enabled by the Philips Ledgine optimised platform, and further optimisation in L-Tune is also possible
- Choice of different shapes for housing (cone, dome), option of decorative ring and colours (clear and golden)
- Ready to be paired with standalone lighting controls such as LumiStep, DynaDimmer and LineSwitch, and advanced system and software applications, such as Interact City
- Wide choice of lumen packages, ranging from 600 to 12,000 lumens
- Choice of colour temperature: 3,000 K (warm white) or 4,000 K (neutral white)
- Long lifetime of 100,000 hours at minimum L80
- Suitable for new and retrofit installations
- IK08, IP66

## Application

- Urban and residential areas
- City centres and high streets
- Cycle paths, footpaths and pedestrian crossings
- Car parks

## Versions



## Product details



# TownTune Asymmetric Lyre DTD

## Product details



# TownTune Asymmetric Lyre DTD

## Application Conditions

Maximum dim level	10%
-------------------	-----

## Approval and Application

Mech. impact protection code	IK09
Surge Protection (Common/Differential)	Philips standard surge protection level kV

## Controls and Dimming

Dimmable	Yes
----------	-----

## General Information

CE mark	CE mark
Optical cover/lens type	PC-UV
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	F
Light source replaceable	Yes
Number of gear units	1 unit
Product Family Code	BDP273

## Light Technical

Standard tilt angle side entry	-
Standard tilt angle posttop	0°
Upward light output ratio	0

## Mechanical and Housing

Colour	Dark Grey
--------	-----------

## General Information

Order Code	Full Product Name	Luminaire light beam spread	Light source colour	Lamp family code	Optic type
49768200	BDP273 LED30-4S/740 DW50 DR-GO CLO DDF1	6° - 18° × 133°	740 neutral white	LED30	Distribution wide 50
49772900	BDP273 LED74-4S/830 DW10 CLO SRT SRB 62P	7° - 52° × 150°	830 warm white	LED74	Distribution wide 10

## Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Colour		
		Init. Corr. Colour Temperature	Rendering Index	Initial luminous flux
49768200	BDP273 LED30-4S/740 DW50 DR-GO CLO DDF1	4000 K	>70	2128 lm

Order Code	Full Product Name	Init. Colour		
		Init. Corr. Colour Temperature	Rendering Index	Initial luminous flux
49772900	BDP273 LED74-4S/830 DW10 CLO SRT SRB 62P	3000 K	>80	5120 lm

