



The ultra-thin downlight for general lighting applications with limited build-in height

Greenup Slim Downlight

Greenup Slim downlight is ultra-thin product for general lighting applications with limited build-in height, which is suitable for a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, cut out size, color temp and dimming option (ETO approach).

Benefits

- Compact design for better integration with the building
- Comfortable light with high efficiency
- Reliable performance for indoor applications
- Connected lighting and future-proof smart technology

Features

- Lumen package: 600lm, 1000lm, 1500lm, 2100lm
- Cut out size: 3", 5", 6", 8"
- CCT: 3000K / 4000K
- CRI: 80
- On/off (DALI, 1-10V ETO)
- Lifetime: 50,000hours L70 Ta 25°C

Greenup Slim Downlight

Application

- Office Building
- Retail
- Hospitality

Versions



Greenup Slim downlight

Greenup Slim Downlight

Application Conditions

Ambient temperature range	-20 to +40 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Approval and Application

Mech. impact protection code	IK02
Ingress protection code	IP20

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

General Information

Beam angle of light source	- °
Protection class IEC	Safety class II
Optical cover/lens type	Polycarbonate Diffuser
Driver included	Yes
ENEC mark	-
Flammability mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
Number of gear units	1 unit
Optic type	-

Initial Performance (IEC Compliant)

Initial chromaticity	SDCM<5
Init. Color Rendering Index	>80
Initial LED luminaire efficacy	95 lm/W
Luminous flux tolerance	+/-10%

Mechanical and Housing

Color	White
-------	-------

Over Time Performance (IEC Compliant)

Median useful life L80B50	35000 h
Median useful life L90B50	16000 h

General Information

Order Code	Full Product Name	CE mark
911401802780	DN150B LED6S 830 PSU GC	-
911401802880	DN150B LED6S 840 PSU GC	-
911401802980	DN150B LED6S 830 PSU GM	CE mark
911401803080	DN150B LED6S 840 PSU GM	CE mark
911401803180	DN150B LED10S 830 PSU GC	-
911401803280	DN150B LED10S 840 PSU GC	-
911401803380	DN150B LED10S 830 PSU GM	CE mark
911401803480	DN150B LED10S 840 PSU GM	CE mark
911401803580	DN150B LED15S 830 PSU GC	-
911401803680	DN150B LED15S 840 PSU GC	-
911401803780	DN150B LED15S 830 PSU GM	CE mark
911401803880	DN150B LED15S 840 PSU GM	CE mark
911401803980	DN150B LED20S 830 PSU GC	-
911401804080	DN150B LED20S 840 PSU GC	-
911401804180	DN150B LED20S 830 PSU GM	CE mark
911401804280	DN150B LED20S 840 PSU GM	CE mark

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401802780	DN150B LED6S 830 PSU GC	3000 K	650 lm	6.5 W
911401802880	DN150B LED6S 840 PSU GC	4000 K	650 lm	6.5 W
911401802980	DN150B LED6S 830 PSU GM	3000 K	650 lm	6.5 W
911401803080	DN150B LED6S 840 PSU GM	4000 K	650 lm	6.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401803180	DN150B LED10S 830 PSU GC	3000 K	1000 lm	11 W
911401803280	DN150B LED10S 840 PSU GC	4000 K	1000 lm	11 W
911401803380	DN150B LED10S 830 PSU GM	3000 K	1000 lm	11 W
911401803480	DN150B LED10S 840 PSU GM	4000 K	1000 lm	11 W

Greenup Slim Downlight

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401803580	DN150B LED15S 830 PSU GC	3000 K	1500 lm	15 W
911401803680	DN150B LED15S 840 PSU GC	4000 K	1500 lm	15 W
911401803780	DN150B LED15S 830 PSU GM	3000 K	1500 lm	15 W
911401803880	DN150B LED15S 840 PSU GM	4000 K	1500 lm	15 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
911401803980	DN150B LED20S 830 PSU GC	3000 K	2100 lm	21 W
911401804080	DN150B LED20S 840 PSU GC	4000 K	2100 lm	21 W
911401804180	DN150B LED20S 830 PSU GM	3000 K	2100 lm	21 W
911401804280	DN150B LED20S 840 PSU GM	4000 K	2100 lm	21 W

