

Project:	
Location:	
Cat.No:	
Туре:	
Lamps:	Qty:
Notes:	

Ordering guide

Series	Size	Mounting	Lamping
9630			
9630 Classics Step Cylinder	WH Matte White BK Matte Black	All Lytespan Track Systems	A19, PAR16 PAR30 75W Max

Features

- Lytespan attachment fitting: Die-cast zinc alloy.
- 2. Housing: .40" aluminum
- Step baffle: Compression-molded high heat phenolic with stepped conical surface for low brightness. Integral black finish.
- 4. **Lever:** Locks attachment fitting electrically and mechanically anywhere along the track.
- 5. **Movable brass Contact:** Extends for connection to 2nd circuit in Advent Lytespan Track.
- 6. **Swivel**: Die-cast zinc alloy. 350° horizontal adjustment.
- 7. **Pivot mounting:** Tensioned with built-in stop, provides 90° vertical adjustment.

Electrical


Porcelain socket, medium base, nickel plated screw shell. 4 No. 18 braided SF-1 leads

Finish

All painted finishes baked enamel.

Labels

UL, I.B.E.W.



example: 9630WH



© 2014 Koninklijke Philips N.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication. philips.com/luminaires



Philips Lighting, North America Corporation 200 Franklin Square Drive, Somerset, NJ 08873 Tel. 855-486-2216

Imported by: Philips Lighting, A division of Philips Electronics Ltd. 281 Hillmount Rd, Markham, ON, Canada L6C 2S3 Tel. 800-668-9008