LuxSpace G4 筒灯
DN590B PoE/ DN592B PoE
Mounting Instruction/ 安装说明

444100006871


III IP20


Type Number 产品型号	Lum. Power 整灯功率	Lamp Power 光源功率	Voltage 电压	kg
DN590B PoE	13.5W	12W	53Vdc	0.45
DN592B PoE	22.8W	21.6W	53Vdc	0.80

如需实现PoE Master灯具功能，需要另购配件 DN58X PoE sensor accessory。

I


Unit: mm
单位：毫米





Type Number 产品型号	Cut Out 开孔尺寸	A (mm)	B (mm)
DN590B POE	D125-130	137	90
DN592B POE	D152-157	162	100


Unit: mm
单位：毫米




PHILIPS


Philips Lighting (China) Investment Co., Ltd.
Address: Building No. 9, Lane 888, Tianlin Road, Minhang District, Shanghai, China
China Postal code: 200233
飞利浦照明(中国)投资有限公司
地址：中国上海市闵行区田林路888弄9号楼
邮编：200233


The maximum length of the cable to be 20 meters.
网线最大长度建议为20m。



Plug in RJ45 Ethernet wire（CAT5E or CAT6 cable）.
接上RJ45网线（超五类或者六类）。
Recommended Switch models:Cisco,WS-C3850-24U-L;
Huawei,S5720-16X-PWH-LI-AC
建议使用的Switch型号：思科，WS-C3850-24U-L；
华为，S5720-16X-PWH-LI-AC。







1. The luminaire shall be installed by a qualified electrician and wired in accordance with the latest IEE electrical regulations or the national requirements.
灯具应由有资格的电工安装，接线要符合IEE电气标准或国家标准。
2. The luminaire shall, under no circumstance, be covered with thermal insulation matting or similar material.
此灯具不适合被隔热衬垫或类似材料覆盖
3. Do not switch on before complete installation.
接线过程中，切勿通电。
4. For non-user replaceable light sources:
对非使用者替换光源:
The light source contained in this luminaire shall only be replaced by the manufacturer orhis service agent or a similar qualified person."
此灯具内的光源应由制造商或其服务代理商或一个有类似资格的人来更换。
5. The corrosive atmosphere or hazardous materials such as sulfur, chlorine, phthalate, etc must be avoided during the use and storage.
灯具避免在腐蚀性环境或者含有有害物质，例如硫化物，卤化物，邻苯二甲酸酯等环境中存储和使用。

Philips Lighting (China) Investment Co., Ltd.
Address: Building No. 9, Lane 888, Tianlin Road, Minhang District, Shanghai, China
China Postal code: 200233
飞利浦照明(中国)投资有限公司
地址：中国上海市闵行区田林路888弄9号楼
邮编：200233

PHILIPS