



# APX LED High Bay

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens

24,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens

The APX LED High Bay provides durability and high performance for your customer's demanding environments. With packages ranging from 8,000 to 24,000 nominal lumens, the APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs. The additional capability of dimming and optional sensors can ensure even more energy savings.

## Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Luminaire Input Watts	191
Voltages	120/208/240/277/347/480/UNIV V
Initial Performance (IEC Compliant)	
Luminaire Lumens	24000

Product Data	
Order product name	24,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens
Commercial Code	APX24LL40-UNV-LFP
Order code	APX24LL40-UNV-LFP
Catalog Number Description	24,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution, Frosted Polycarbonate Lens
Material Nr. (12NC)	DAY00008525