



SML Surface Modular LED

2x4, Surface, 4800 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse

2x4, Surface, 4800 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse

The Philips Day-Brite / Philips CFI Surface Modular LED luminaire is a shallow body, surface mounted premium grade luminaire with a variety of door frames and lens options available.

Product data

General Information		Initial Performance (IEC Compliant)	
Lamp Source Code	LED	Luminaire Lumens	4800
Color Temperature	4000K		
CRI	80		
Mounting	Surface Suspended		
Operating and Electrical		Product Data	
Luminaire Input Watts	39	Order product name	2x4, Surface, 4800 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse
Voltages	120/277/347/UNIV V	Commercial Code	2SML48L840-4-FS-02F-UNV
		Order code	2SML48L840-4-FS-02F-UNV
		Catalog Number Description	2x4, Surface, 4800 Nominal Delivered Lumens, 80 CRI, 4000K, Diffuse
		Service / Spec Smart	-
		Material Nr. (12NC)	DAY70000421
Mechanical and Housing			
Fixture Size	2 ft x 4 ft		
Shape	Rectangular		