



# ConTempo 150-250-350

## RVP250 MHN-TD150W IC 220V-50Hz A SP

MHN-TD, 150 W, Asymmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

#### **Product data**

General Information  Lamp family code MHN-TD  Cap-Base R7S [R7s]	
Can_Base P7S [P7s]	
Cap-base 11/3 [11/3]	
Gear CONV [Conventional]	
Light Technical	
Number of light sources 1	
Optic type outdoor Asymmetrical	
Operating and Electrical	
Input Voltage 220 V	
Line Frequency 50 Hz	
Power Consumption 150 W	

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Product Data	
Order product name	RVP250 MHN-TD150W IC 220V-50Hz A SP
Full product name	RVP250 MHN-TD150W IC 220V-50Hz A SP
Full product code	910401648580
Order code	910401648580
Material Nr. (12NC)	910401648580
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Datasheet, 2023, April 29 data subject to change

# ConTempo 150-250-350

## Dimensional drawing



