



EFix TCS260

TCS260 2x49W/830 HFD-T D6 ACL PVCFR WH

EFix surface mounted, 2, 49 W, 830 warm white, HF DALI touch-switch dimming, Semi-high-gloss optic double parabolic, ActiLume. White

The EFix TL5 luminaire range is a dedicated, affordable choice of innovative lighting that enables massive energy savings to be made when old electromagnetic installations are replaced by the latest Philips technology. The range's optical performance complies with the latest EN-12464 norms, ensuring improved lighting quality in every application. Used in combination with high-frequency gear, Philips MASTER TL5 lamps enable substantial energy savings to be made. These savings can be further increased by using a Luxsense daylight controller integrated into the luminaire. The practical design of EFix combines both surface-mounted (TCS260) and suspended (TPS262) luminaires in one design. Thanks to the luminaire's easily removable top cover, the beam can be adjusted to provide direct or direct/indirect lighting. EFix is supplied with lamps and is ready to install, minimizing installation time. EFix recessed TBS260 completes Philips' range of luminaires for general lighting applications in offices and shops.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	HFD-T [HF DALI touch-switch dimming]
Product family code	TCS260 [EFix surface mounted]
Value ladder	Performance
Embedded control	ActiLume
CE mark	Yes
Flammability mark	For mounting on normally flammable surfaces

Light Technical			
Number of light sources	2		
Light source color	830 warm white		
Optic type	Semi-high-gloss optic double parabolic		
Optical cover type	-		
Operating and Electrical			
Input Voltage	220 to 240 V		


Datasheet, 2023, September 4 data subject to change


EFix TCS260

Power Consumption	49 W
Mechanical and Housing	
Fixation point length distance (Nom)	1,300 mm
Housing Color	White
Overall length	1,541 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I
Application Conditions	
Suitable for random switching	Not applicable

Product Data			
Order product name	TCS260 2x49W/830 HFD-T D6 ACL PVCFR WH		
Full product name	TCS260 2x49W/830 HFD-T D6 ACL PVCFR WH		
Full product code	872790062191400		
Order code	910402299112		
Material Nr. (12NC)	910402299112		
Numerator - Quantity Per Pack	1		
EAN/UPC - Product/Case	8727900621914		
Numerator - Packs per outer box	1		
EAN/UPC - Case	8727900621914		

Dimensional drawing





Product	Α	В	С
TCS260 2x49W/830 HFD-T D6 ACL PVCFR WH	1,300 mm	650 mm	1,541 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.